SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity rx2620 (1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp®2006 = 15.8

SPECfp_base2006 = 15.2

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Sep-2006
Hardware Availability: Sep-2006
Software Availability: Sep-2006



Hardware

CPU Name:	Dual-Core Intel Itanium 2 9040
CPU Characteristics:	1.6GHz/18MB, 400MHz FSB
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1-2 chips
Primary Cache:	16 KB I + 16 KB D on chip per core
Secondary Cache:	1 MB I + 256 KB D on chip per core

Continued on next page

Software

Operating System:	HPUX11i-TCOE B.11.23.0609
Compiler:	HP C/aC++ Developer's Bundle C.11.23.12 HP Fortran90 Compiler B.11.23.32
Auto Parallel:	No
File System:	vxfs
System State:	Multi-user
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity rx2620 (1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp2006 = 15.8

SPECfp_base2006 = 15.2

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Sep-2006
Hardware Availability: Sep-2006
Software Availability: Sep-2006

L3 Cache: 9 MB I+D on chip per core
Other Cache: None
Memory: 24 GB (12x2GB DIMMs)
Disk Subsystem: 36GB 15K RPM SCSI
Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	459	29.6	459	29.6	**459**	**29.6**	459	29.6	459	29.6	**459**	**29.6**
416.gamess	2237	8.75	**2236**	**8.76**	2236	8.76	**2133**	**9.18**	2133	9.18	2135	9.17
433.milc	**684**	**13.4**	684	13.4	683	13.4	**628**	**14.6**	628	14.6	629	14.6
434.zeusmp	581	15.7	581	15.7	**581**	**15.7**	581	15.7	581	15.7	**581**	**15.7**
435.gromacs	515	13.9	**515**	**13.9**	515	13.9	**454**	**15.7**	454	15.7	455	15.7
436.cactusADM	391	30.6	391	30.6	**391**	**30.6**	391	30.6	391	30.6	**391**	**30.6**
437.leslie3d	**600**	**15.7**	601	15.7	600	15.7	**600**	**15.7**	601	15.7	600	15.7
444.namd	304	26.4	**304**	**26.4**	304	26.4	304	26.4	**304**	**26.4**	304	26.4
447.dealII	561	20.4	**561**	**20.4**	561	20.4	561	20.4	**561**	**20.4**	561	20.4
450.soplex	991	8.42	**991**	**8.41**	992	8.41	858	9.72	859	9.71	**859**	**9.71**
453.povray	**592**	**8.99**	592	8.98	592	8.99	485	11.0	**485**	**11.0**	485	11.0
454.calculix	580	14.2	**581**	**14.2**	581	14.2	580	14.2	**581**	**14.2**	581	14.2
459.GemsFDTD	989	10.7	**990**	**10.7**	990	10.7	922	11.5	**923**	**11.5**	924	11.5
465.tonto	1027	9.59	**1027**	**9.58**	1027	9.58	982	10.0	983	10.0	**983**	**10.0**
470.lbm	**683**	**20.1**	683	20.1	682	20.1	**683**	**20.1**	683	20.1	682	20.1
481.wrf	771	14.5	771	14.5	**771**	**14.5**	771	14.5	771	14.5	**771**	**14.5**
482.sphinx3	**1036**	**18.8**	1036	18.8	1036	18.8	993	19.6	996	19.6	**995**	**19.6**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
The system had the September 2006 HP-UX 11i v2 Technical Computing
Operating Environment (TCOE) and compilers installed, along with
the following patches:

PHSS_34858  linker + fdp cumulative patch
PHSS_34853  Math Library Cumulative Patch
PHSS_34854  Integrity Unwind Library
PHSS_34855  HP C Compiler (A.06.12)
PHSS_34856  aC++ Compiler (A.06.12)
PHSS_34857  u2comp/be/plugin library patch
PHSS_34395  FORTRAN I/O Library [libIO77]
PHSS_34397  FORTRAN Intrinsics [libF90 B.11.23.17]
PHSS_34399  Fortran Product Patch, v3.1 to v3.1.1
PHKL_34020  Perfmon enhancements and Itanium Dual-Core
```

Continued on next page

Operating System Notes (Continued)

```
The following kernel tunables were set, in addition to the defaults
set by the Technical Computing OE:

dbc_max_pct=20
dbc_min_pct=20
maxdsiz=3221225472
maxssiz=401604608
```

Platform Notes

```
The "cpuconfig" EFI command was used prior to booting
  to deconfigure processors.

Although two cores were enabled during testing,
  the SPEC CPU2006 benchmarks used only one core.
```

Base Compiler Invocation

C benchmarks:
```
/opt/ansic/bin/cc -Ae
```

C++ benchmarks:
```
/opt/aCC/bin/aCC -Aa
```

Fortran benchmarks:
```
/opt/fortran90/bin/f90
```

Benchmarks using both Fortran and C:
```
/opt/ansic/bin/cc -Ae /opt/fortran90/bin/f90
```

Base Portability Flags

453.povray: `-DSPEC_CPU_NEED_INVHYP`
454.calculix: `-DSPEC_CPU_NOZMODIFIER`
481.wrf: `-DNOUNDERSCORE +noppu`

Base Optimization Flags

C benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
```

C++ benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
```

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
+Ofaster -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M -Wl,-N

Benchmarks using both Fortran and C:
+Ofaster(-hp_cc) +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Ofaster(-hp_f90) -Wl,-N

Peak Compiler Invocation

C benchmarks:
/opt/ansic/bin/cc -Ae

C++ benchmarks:
/opt/aCC/bin/aCC -Aa

Fortran benchmarks:
/opt/fortran90/bin/f90

Benchmarks using both Fortran and C:
/opt/ansic/bin/cc -Ae /opt/fortran90/bin/f90

Peak Portability Flags

453.povray: -DSPEC_CPU_NEED_INVHYP
454.calculix: -DSPEC_CPU_NOZMODIFIER
481.wrf: -DNOUNDERSCORE +noppu

Peak Optimization Flags

C benchmarks:

433.milc: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap -Wl,-N

470.lbm: basepeak = yes

482.sphinx3: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap

Continued on next page

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap -Wl,-N

453.povray: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: +Ofaster -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Odataprefetch=direct -Wl,-N

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Odataprefetch=direct -Wl,-N

465.tonto: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Odataprefetch=direct

Benchmarks using both Fortran and C:

435.gromacs: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster(-hp_cc) +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap +Ofaster(-hp_f90)

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.06.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.06.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:06:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 October 2006.