SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3400 (Intel Xeon E5335)

SPECfp®_rate2006 = Not Run

SPECfp_rate_base2006 = 48.8

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jan-2007
Hardware Availability: Feb-2007
Software Availability: Aug-2006



Hardware

CPU Name:	Intel Xeon E5335
CPU Characteristics:	1066MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20060816 Intel Fortran Compiler for IA32 version 9.1 Build no 20060816 Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3400 (Intel Xeon E5335)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 48.8

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jan-2007
Hardware Availability: Feb-2007
Software Availability: Aug-2006

L3 Cache: None
Other Cache: None
Memory: 8 GB (8 x 1GB DDR2-5300F ECC)
Disk Subsystem: 1 x 80 GB SATA, 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32-bit
Peak Pointers: Not Applicable
Other Software: Smart Heap Library, Version 8

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3441	31.6	3443	31.6	**3443**	**31.6**							
416.gamess	8	**1657**	**94.5**	1657	94.5	1657	94.5							
433.milc	8	3628	20.2	3630	20.2	**3629**	**20.2**							
434.zeusmp	8	1262	57.7	1254	58.0	**1258**	**57.9**							
435.gromacs	8	635	89.9	**635**	**89.9**	634	90.1							
436.cactusADM	8	1476	64.8	1474	64.9	**1474**	**64.9**							
437.leslie3d	8	3223	23.3	3231	23.3	**3229**	**23.3**							
444.namd	8	795	80.7	795	80.7	**795**	**80.7**							
447.dealII	8	986	92.8	**976**	**93.8**	969	94.4							
450.soplex	8	2267	29.4	**2270**	**29.4**	2270	29.4							
453.povray	8	379	112	**379**	**112**	379	112							
454.calculix	8	**917**	**72.0**	916	72.1	918	71.9							
459.GemsFDTD	8	3882	21.9	**3889**	**21.8**	3905	21.7							
465.tonto	8	**1491**	**52.8**	1488	52.9	1497	52.6							
470.lbm	8	4375	25.1	4377	25.1	**4377**	**25.1**							
481.wrf	8	2006	44.6	**1999**	**44.7**	1999	44.7							
482.sphinx3	8	3381	46.1	3392	46.0	**3390**	**46.0**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on an IBM System X 3400.   IBM System X 3400 and IBM System
X 3500 are electronically equivalent.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc7.1 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DBOOST_NO_INTRINSIC_WCHAR_T
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:
-fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-fast -Qcxx_features /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:
-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:
-fast /F950000000 -link /FORCE:MULTIPLE

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:13:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 February 2007.