SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL480c
(1.86 GHz, Intel Xeon processor E5320)

SPECfp®_rate2006 = 26.0

SPECfp_rate_base2006 = 25.6

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon E5320
CPU Characteristics:	1.86 GHz, 2x4 MB L2 shared, 1066 MHz system bus
CPU MHz:	1860
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	SuSE Linux Enterprise Server 10 (x86_64) kernel 2.6.16.21-0.8-smp
Compiler:	Intel C++ Compiler for Intel EM64T-based applications, Version 9.1 Build 20061101, Package ID: l_cc_c_9.1.045 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1 Build 20061101, Package ID: l_fc_c_9.1.040
Auto Parallel:	No

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL480c
(1.86 GHz, Intel Xeon processor E5320)

SPECfp_rate2006 = 26.0

SPECfp_rate_base2006 = 25.6

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006

L3 Cache:	None	File System:	ext2
Other Cache:	None	System State:	Multi-user run level 3
Memory:	16 GB (8x2 GB PC2-5300F CL5)	Base Pointers:	64-bit
Disk Subsystem:	1x72 GB 10k SAS	Peak Pointers:	32/64-bit
Other Hardware:	None	Other Software:	None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	**3042**	**17.9**	3048	17.8	3042	17.9	4	3041	17.9	**3044**	**17.9**	3045	17.9
416.gamess	4	1528	51.3	**1528**	**51.3**	1528	51.2	4	**1659**	**47.2**	1656	47.3	1669	46.9
433.milc	4	**3041**	**12.1**	3039	12.1	3041	12.1	4	3005	12.2	3003	12.2	**3003**	**12.2**
434.zeusmp	4	**1292**	**28.2**	1286	28.3	1297	28.1	4	1324	27.5	**1316**	**27.7**	1314	27.7
435.gromacs	4	641	44.6	**639**	**44.7**	639	44.7	4	**620**	**46.1**	620	46.1	618	46.2
436.cactusADM	4	1439	33.2	**1442**	**33.1**	1454	32.9	4	**1478**	**32.3**	1476	32.4	1478	32.3
437.leslie3d	4	3025	12.4	**3040**	**12.4**	3046	12.3	4	3043	12.4	3040	12.4	**3042**	**12.4**
444.namd	4	**820**	**39.1**	820	39.1	821	39.1	4	833	38.5	**832**	**38.5**	832	38.6
447.dealII	4	904	50.6	**904**	**50.6**	900	50.8	4	850	53.8	**882**	**51.9**	887	51.6
450.soplex	4	2090	16.0	**2093**	**15.9**	2099	15.9	4	**2089**	**16.0**	2089	16.0	2089	16.0
453.povray	4	**414**	**51.4**	413	51.5	415	51.2	4	**316**	**67.4**	316	67.4	315	67.6
454.calculix	4	885	37.3	877	37.6	**879**	**37.5**	4	856	38.5	868	38.0	**865**	**38.2**
459.GemsFDTD	4	3682	11.5	3674	11.6	**3680**	**11.5**	4	**3682**	**11.5**	3676	11.5	3683	11.5
465.tonto	4	1220	32.3	1234	31.9	**1226**	**32.1**	4	1192	33.0	1189	33.1	**1191**	**33.0**
470.lbm	4	4578	12.0	**4578**	**12.0**	4577	12.0	4	4576	12.0	**4576**	**12.0**	4590	12.0
481.wrf	4	1896	23.6	**1892**	**23.6**	1890	23.6	4	1898	23.5	1878	23.8	**1889**	**23.7**
482.sphinx3	4	3253	24.0	**3251**	**24.0**	3248	24.0	4	3231	24.1	3236	24.1	**3232**	**24.1**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch Disabled in BIOS.
"/usr/bin/taskset" used to bind processes to CPUs.
Environment stack size set to 'unlimited'
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks:
icc

Continued on next page

Peak Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

C++ benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Fortran benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/hp-ic91-flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/hp-ic91-flags.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:43:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 March 2007.