SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor E5345, 2.33 GHz)

SPECfp®_rate2006 = Not Run

SPECfp_rate_base2006 = 55.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Dec-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon E5345
CPU Characteristics:	1333 MHz Bus Speed
CPU MHz:	2333
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	SuSE Linux Enterprise Server 10 EM64T kernel 2.6.16.21-0.8-smp
Compiler:	Intel C++ Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_cc_c_9.1.045 Build no 20061101 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_fc_c_9.1.040 Build no 20061101
Auto Parallel:	No

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor E5345, 2.33 GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 55.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Dec-2006
Software Availability: Nov-2006

L3 Cache:	None	File System:	ext2
Other Cache:	None	System State:	Multi-user run level 3
Memory:	16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)	Base Pointers:	64-bit
Disk Subsystem:	1 x 73 GB SAS 15k RPM	Peak Pointers:	Not Applicable
Other Hardware:	None	Other Software:	None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3440	31.6	3438	31.6	**3439**	**31.6**							
416.gamess	8	1227	128	1230	127	**1228**	**128**							
433.milc	8	**2497**	**29.4**	2496	29.4	2499	29.4							
434.zeusmp	8	1260	57.8	**1255**	**58.0**	1251	58.2							
435.gromacs	8	536	106	**537**	**106**	539	106							
436.cactusADM	8	1445	66.2	1454	65.8	**1447**	**66.1**							
437.leslie3d	8	3247	23.2	**3244**	**23.2**	3226	23.3							
444.namd	8	660	97.2	**660**	**97.1**	661	97.1							
447.dealII	8	**812**	**113**	814	112	807	113							
450.soplex	8	2099	31.8	2104	31.7	**2104**	**31.7**							
453.povray	8	320	133	**320**	**133**	323	132							
454.calculix	8	745	88.5	**741**	**89.1**	738	89.5							
459.GemsFDTD	8	3609	23.5	3613	23.5	**3609**	**23.5**							
465.tonto	8	1125	70.0	1126	69.9	**1125**	**70.0**							
470.lbm	8	**4586**	**24.0**	4610	23.8	4586	24.0							
481.wrf	8	2015	44.4	**2017**	**44.3**	2027	44.1							
482.sphinx3	8	3225	48.4	**3228**	**48.3**	3229	48.3							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Hardware Prefetcher disabled in BIOS
Adjacent Cache Line Prefetch disabled in BIOS
"ulimit -s unlimited" set
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/dell-ic91-flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/dell-ic91-flags.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor E5345, 2.33 GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 55.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Dec-2006
Software Availability: Nov-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:04:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 April 2007.