SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5160, 3.0 GHz

SPECfp®_rate2006 = 45.5

SPECfp_rate_base2006 = 44.0

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007



Hardware

CPU Name:	Intel Xeon 5160
CPU Characteristics:	1333 MHz system bus
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip

Continued on next page

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler:	Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l_fc_p_9.1.043
Auto Parallel:	No
File System:	ext2

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor 5160, 3.0 GHz

SPECfp_rate2006 = 45.5

SPECfp_rate_base2006 = 44.0

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem: SAS (73GB 15400 rpm)
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1557	34.9	1556	34.9	**1556**	**34.9**	4	1557	34.9	1556	34.9	**1556**	**34.9**
416.gamess	4	956	81.9	**956**	**82.0**	956	82.0	4	956	81.9	**956**	**82.0**	956	82.0
433.milc	4	1626	22.6	**1614**	**22.8**	1612	22.8	4	**1664**	**22.1**	1665	22.1	1664	22.1
434.zeusmp	4	764	47.6	766	47.5	**765**	**47.6**	4	767	47.5	764	47.6	**765**	**47.6**
435.gromacs	4	399	71.7	**399**	**71.5**	404	70.7	4	386	74.0	**387**	**73.8**	388	73.6
436.cactusADM	4	892	53.6	897	53.3	**892**	**53.6**	4	892	53.6	897	53.3	**892**	**53.6**
437.leslie3d	4	1540	24.4	1544	24.4	**1542**	**24.4**	4	1540	24.4	1544	24.4	**1542**	**24.4**
444.namd	4	511	62.7	516	62.2	**512**	**62.7**	4	511	62.7	516	62.2	**512**	**62.7**
447.dealII	4	532	86.1	538	85.0	**535**	**85.6**	4	**527**	**86.9**	522	87.7	527	86.9
450.soplex	4	**1182**	**28.2**	1178	28.3	1183	28.2	4	1096	30.4	1102	30.3	**1101**	**30.3**
453.povray	4	260	81.9	**260**	**81.8**	262	81.2	4	197	108	**197**	**108**	199	107
454.calculix	4	553	59.7	**552**	**59.8**	550	60.0	4	**540**	**61.2**	541	61.0	539	61.2
459.GemsFDTD	4	1895	22.4	**1905**	**22.3**	1911	22.2	4	1895	22.4	**1905**	**22.3**	1911	22.2
465.tonto	4	733	53.7	**736**	**53.5**	737	53.4	4	713	55.2	**717**	**54.9**	719	54.8
470.lbm	4	**2902**	**18.9**	2902	18.9	2901	18.9	4	**2665**	**20.6**	2665	20.6	2666	20.6
481.wrf	4	**1015**	**44.0**	1015	44.0	1014	44.1	4	**1015**	**44.0**	1015	44.0	1014	44.1
482.sphinx3	4	**1934**	**40.3**	1935	40.3	1922	40.6	4	1802	43.3	**1799**	**43.3**	1796	43.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

General Notes

```
The system bus runs at 1333 MHz

All binaries were built with 64-bit Intel compiler except:
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers in your country please see:
```

Continued on next page

General Notes (Continued)

http://www.fujitsu-siemens.com/countries

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
`-fast`

Peak Compiler Invocation

C benchmarks:
`/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `/opt/intel/cc/9.1.047/bin/icpc -I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib`

Fortran benchmarks (except as noted below):
`ifort`

434.zeusmp: `/opt/intel/fc/9.1.043/bin/ifort -I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib`

Benchmarks using both Fortran and C:
`icc ifort`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

Continued on next page

Peak Optimization Flags (Continued)

433.milc: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

470.lbm: `Same as 433.milc`

482.sphinx3: `-fast`

C++ benchmarks:

444.namd: `basepeak = yes`

447.dealII: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

450.soplex: `Same as 447.dealII`

453.povray: `Same as 447.dealII`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `basepeak = yes`

434.zeusmp: `-fast`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `basepeak = yes`

465.tonto: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

Benchmarks using both Fortran and C:

435.gromacs: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

436.cactusADM: `basepeak = yes`

454.calculix: `Same as 435.gromacs`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:39:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.