SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp®_rate2006 = 37.3

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007



Hardware

CPU Name:	Intel Xeon 5130
CPU Characteristics:	1333 MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip

Continued on next page

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler:	Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l_fc_p_9.1.043
Auto Parallel:	No
File System:	ext2

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.3

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem: SAS (73GB 15400 rpm)
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1634	33.3	1632	33.3	**1633**	**33.3**	4	1634	33.3	1632	33.3	**1633**	**33.3**
416.gamess	4	1436	54.6	1433	54.7	**1434**	**54.6**	4	1436	54.6	1433	54.7	**1434**	**54.6**
433.milc	4	1678	21.9	**1678**	**21.9**	1684	21.8	4	**1769**	**20.8**	1769	20.8	1763	20.8
434.zeusmp	4	939	38.8	**943**	**38.6**	951	38.3	4	942	38.6	936	38.9	**937**	**38.9**
435.gromacs	4	590	48.4	**589**	**48.5**	588	48.6	4	576	49.6	572	49.9	**573**	**49.8**
436.cactusADM	4	**1049**	**45.6**	1049	45.6	1044	45.8	4	**1049**	**45.6**	1049	45.6	1044	45.8
437.leslie3d	4	1599	23.5	1617	23.3	**1613**	**23.3**	4	1599	23.5	1617	23.3	**1613**	**23.3**
444.namd	4	766	41.9	**765**	**41.9**	765	41.9	4	766	41.9	**765**	**41.9**	765	41.9
447.dealII	4	**698**	**65.5**	701	65.3	698	65.6	4	685	66.8	**685**	**66.8**	689	66.4
450.soplex	4	1267	26.3	**1266**	**26.4**	1261	26.5	4	1177	28.3	1173	28.4	**1175**	**28.4**
453.povray	4	389	54.7	**389**	**54.7**	392	54.2	4	295	72.2	296	71.9	**295**	**72.0**
454.calculix	4	**793**	**41.6**	790	41.8	794	41.6	4	764	43.2	**769**	**42.9**	770	42.9
459.GemsFDTD	4	1947	21.8	2003	21.2	**1964**	**21.6**	4	1947	21.8	2003	21.2	**1964**	**21.6**
465.tonto	4	988	39.9	**988**	**39.8**	989	39.8	4	959	41.1	961	41.0	**959**	**41.0**
470.lbm	4	2996	18.3	2999	18.3	**2998**	**18.3**	4	2816	19.5	2813	19.5	**2815**	**19.5**
481.wrf	4	1133	39.4	1139	39.2	**1133**	**39.4**	4	1133	39.4	1139	39.2	**1133**	**39.4**
482.sphinx3	4	2119	36.8	2106	37.0	**2108**	**37.0**	4	1969	39.6	1974	39.5	**1971**	**39.5**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

General Notes

```
The system bus runs at 1333 MHz

All binaries were built with 64-bit Intel compiler except:
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path for include and library files.

This result was measured on the PRIMERGY RX300 S3. The PRIMERGY RX300 S3 and
```

Continued on next page

General Notes (Continued)

```
the PRIMERGY TX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
`-fast`

Benchmarks using both Fortran and C:
`-fast`

Peak Compiler Invocation

C benchmarks:
`/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `/opt/intel/cc/9.1.047/bin/icpc -I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib`

Fortran benchmarks (except as noted below):
`ifort`

434.zeusmp: `/opt/intel/fc/9.1.043/bin/ifort -I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib`

Benchmarks using both Fortran and C:
`icc ifort`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

433.milc: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

470.lbm: `Same as 433.milc`

482.sphinx3: `-fast`

C++ benchmarks:

444.namd: `basepeak = yes`

447.dealII: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

450.soplex: `Same as 447.dealII`

453.povray: `Same as 447.dealII`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `basepeak = yes`

434.zeusmp: `-fast`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `basepeak = yes`

465.tonto: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

Benchmarks using both Fortran and C:

435.gromacs: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

436.cactusADM: `basepeak = yes`

454.calculix: `Same as 435.gromacs`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:43:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.