SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

Fujitsu SPARC Enterprise M9000

SPECfp®_rate2006 = 600

SPECfp_rate_base2006 = 556

CPU2006 license: 19
Test sponsor: Fujitsu Limited
Tested by: Fujitsu Limited

Test date: May-2007
Hardware Availability: Apr-2007
Software Availability: May-2007



Hardware

CPU Name:	SPARC64 VI
CPU Characteristics:	
CPU MHz:	2280
FPU:	Integrated
CPU(s) enabled:	64 cores, 32 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1 to 8 CMUs; each CMU contains 2 or 4 chips
Primary Cache:	128 KB I + 128 KB D on chip per core
Secondary Cache:	5 MB I+D on chip per chip

Continued on next page

Software

Operating System:	Solaris 10 11/06
Compiler:	Sun Studio 12 (Early Access)
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

Fujitsu SPARC Enterprise M9000

SPECfp_rate2006 = 600

SPECfp_rate_base2006 = 556

CPU2006 license: 19
Test sponsor: Fujitsu Limited
Tested by: Fujitsu Limited

Test date: May-2007
Hardware Availability: Apr-2007
Software Availability: May-2007

L3 Cache: None
Other Cache: None
Memory: 256 GB (256 x 1 GB)
Disk Subsystem: 1095 GB RAID 0 using 15 x 73 GB, 10,000 RPM Fujitsu ETERNUS4000 Model 80
Other Hardware: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	127	2263	763	**2214**	**780**	2124	812	127	2263	763	**2214**	**780**	2124	812
416.gamess	127	**3996**	**622**	3994	623	3999	622	127	**3996**	**622**	3994	623	3999	622
433.milc	127	3267	357	3266	357	**3266**	**357**	127	2911	400	**2911**	**400**	2907	401
434.zeusmp	127	2501	462	2522	458	**2513**	**460**	127	**2503**	**462**	2498	463	2526	458
435.gromacs	127	1452	624	1453	624	**1453**	**624**	63	661	681	**661**	**680**	661	680
436.cactusADM	127	**1793**	**846**	1794	846	1791	847	127	1832	828	1790	848	**1792**	**847**
437.leslie3d	127	2249	531	2252	530	**2250**	**531**	127	**2174**	**549**	2178	548	2172	550
444.namd	127	**1699**	**600**	1697	600	1704	598	63	**808**	**625**	808	625	810	624
447.dealII	127	**1915**	**759**	1891	768	1934	751	127	1673	868	**1672**	**869**	1666	872
450.soplex	127	2969	357	2944	360	**2955**	**358**	127	2969	357	2944	360	**2955**	**358**
453.povray	127	1297	521	**1293**	**523**	1292	523	63	394	851	**394**	**850**	394	850
454.calculix	127	1504	697	**1476**	**710**	1475	711	127	1420	738	**1416**	**740**	1414	741
459.GemsFDTD	127	3543	380	3609	373	**3601**	**374**	127	3543	380	3609	373	**3601**	**374**
465.tonto	127	2028	616	2033	615	**2029**	**616**	63	**884**	**701**	892	695	884	701
470.lbm	127	**3473**	**502**	3473	503	3474	502	127	3337	523	**3337**	**523**	3337	523
481.wrf	127	2144	662	2147	661	**2144**	**662**	127	**2116**	**670**	2025	700	2125	668
482.sphinx3	127	5576	444	5544	446	**5548**	**446**	127	4703	526	**4715**	**525**	4720	524

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Processes were bound to cores using "submit" and "pbind".

 Shell Environment:
      Stack size set to unlimited via "ulimit -s unlimited"
      MPSSHEAP=4MB
      MPSSSTACK=4MB
      MADV=access_lwp
      LD_PRELOAD=mpss.so.1:madv.so.1


 System Tunables:
 (/etc/system parameters)
    maxphys=4194304
```

Continued on next page

Operating System Notes (Continued)

```
   Defines the maximum size of I/O requests, in bytes.
maxpgio=1024
   Defines the maximum number of page I/O requests that can
   be queued by the paging system.
tune_t_fsflushr=30
   Controls how many seconds elapse between runs of the
   page flush daemon, fsflush.
autoup=300
   Causes pages older than the listed number of seconds to
   be written by fsflush.
bufhwm=3000
   Memory byte limit for caching I/O buffers
segmap_percent=1
   Set maximum percent memory for file system cache
```

Platform Notes

```
"CMU" = CPU/Memory Unit; each holds 2 or 4 CPU chips.

Memory was 8-way interleaved by filling all slots with
the same capacity DIMMs.

This result was measured on a Fujitsu SPARC Enterprise
M9000 Server.  Note that the Fujitsu SPARC Enterprise
M9000 and Sun SPARC Enterprise M9000 are electrically
equivalent.
```

Base Compiler Invocation

C benchmarks:
```
/opt/SUNWspro12_EA070303/bin/cc
```

C++ benchmarks:
```
/opt/SUNWspro12_EA070303/bin/CC
```

Fortran benchmarks:
```
/opt/SUNWspro12_EA070303/bin/f90
```

Benchmarks using both Fortran and C:
```
/opt/SUNWspro12_EA070303/bin/cc /opt/SUNWspro12_EA070303/bin/f90
```

Base Optimization Flags

C benchmarks:
```
-fast -xipo=2 -xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Wc,-fma=fused -xprefetch_level=2
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-library=stlport4 -fast -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused

Fortran benchmarks:
-fast -xipo=2 -xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Qoption cg -fma=fused -xprefetch_level=2

Benchmarks using both Fortran and C:
-fast(cc) -fast(f90) -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Wc,-fma=fused -xprefetch_level=2 -Qoption cg -fma=fused

Peak Compiler Invocation

C benchmarks:
/opt/SUNWspro12_EA070303/bin/cc

C++ benchmarks:
/opt/SUNWspro12_EA070303/bin/CC

Fortran benchmarks:
/opt/SUNWspro12_EA070303/bin/f90

Benchmarks using both Fortran and C:
/opt/SUNWspro12_EA070303/bin/cc /opt/SUNWspro12_EA070303/bin/f90

Peak Optimization Flags

C benchmarks:

433.milc: -fast -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Wc,-fma=fused -xalias_level=strong -xprefetch_level=2
-xprefetch_auto_type=indirect_array_access

470.lbm: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=v8plusb -xprefetch_level=2 -fma=fused -Wc,-fma=fused

482.sphinx3: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12

Continued on next page

Peak Optimization Flags (Continued)

482.sphinx3 (continued):
-xarch=sparcfmaf -fma=fused -Wc,-fma=fused

C++ benchmarks:

444.namd: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Qoption cg -fma=fused -xdepend

447.dealII: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Qoption cg -fma=fused -xdepend
-xalias_level=compatible -xrestrict

450.soplex: basepeak = yes

453.povray: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Qoption cg -fma=fused -xdepend
-xalias_level=compatible

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused -lmopt

437.leslie3d: -fast -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused -xprefetch_level=2
-xprefetch=latx:8.0

459.GemsFDTD: basepeak = yes

465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=v8plusa -fma=fused -Qoption cg -fma=fused -lfast

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xipo=2 -xtarget=sparc64vi -xcache=128/64/2:6144/256/12

Continued on next page

Peak Optimization Flags (Continued)

435.gromacs (continued):
-xarch=sparcfmaf -fma=fused -Wc,-fma=fused
-Qoption cg -fma=fused

436.cactusADM: -fast(cc) -fast(f90) -xipo=2 -xtarget=sparc64vi
-xcache=128/64/2:6144/256/12 -xarch=sparcfmaf -fma=fused
-Wc,-fma=fused -Qoption cg -fma=fused

454.calculix: Same as 436.cactusADM

481.wrf: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xipo=2 -xtarget=sparc64vi -xcache=128/64/2:6144/256/12
-xarch=sparcfmaf -fma=fused -Wc,-fma=fused
-Qoption cg -fma=fused -xprefetch_level=2

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:43:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.