SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5130,2.00GHz)

SPECfp®_rate2006 = 36.1

SPECfp_rate_base2006 = 35.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006



Hardware

CPU Name:	Intel Xeon 5130
CPU Characteristics:	2.00 GHz, 4 MB L2, 1333 MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1 to 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip

Continued on next page

Software

Operating System:	SuSE Linux Enterprise Server 10 (EM64T) kernel 2.6.16.21-0.8-smp
Compiler:	Intel C++ Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_cc_c_9.1.045 Build no 20061101 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_fc_c_9.1.040 Build no 20061101
Auto Parallel:	No

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5130,2.00GHz)

SPECfp_rate2006 = 36.1

SPECfp_rate_base2006 = 35.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

L3 Cache:	None	File System:	ext2
Other Cache:	None	System State:	Multi-user run level 3
Memory:	24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5	Base Pointers:	64-bit
Disk Subsystem:	1x73 GB SAS, 15000 RPM	Peak Pointers:	32/64-bit
Other Hardware:	None	Other Software:	None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	**1687**	**32.2**	1686	32.2	1692	32.1	4	1687	32.2	1688	32.2	**1688**	**32.2**
416.gamess	4	1428	54.9	1426	54.9	**1426**	**54.9**	4	**1547**	**50.6**	1550	50.5	1545	50.7
433.milc	4	1724	21.3	**1723**	**21.3**	1723	21.3	4	**1726**	**21.3**	1726	21.3	1727	21.3
434.zeusmp	4	943	38.6	**947**	**38.4**	950	38.3	4	**980**	**37.1**	970	37.5	981	37.1
435.gromacs	4	598	47.8	591	48.4	**591**	**48.4**	4	**571**	**50.0**	571	50.0	571	50.0
436.cactusADM	4	1056	45.3	1071	44.6	**1065**	**44.9**	4	1083	44.1	1080	44.3	**1083**	**44.2**
437.leslie3d	4	1631	23.1	**1639**	**22.9**	1645	22.9	4	1643	22.9	**1641**	**22.9**	1639	22.9
444.namd	4	763	42.1	763	42.0	**763**	**42.0**	4	**775**	**41.4**	775	41.4	775	41.4
447.dealII	4	722	63.4	724	63.2	**722**	**63.3**	4	**711**	**64.4**	713	64.2	708	64.6
450.soplex	4	1267	26.3	1273	26.2	**1272**	**26.2**	4	**1266**	**26.3**	1265	26.4	1267	26.3
453.povray	4	389	54.7	386	55.1	**387**	**55.0**	4	**297**	**71.5**	311	68.4	297	71.7
454.calculix	4	795	41.5	**795**	**41.5**	798	41.4	4	780	42.3	**778**	**42.4**	775	42.6
459.GemsFDTD	4	**1991**	**21.3**	1985	21.4	2001	21.2	4	1992	21.3	1994	21.3	**1993**	**21.3**
465.tonto	4	1006	39.1	**997**	**39.5**	996	39.5	4	970	40.6	964	40.8	**969**	**40.6**
470.lbm	4	**3103**	**17.7**	3101	17.7	3104	17.7	4	3161	17.4	**3103**	**17.7**	3102	17.7
481.wrf	4	1143	39.1	1140	39.2	**1141**	**39.1**	4	1152	38.8	**1157**	**38.6**	1163	38.4
482.sphinx3	4	2131	36.6	2135	36.5	**2135**	**36.5**	4	2084	37.4	2082	37.5	**2082**	**37.4**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Environment stack size set to 'unlimited'
'/usr/bin/taskset' used to bind processes to CPUs
```

General Notes

```
The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

C++ benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Fortran benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5130,2.00GHz)

SPECfp_rate2006 = 36.1

SPECfp_rate_base2006 = 35.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:03:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.