



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M,
3.0 GHz

SPECfp®_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007



Hardware

CPU Name: Intel Xeon 7120M
CPU Characteristics: 800 MHz system bus
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable: 1,2,4 chips
Primary Cache: 12 K micro-ops I + 16 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l_fc_p_9.1.043
Auto Parallel: No
File System: ReiserFS

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M, 3.0 GHz

SPECfp_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22

Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Aug-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Mar-2007

L3 Cache:	4 MB I+D on chip per chip
Other Cache:	None
Memory:	32 GB (16x2 GB DDR2 PC2-3200R, 2 rank, CAS 3-3-3, with ECC)
Disk Subsystem:	Seagate ST973401SS (SAS 73GB 10 krpm)
Other Hardware:	None

System State:	Multiuser Runlevel 3
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	6623	32.8	6631	32.8	6623	32.8	16	6623	32.8	6631	32.8	6623	32.8	6623	32.8
416.gamess	16	4022	77.9	4067	77.0	4156	75.4	16	4022	77.9	4067	77.0	4156	75.4		
433.milc	16	6091	24.1	6100	24.1	6095	24.1	16	6393	23.0	6397	23.0	6395	23.0		
434.zeusmp	16	2916	49.9	2793	52.1	2925	49.8	16	3012	48.3	3001	48.5	2999	48.5		
435.gromacs	16	1612	70.9	1596	71.6	1640	69.7	16	1459	78.3	1458	78.4	1530	74.6		
436.cactusADM	16	3291	58.1	3277	58.3	3308	57.8	16	3291	58.1	3277	58.3	3308	57.8		
437.leslie3d	16	6529	23.0	6535	23.0	6531	23.0	16	6529	23.0	6535	23.0	6531	23.0		
444.namd	16	1512	84.9	1534	83.7	1573	81.6	16	1512	84.9	1534	83.7	1573	81.6		
447.dealII	16	2079	88.0	1930	94.8	1950	93.9	16	2129	86.0	1967	93.1	1963	93.2		
450.soplex	16	5032	26.5	4981	26.8	4985	26.8	16	4666	28.6	4625	28.9	4622	28.9		
453.povray	16	920	92.5	900	94.5	969	87.8	16	804	106	815	104	820	104		
454.calculix	16	1793	73.6	1800	73.3	1810	72.9	16	1786	73.9	1794	73.6	1790	73.7		
459.GemsFDTD	16	7720	22.0	7694	22.1	7707	22.0	16	7720	22.0	7694	22.1	7707	22.0		
465.tonto	16	2895	54.4	2887	54.5	2853	55.2	16	2825	55.7	2765	56.9	2700	58.3		
470.lbm	16	9362	23.5	9362	23.5	9363	23.5	16	9115	24.1	9119	24.1	9119	24.1		
481.wrf	16	4063	44.0	4074	43.9	4069	43.9	16	4063	44.0	4074	43.9	4069	43.9		
482.sphinx3	16	8612	36.2	8364	37.3	8353	37.3	16	8007	38.9	7947	39.2	7950	39.2		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
 '/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 800 MHz

All binaries were built with 64-bit Intel compiler except:
 433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with
 32-bit Intel compiler by changing the path for include and library files.

BIOS configuration:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M,
3.0 GHz

SPECfp_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22

Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Aug-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Mar-2007

General Notes (Continued)

Hardware Prefetch = Enable

This result was measured on the PRIMERGY RX600 S3.

The PRIMERGY RX600 S3 and the PRIMERGY TX600 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M,
3.0 GHz

SPECfp_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22

Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Aug-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Mar-2007

Base Optimization Flags (Continued)

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include  
-L/opt/intel/cc/9.1.047/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.047/bin/icpc  
           -I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.043/bin/ifort  
           -I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M,
3.0 GHz

SPECfp_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Aug-2006

Software Availability: Mar-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast

470.lbm: Same as 433.milc

482.sphinx3: -fast

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -prof_gen(pass 1) -prof_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:

435.gromacs: -prof_gen(pass 1) -prof_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M,
3.0 GHz

SPECfp_rate2006 = 47.0

SPECfp_rate_base2006 = 46.1

CPU2006 license: 22

Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Aug-2006

Tested by: Fujitsu Siemens Computers

Software Availability: Mar-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 11:19:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 26 June 2007.