SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G540 (Intel Xeon E5345)

SPECfp®_rate2006 = 57.1

SPECfp_rate_base2006 = 55.6

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jul-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon E5345
CPU Characteristics:	1333MHz system bus
CPU MHz:	2333
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	SUSE Linux Enterprise Server 10 EM64T (kernel 2.6.16.21-0.8-smp)
Compiler:	Intel C++ Compiler for Linux32 version 10.0 Build 20070426 Package ID: l_cc_p_10.0.023 Intel Fortran Compiler for Linux32 version 10.0 Build 20070426 Package ID: l_fc_p_10.0.023
Auto Parallel:	No
File System:	ReiserFS
System State:	Default

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos G540 (Intel Xeon E5345)

SPECfp_rate2006 = 57.1

SPECfp_rate_base2006 = 55.6

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jul-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem: 1 x 73 GB 10000RPM SAS HDD
Other Hardware: None

Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	**3509**	**31.0**	3509	31.0	3509	31.0	8	**3508**	**31.0**	3508	31.0	3508	31.0
416.gamess	8	1175	133	**1177**	**133**	1178	133	8	**1141**	**137**	1142	137	1138	138
433.milc	8	2556	28.7	2563	28.7	**2561**	**28.7**	8	2579	28.5	**2579**	**28.5**	2575	28.5
434.zeusmp	8	**1233**	**59.0**	1241	58.6	1232	59.1	8	1230	59.2	1243	58.6	**1238**	**58.8**
435.gromacs	8	531	108	**531**	**107**	531	107	8	**527**	**108**	529	108	526	109
436.cactusADM	8	1500	63.8	**1495**	**63.9**	1485	64.4	8	1527	62.6	**1526**	**62.7**	1523	62.8
437.leslie3d	8	**3221**	**23.3**	3228	23.3	3213	23.4	8	3150	23.9	**3151**	**23.9**	3156	23.8
444.namd	8	**656**	**97.8**	655	98.0	657	97.6	8	651	98.6	651	98.6	**651**	**98.6**
447.dealII	8	828	110	**855**	**107**	857	107	8	**836**	**109**	837	109	834	110
450.soplex	8	2132	31.3	2108	31.7	**2111**	**31.6**	8	1971	33.8	1942	34.4	**1942**	**34.4**
453.povray	8	285	149	**288**	**148**	289	147	8	**246**	**173**	243	175	247	173
454.calculix	8	737	89.6	740	89.2	**737**	**89.6**	8	735	89.8	744	88.7	**736**	**89.6**
459.GemsFDTD	8	3651	23.2	**3648**	**23.3**	3644	23.3	8	**3635**	**23.4**	3640	23.3	3629	23.4
465.tonto	8	965	81.5	**968**	**81.4**	970	81.2	8	963	81.8	**961**	**81.9**	959	82.1
470.lbm	8	4614	23.8	4613	23.8	**4613**	**23.8**	8	**4298**	**25.6**	4297	25.6	4298	25.6
481.wrf	8	1992	44.9	**1994**	**44.8**	1994	44.8	8	2000	44.7	**1993**	**44.8**	1991	44.9
482.sphinx3	8	3454	45.1	3285	47.5	**3290**	**47.4**	8	3219	48.4	**3069**	**50.8**	3052	51.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
All programs compiled with the 64-bit compiler except
437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak,
compiled with the 32-bit compiler

taskset was used to bind copies to cores
```

Base Compiler Invocation

C benchmarks:
icc

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast -auto-ilp32

C++ benchmarks:
-fast -auto-ilp32

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:

435.gromacs: -fast -auto-ilp32 -nofor_main(*)

436.cactusADM: Same as 435.gromacs

Continued on next page

Base Optimization Flags (Continued)

454.calculix: Same as 435.gromacs

481.wrf: -fast -auto-ilp32

(*) Indicates an optimization flag that was found in a portability variable.

Peak Compiler Invocation

C benchmarks (except as noted below):
/opt/intel/cc/10.0.023/bin/icc -L/opt/intel/cc/10.0.023/lib
-I/opt/intel/cc/10.0.023/include

433.milc: icc

C++ benchmarks (except as noted below):
icpc

450.soplex: /opt/intel/cc/10.0.023/bin/icpc -L/opt/intel/cc/10.0.023/lib
-I/opt/intel/cc/10.0.023/include

Fortran benchmarks (except as noted below):
ifort

437.leslie3d: /opt/intel/fc/10.0.023/bin/ifort -L/opt/intel/fc/10.0.023/lib
-I/opt/intel/fc/10.0.023/include

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch

482.sphinx3: -fast -unroll2

Continued on next page

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xT -ipo -O3 -no-prec-div

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -fast

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: Same as 434.zeusmp

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -auto-ilp32 -nofor_main(*)

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -auto-ilp32 -nofor_main(*)

454.calculix: -fast -auto-ilp32 -nofor_main(*)

481.wrf: -fast -auto-ilp32

(*) Indicates an optimization flag that was found in a portability variable.

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:53:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 August 2007.