



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp®_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55


Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Jun-2007



Hardware

CPU Name: Intel Core 2 Extreme QX6800
 CPU Characteristics: 1066 MHz Bus Speed
 CPU MHz: 2933
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: Windows XP Professional x64 Edition SP2
 Compiler: Intel C++ Compiler for Intel 64, Version 10.0
 Build 20070426 Package ID: W_CC_P_10.0.025
 Intel Visual Fortran Compiler for Intel 64,
 Version 10.0
 Build 20070426 Package ID: W_FC_P_10.0.025
 Microsoft Visual Studio 2005 SP1
 Auto Parallel: No
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Jun-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (4x2 GB 667 MHz ECC CL5 DDR2)
Disk Subsystem: 1 x 80 GB SATA 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: MicroQuill SmartHeap Library 8.0 for x64

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2312	23.5	<u>2298</u>	<u>23.7</u>	2290	23.7	4	<u>2297</u>	<u>23.7</u>	2299	23.6	2297	23.7
416.gamess	4	<u>959</u>	<u>81.7</u>	958	81.8	959	81.7	4	939	83.4	938	83.5	<u>939</u>	<u>83.4</u>
433.milc	4	<u>2294</u>	<u>16.0</u>	2287	16.1	2297	16.0	4	<u>2282</u>	<u>16.1</u>	2284	16.1	2271	16.2
434.zeusmp	4	846	43.0	<u>845</u>	<u>43.1</u>	843	43.2	4	819	44.5	<u>816</u>	<u>44.6</u>	813	44.8
435.gromacs	4	395	72.2	<u>395</u>	<u>72.2</u>	395	72.3	4	394	72.4	393	72.7	<u>393</u>	<u>72.7</u>
436.cactusADM	4	998	47.9	999	47.8	<u>998</u>	<u>47.9</u>	4	998	47.9	999	47.8	<u>998</u>	<u>47.9</u>
437.leslie3d	4	2268	16.6	<u>2263</u>	<u>16.6</u>	2257	16.7	4	2263	16.6	2263	16.6	<u>2263</u>	<u>16.6</u>
444.namd	4	520	61.7	520	61.7	<u>520</u>	<u>61.7</u>	4	515	62.3	<u>512</u>	<u>62.7</u>	512	62.7
447.dealII	4	783	58.5	780	58.7	<u>783</u>	<u>58.5</u>	4	751	60.9	<u>746</u>	<u>61.4</u>	742	61.7
450.soplex	4	1613	20.7	1609	20.7	<u>1611</u>	<u>20.7</u>	4	1617	20.6	1615	20.7	<u>1615</u>	<u>20.7</u>
453.povray	4	245	87.0	245	86.9	<u>245</u>	<u>86.9</u>	4	<u>196</u>	<u>109</u>	196	108	196	109
454.calculix	4	<u>612</u>	<u>54.0</u>	614	53.7	595	55.4	4	615	53.7	<u>614</u>	<u>53.8</u>	612	53.9
459.GemsFDTD	4	2913	14.6	2914	14.6	<u>2914</u>	<u>14.6</u>	4	2913	14.6	2914	14.6	<u>2914</u>	<u>14.6</u>
465.tonto	4	826	47.7	<u>817</u>	<u>48.2</u>	817	48.2	4	<u>814</u>	<u>48.4</u>	811	48.5	818	48.1
470.lbm	4	<u>3388</u>	<u>16.2</u>	3386	16.2	3389	16.2	4	<u>3387</u>	<u>16.2</u>	3386	16.2	3388	16.2
481.wrf	4	1378	32.4	<u>1373</u>	<u>32.5</u>	1372	32.6	4	<u>1379</u>	<u>32.4</u>	1383	32.3	1372	32.6
482.sphinx3	4	2353	33.1	<u>2333</u>	<u>33.4</u>	2333	33.4	4	2341	33.3	2323	33.6	<u>2334</u>	<u>33.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Binaries were built on Windows Vista Ultimate (64-bit)

Base Compiler Invocation

C benchmarks:
icl -Qstd=c99

C++ benchmarks:
icl

Fortran benchmarks:
ifort

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Jun-2007

Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

```
icl -Qstd=c99 ifort
```

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -D_Complex= -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -D_Complex= -DSPEC_CPU_P64
436.cactusADM: -D_Complex= -DSPEC_CPU_P64 -Qlowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -D_Complex= -DSPEC_CPU_P64 -DBOOST_NO_INTRINSIC_WCHAR_T
-DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -D_Complex= -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER
-Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -D_Complex= -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -D_Complex= -DSPEC_CPU_P64

```

Base Optimization Flags

C benchmarks:

```
-fast -Qauto_ilp32 /F950000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features -Qauto_ilp32 /F950000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-fast /F950000000 -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-fast -Qauto_ilp32 /F950000000 -link /FORCE:MULTIPLE
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Jun-2007

Peak Compiler Invocation

C benchmarks:
icl -Qstd=c99

C++ benchmarks:
icl

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Oa -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE

470.lbm: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Qscalar-rep- -Qprefetch -Qauto_ilp32
/F950000000 shlw64M.lib -link /FORCE:MULTIPLE

482.sphinx3: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE

C++ benchmarks:

444.namd: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
-Qcxx_features -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE

447.dealIII: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qprefetch -Qcxx_features -Qauto_ilp32 /F950000000
shlw64M.lib -link /FORCE:MULTIPLE

450.soplex: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qcxx_features -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Sep-2007

Tested by: Dell Inc.

Software Availability: Jun-2007

Peak Optimization Flags (Continued)

453.povray: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qansi-alias -Qcxx_features -Qauto_ilp32 /F950000000
sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: ONESTEP -fast /F950000000 -link /FORCE:MULTIPLE

416.gamess: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F950000000
-link /FORCE:MULTIPLE

434.zeusmp: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2
-Qprec-div- -Qunroll0 -Qscalar-rep- /F950000000
-link /FORCE:MULTIPLE

437.leslie3d: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
/F950000000 -link /FORCE:MULTIPLE

459.GemsFDTD: basepeak = yes

465.tonto: Same as 437.leslie3d

Benchmarks using both Fortran and C:

435.gromacs: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
-Qauto_ilp32 /F950000000 -link /FORCE:MULTIPLE

436.cactusADM: basepeak = yes

454.calculix: -fast -Qauto_ilp32 /F950000000
-link /FORCE:MULTIPLE

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 37.1

Dell Precision 390 (Intel QX6800, 2.93 GHz)

SPECfp_rate_base2006 = 36.3

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Aug-2007

Hardware Availability: Sep-2007

Software Availability: Jun-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:16:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 4 September 2007.