



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp<sup>®</sup>\_rate2006 = 22.5

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

SPECfp\_rate\_base2006 = 22.0

CPU2006 license: 3


Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007



SPECfp\_rate\_base2006 = 22.0

SPECfp\_rate2006 = 22.5

### Hardware

CPU Name: Intel Xeon 7140M  
 CPU Characteristics: 3.4 GHz, 800 MHz system bus  
 CPU MHz: 3400  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2,4 chips  
 Primary Cache: 12 K micro-ops I + 16 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

### Software

Operating System: SuSE LinuxEnterprise Server 10 (x86\_64)  
 kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler for IA32/EM64T applications, Version 10.0  
 Build 20070426 Package ID: 1\_cc\_p\_10.0.023  
 Intel Fortran Compiler for applications running on Intel 64, Version 10.0  
 Build 20070426 Package ID: 1\_fc\_p\_10.0.023  
 Auto Parallel: No

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp\_rate2006 = 22.5

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

SPECfp\_rate\_base2006 = 22.0

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007

L3 Cache: 16 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16x2 GB PC2-3200R)  
Disk Subsystem: 1x72 GB 15 K SAS  
Other Hardware: None

File System: ext2  
System State: Multi-user run level 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	1098	24.8	<u>1104</u>	<u>24.6</u>	1105	24.6	2	1098	24.8	<u>1106</u>	<u>24.6</u>	1106	24.6
416.gamess	2	1734	22.6	1740	22.5	<u>1737</u>	<u>22.5</u>	2	1698	23.1	1701	23.0	<u>1699</u>	<u>23.0</u>
433.milc	2	<u>1487</u>	<u>12.3</u>	1490	12.3	1487	12.3	2	1483	12.4	<u>1481</u>	<u>12.4</u>	1477	12.4
434.zeusmp	2	1078	16.9	<u>1077</u>	<u>16.9</u>	1077	16.9	2	1085	16.8	1084	16.8	<u>1084</u>	<u>16.8</u>
435.gromacs	2	719	19.9	<u>715</u>	<u>20.0</u>	708	20.2	2	716	19.9	<u>715</u>	<u>20.0</u>	711	20.1
436.cactusADM	2	<u>812</u>	<u>29.4</u>	812	29.4	792	30.2	2	780	30.6	801	29.9	<u>783</u>	<u>30.5</u>
437.leslie3d	2	1108	17.0	1114	16.9	<u>1112</u>	<u>16.9</u>	2	1140	16.5	<u>1129</u>	<u>16.6</u>	1125	16.7
444.namd	2	821	19.5	<u>821</u>	<u>19.5</u>	823	19.5	2	815	19.7	815	19.7	<u>815</u>	<u>19.7</u>
447.dealII	2	701	32.6	700	32.7	<u>701</u>	<u>32.6</u>	2	<u>643</u>	<u>35.6</u>	642	35.6	643	35.6
450.soplex	2	872	19.1	<u>861</u>	<u>19.4</u>	857	19.5	2	786	21.2	788	21.2	<u>786</u>	<u>21.2</u>
453.povray	2	<u>426</u>	<u>25.0</u>	426	25.0	425	25.0	2	<u>381</u>	<u>27.9</u>	381	27.9	381	27.9
454.calculix	2	<u>889</u>	<u>18.6</u>	888	18.6	889	18.6	2	888	18.6	889	18.6	<u>889</u>	<u>18.6</u>
459.GemsFDTD	2	1449	14.6	1442	14.7	<u>1442</u>	<u>14.7</u>	2	<u>1434</u>	<u>14.8</u>	1432	14.8	1437	14.8
465.tonto	2	804	24.5	800	24.6	<u>802</u>	<u>24.5</u>	2	<u>771</u>	<u>25.5</u>	771	25.5	771	25.5
470.lbm	2	1010	27.2	1005	27.3	<u>1010</u>	<u>27.2</u>	2	996	27.6	1011	27.2	<u>1006</u>	<u>27.3</u>
481.wrf	2	832	26.8	<u>833</u>	<u>26.8</u>	834	26.8	2	<u>834</u>	<u>26.8</u>	834	26.8	835	26.8
482.sphinx3	2	<u>997</u>	<u>39.1</u>	1003	38.9	997	39.1	2	<u>985</u>	<u>39.6</u>	983	39.7	985	39.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS configuration:  
Power Regulator Disabled  
Adjacent Sector Prefetch Enabled  
Hardware Prefetcher Enabled  
Hyper-Threading Technology Disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 22.5**

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

**SPECfp\_rate\_base2006 = 22.0**

**CPU2006 license:** 3

**Test date:** Aug-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Aug-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** May-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xP -ipo -O3 -static -no-prec-div

C++ benchmarks:

-xP -ipo -O3 -static -no-prec-div

Fortran benchmarks:

-xP -ipo -O3 -static -no-prec-div

Benchmarks using both Fortran and C:

-xP -ipo -O3 -static -no-prec-div



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 22.5**

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

**SPECfp\_rate\_base2006 = 22.0**

**CPU2006 license:** 3

**Test date:** Aug-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Aug-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** May-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.0.023/bin/icc -L/opt/intel/cc/10.0.023/lib
-I/opt/intel/cc/10.0.023/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.0.023/bin/icpc -L/opt/intel/cc/10.0.023/lib
-I/opt/intel/cc/10.0.023/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.0.023/bin/ifort -L/opt/intel/fc/10.0.023/lib
-I/opt/intel/fc/10.0.023/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -fno-alias
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -unroll2 -no-scalar-rep -prefetch
```

```
482.sphinx3: -xP -ipo -O3 -static -no-prec-div -unroll2
```

C++ benchmarks:

```
444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -fno-alias -auto-ilp32
```

```
447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -unroll2 -ansi-alias -no-scalar-rep
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 22.5**

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

**SPECfp\_rate\_base2006 = 22.0**

**CPU2006 license:** 3  
**Test sponsor:** Hewlett-Packard Company  
**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2007  
**Hardware Availability:** Aug-2006  
**Software Availability:** May-2007

## Peak Optimization Flags (Continued)

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xP -ipo -O3 -static -no-prec-div

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll2 -Ob0 -ansi-alias -no-scalar-rep

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div

437.leslie3d: Same as 434.zeusmp

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll2 -Ob0

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -fno-alias

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll2 -auto-ilp32

454.calculix: -xP -ipo -O3 -static -no-prec-div -auto-ilp32

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic10-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic10-flags.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

ProLiant DL580 G4  
(3.4 GHz, Intel Xeon processor 7140M)

**SPECfp\_rate2006 = 22.5**

**SPECfp\_rate\_base2006 = 22.0**

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Aug-2007

**Hardware Availability:** Aug-2006

**Software Availability:** May-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 13:59:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 October 2007.