SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor E5335, 2.00GHz)

SPECfp®_rate2006 = 52.1

SPECfp_rate_base2006 = 51.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Aug-2007
Hardware Availability: Mar-2007
Software Availability: May-2007



Hardware

CPU Name:	Intel Xeon E5335
CPU Characteristics:	2.00 GHz, 8 MB L2, 1333 MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1 to 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	SUSE LINUX Enterprise Server 10 Kernel 2.6.16.21-0.8-smp for x86_64
Compiler:	Intel C++ Compiler for IA32/EM64T application version 10.0 Build 20070426 Package ID: l_cc_p_10.0.023 Intel Fortran Compiler for IA32/EM64T application version 10.0 Build 20070426 Package ID: l_fc_p_10.0.023
Auto Parallel:	No
File System:	ext2

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor E5335, 2.00GHz)

SPECfp_rate2006 = 52.1

SPECfp_rate_base2006 = 51.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Aug-2007
Hardware Availability: Mar-2007
Software Availability: May-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

System State: Multi-user run level 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3502	31.0	3502	31.0	**3502**	**31.0**	8	**3516**	**30.9**	3516	30.9	3516	30.9
416.gamess	8	1368	115	**1368**	**115**	1366	115	8	1456	108	1466	107	**1465**	**107**
433.milc	8	**3531**	**20.8**	3530	20.8	3536	20.8	8	**3709**	**19.8**	3706	19.8	3710	19.8
434.zeusmp	8	1227	59.3	1222	59.6	**1224**	**59.5**	8	1250	58.3	1221	59.6	**1245**	**58.5**
435.gromacs	8	584	97.7	592	96.5	**587**	**97.3**	8	580	98.5	584	97.7	**580**	**98.5**
436.cactusADM	8	1447	66.0	**1446**	**66.1**	1441	66.3	8	1449	66.0	**1453**	**65.8**	1458	65.6
437.leslie3d	8	**3257**	**23.1**	3262	23.1	3241	23.2	8	**3262**	**23.1**	3265	23.0	3249	23.1
444.namd	8	**760**	**84.4**	761	84.3	759	84.5	8	**763**	**84.1**	763	84.1	764	84.0
447.dealII	8	**810**	**113**	807	113	813	113	8	800	114	799	115	**799**	**115**
450.soplex	8	**2381**	**28.0**	2379	28.0	2383	28.0	8	2170	30.7	2163	30.8	**2163**	**30.8**
453.povray	8	339	126	**333**	**128**	333	128	8	287	148	**286**	**149**	286	149
454.calculix	8	816	80.9	807	81.7	**813**	**81.2**	8	850	77.6	855	77.2	**853**	**77.3**
459.GemsFDTD	8	4306	19.7	**4306**	**19.7**	4306	19.7	8	4312	19.7	4302	19.7	**4307**	**19.7**
465.tonto	8	**1036**	**76.0**	1043	75.5	1035	76.1	8	**1037**	**75.9**	1039	75.8	1035	76.1
470.lbm	8	**4626**	**23.8**	4629	23.7	4624	23.8	8	4341	25.3	4341	25.3	**4341**	**25.3**
481.wrf	8	1924	46.4	1929	46.3	**1929**	**46.3**	8	**1928**	**46.4**	1928	46.4	1929	46.3
482.sphinx3	8	**3754**	**41.5**	3753	41.5	3754	41.5	8	**3471**	**44.9**	3471	44.9	3470	44.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

All binaries were built with 64-bit Intel compiler except:
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path for include and library files.

The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks:
`/opt/intel/cc/10.0.023/bin/icc -L/opt/intel/cc/10.0.023/lib -I/opt/intel/cc/10.0.023/include`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `/opt/intel/cc/10.0.023/bin/icpc -L/opt/intel/cc/10.0.023/lib -I/opt/intel/cc/10.0.023/include`

Fortran benchmarks (except as noted below):
`ifort`

434.zeusmp: `/opt/intel/fc/10.0.023/bin/ifort -L/opt/intel/fc/10.0.023/lib -I/opt/intel/fc/10.0.023/include`

Benchmarks using both Fortran and C:
`icc ifort`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

433.milc: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast -auto_ilp32`

470.lbm: `Same as 433.milc`

482.sphinx3: `-fast -auto_ilp32`

C++ benchmarks:
`-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast -auto_ilp32`

Continued on next page

Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

416.gamess: `Same as 410.bwaves`

434.zeusmp: `-fast`

437.leslie3d: `Same as 410.bwaves`

459.GemsFDTD: `Same as 410.bwaves`

465.tonto: `Same as 410.bwaves`

Benchmarks using both Fortran and C:
`-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast -auto_ilp32`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/EM64T_Intel100_flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/EM64T_Intel100_flags.20090714.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:58:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 October 2007.