



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp®2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jan-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5405
CPU Characteristics: 2.00 GHz, 2x6 MB L2 shared, 1333 MHz bus
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
Auto Parallel: Yes
File System: ext2

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jan-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x73.2 GB SAS, 15000RPM
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: binutils-2.17.tar.gz, Version 2.17

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---------------|-------------|-------------|------------|-------------|-------------|-------------|------------|-------|-------------|-------------|------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 438 | 31.0 | 440 | 30.9 | 440 | 30.9 | 434 | 31.3 | 435 | 31.3 | 435 | 31.2 |
| 416.gamess | 1356 | 14.4 | 1368 | 14.3 | 1363 | 14.4 | 1313 | 14.9 | 1314 | 14.9 | 1316 | 14.9 |
| 433.milc | 923 | 9.94 | 923 | 9.94 | 924 | 9.93 | 919 | 9.99 | 919 | 9.99 | 919 | 9.99 |
| 434.zeusmp | 730 | 12.5 | 730 | 12.5 | 730 | 12.5 | 754 | 12.1 | 754 | 12.1 | 754 | 12.1 |
| 435.gromacs | 550 | 13.0 | 553 | 12.9 | 550 | 13.0 | 550 | 13.0 | 547 | 13.1 | 547 | 13.1 |
| 436.cactusADM | 358 | 33.4 | 361 | 33.1 | 357 | 33.5 | 144 | 82.9 | 142 | 84.3 | 144 | 83.0 |
| 437.leslie3d | 567 | 16.6 | 566 | 16.6 | 566 | 16.6 | 567 | 16.6 | 566 | 16.6 | 566 | 16.6 |
| 444.namd | 759 | 10.6 | 755 | 10.6 | 755 | 10.6 | 756 | 10.6 | 754 | 10.6 | 750 | 10.7 |
| 447.dealII | 579 | 19.8 | 580 | 19.7 | 580 | 19.7 | 541 | 21.2 | 540 | 21.2 | 541 | 21.2 |
| 450.soplex | 760 | 11.0 | 760 | 11.0 | 762 | 11.0 | 688 | 12.1 | 690 | 12.1 | 690 | 12.1 |
| 453.povray | 320 | 16.6 | 323 | 16.5 | 318 | 16.7 | 269 | 19.8 | 268 | 19.8 | 268 | 19.8 |
| 454.calculix | 751 | 11.0 | 753 | 11.0 | 753 | 11.0 | 508 | 16.3 | 507 | 16.3 | 506 | 16.3 |
| 459.GemsFDTD | 621 | 17.1 | 620 | 17.1 | 619 | 17.1 | 606 | 17.5 | 606 | 17.5 | 607 | 17.5 |
| 465.tonto | 670 | 14.7 | 669 | 14.7 | 669 | 14.7 | 641 | 15.4 | 638 | 15.4 | 640 | 15.4 |
| 470.lbm | 1965 | 6.99 | 1964 | 7.00 | 1968 | 6.98 | 678 | 20.3 | 680 | 20.2 | 681 | 20.2 |
| 481.wrf | 646 | 17.3 | 647 | 17.3 | 648 | 17.2 | 675 | 16.6 | 677 | 16.5 | 678 | 16.5 |
| 482.sphinx3 | 1044 | 18.7 | 998 | 19.5 | 987 | 19.7 | 984 | 19.8 | 978 | 19.9 | 977 | 20.0 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run OMP_NUM_THREADS set to number of cores (default).

Platform Notes

Bios settings:

Intel SpeedStep Technology: Disabled

General Notes

All benchmarks compiled in 64-bit mode except 450.soplex,
470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jan-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007

General Notes (Continued)

The NEC Express5800/120Rh-1 (Intel Xeon Processor E5405),
the NEC Express5800/120Rj-2 (Intel Xeon Processor E5405),
the Bull NovaScale R440 E1 (Intel Xeon E5405, 2.00GHz) and
the Bull NovaScale R460 E1 (Intel Xeon E5405, 2.00GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/120Rj-2 (Intel Xeon Processor E5405) model.

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast -parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jan-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007

Base Optimization Flags (Continued)

C++ benchmarks:

-fast -parallel

Fortran benchmarks:

-fast -parallel

Benchmarks using both Fortran and C:

-fast -parallel

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jan-2008

Hardware Availability: Dec-2007

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rh-1
(Intel Xeon processor E5405)

SPECfp2006 = 17.7

SPECfp_base2006 = 15.0

CPU2006 license: 9006

Test date: Jan-2008

Test sponsor: NEC Corporation

Hardware Availability: Dec-2007

Tested by: NEC Corporation

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090714.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090714.01.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 16:27:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 February 2008.