



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS


NovaScale R440 E1  
(Intel Xeon X5460,3.16GHz)

SPECint®2006 = 27.3

SPECint\_base2006 = 23.9

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Dec-2007  
Hardware Availability: Dec-2007  
Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5460  
 CPU Characteristics: 3.16 GHz, 2x6 MB L2 shared, 1333 MHz bus  
 CPU MHz: 3160  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
 Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l\_cc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ext2  
 System State: Multiuser, Runlevel 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap library 8.1 binutils-2.17.tar.gz, Version 2.17



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E1  
(Intel Xeon X5460,3.16GHz)

SPECint2006 = 27.3

SPECint\_base2006 = 23.9

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Dec-2007  
Hardware Availability: Dec-2007  
Software Availability: Nov-2007

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	474	20.6	<b>476</b>	<b>20.5</b>	498	19.6	381	25.6	380	25.7	<b>380</b>	<b>25.7</b>
401.bzip2	567	17.0	562	17.2	<b>564</b>	<b>17.1</b>	521	18.5	523	18.4	<b>522</b>	<b>18.5</b>
403.gcc	<b>549</b>	<b>14.7</b>	548	14.7	550	14.6	412	19.5	413	19.5	<b>412</b>	<b>19.5</b>
429.mcf	378	24.1	<b>380</b>	<b>24.0</b>	382	23.9	385	23.7	<b>384</b>	<b>23.8</b>	383	23.8
445.gobmk	507	20.7	508	20.7	<b>507</b>	<b>20.7</b>	459	22.8	459	22.9	<b>459</b>	<b>22.8</b>
456.hmmer	561	16.6	<b>561</b>	<b>16.6</b>	562	16.6	323	28.9	324	28.8	<b>323</b>	<b>28.9</b>
458.sjeng	<b>662</b>	<b>18.3</b>	663	18.3	658	18.4	589	20.5	<b>590</b>	<b>20.5</b>	591	20.5
462.libquantum	<b>93.9</b>	<b>221</b>	98.5	210	86.1	241	91.6	226	<b>91.6</b>	<b>226</b>	89.6	231
464.h264ref	676	32.7	676	32.7	<b>676</b>	<b>32.7</b>	631	35.1	<b>629</b>	<b>35.2</b>	627	35.3
471.omnetpp	419	14.9	<b>419</b>	<b>14.9</b>	423	14.8	<b>386</b>	<b>16.2</b>	387	16.1	386	16.2
473.astar	457	15.4	<b>456</b>	<b>15.4</b>	455	15.4	420	16.7	415	16.9	<b>416</b>	<b>16.9</b>
483.xalancbmk	255	27.1	256	27.0	<b>255</b>	<b>27.0</b>	255	27.1	256	27.0	<b>255</b>	<b>27.0</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores (default).

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled

## General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,  
for peak, are compiled in 64-bit mode

The NEC Express5800/120Rh-1(Intel Xeon Processor X5460),  
the NEC Express5800/120Rj-2(Intel Xeon Processor X5460),  
the Bull NovaScale R440 E1 (Intel Xeon X5460,3.16GHz) and  
the Bull NovaScale R460 E1 (Intel Xeon X5460,3.16GHz) models are electronically equivalent.  
The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon Processor X5460) model.

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E1  
(Intel Xeon X5460,3.16GHz)

SPECint2006 = 27.3

SPECint\_base2006 = 23.9

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Dec-2007

Hardware Availability: Dec-2007

Software Availability: Nov-2007

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/opt/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:  
icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E1  
(Intel Xeon X5460,3.16GHz)

SPECint2006 = 27.3

SPECint\_base2006 = 23.9

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Dec-2007  
Hardware Availability: Dec-2007  
Software Availability: Nov-2007

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

### C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32  
403.gcc: -fast -inline-calloc -opt-malloc-options=3  
429.mcf: -fast -prefetch  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias  
456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive  
-auto-ilp32  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

### C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs -L/opt/SmartHeap\_8.1/lib -lsmartheap  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs -L/opt/SmartHeap\_8.1/lib -lsmartheap  
483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E1  
(Intel Xeon X5460,3.16GHz)

SPECint2006 = 27.3

SPECint\_base2006 = 23.9

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Dec-2007  
**Hardware Availability:** Dec-2007  
**Software Availability:** Nov-2007

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.01.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:04:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 April 2008.