



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Itautec**

**SPECfp®\_rate2006 = 72.3**

Servidor Itautec LX211 (Intel Xeon X5460)

**SPECfp\_rate\_base2006 = 64.4**

CPU2006 license: 9001


Test date: Apr-2008

Test sponsor: Itautec

Hardware Availability: Dec-2007

Tested by: Itautec

Software Availability: Jan-2008



**SPECfp\_rate\_base2006 = 64.4**

**SPECfp\_rate2006 = 72.3**

## Hardware

CPU Name: Intel Xeon X5460  
 CPU Characteristics:  
 CPU MHz:  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

## Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ and Fortran Compiler for Linux version 10.1 Build 20080112 Package ID: l\_cc\_p\_10.1.012, l\_fc\_p\_10.1.012  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run Level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

**SPECfp\_rate2006 = 72.3**

Servidor Itautec LX211 (Intel Xeon X5460)

**SPECfp\_rate\_base2006 = 64.4**

CPU2006 license: 9001

Test date: Apr-2008

Test sponsor: Itautec

Hardware Availability: Dec-2007

Tested by: Itautec

Software Availability: Jan-2008

L3 Cache: None  
 Other Cache: None  
 Memory: 12 GB (6 \* 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)  
 Disk Subsystem: 1 x SCSI, 73GB, 10000 RPM  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.17.10.50

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3140	34.6	3180	34.2	<b>3170</b>	<b>34.3</b>	8	3140	34.6	3180	34.2	<b>3170</b>	<b>34.3</b>
416.gamess	8	842	186	<b>842</b>	<b>186</b>	845	185	8	<b>829</b>	<b>189</b>	829	189	828	189
433.milc	8	2613	28.1	2484	29.6	<b>2497</b>	<b>29.4</b>	8	2613	28.1	2484	29.6	<b>2497</b>	<b>29.4</b>
434.zeusmp	8	1198	60.8	<b>1111</b>	<b>65.5</b>	1104	65.9	8	<b>1110</b>	<b>65.6</b>	1109	65.7	1120	65.0
435.gromacs	8	378	151	<b>377</b>	<b>151</b>	377	151	8	<b>363</b>	<b>157</b>	363	157	361	158
436.cactusADM	8	<b>1438</b>	<b>66.5</b>	1420	67.3	1449	66.0	1	<b>122</b>	<b>97.9</b>	122	98.2	123	97.5
437.leslie3d	8	4222	17.8	<b>3047</b>	<b>24.7</b>	2997	25.1	4	<b>1465</b>	<b>25.7</b>	1456	25.8	1478	25.4
444.namd	8	484	133	483	133	<b>483</b>	<b>133</b>	8	481	133	<b>481</b>	<b>134</b>	480	134
447.dealII	8	709	129	<b>692</b>	<b>132</b>	689	133	8	696	131	<b>676</b>	<b>135</b>	675	136
450.soplex	8	2053	32.5	<b>1911</b>	<b>34.9</b>	1895	35.2	8	1753	38.1	<b>1750</b>	<b>38.1</b>	1731	38.6
453.povray	8	203	210	<b>202</b>	<b>210</b>	202	210	8	<b>169</b>	<b>252</b>	169	252	172	248
454.calculix	8	559	118	<b>551</b>	<b>120</b>	544	121	8	399	165	<b>405</b>	<b>163</b>	409	161
459.GemsFDTD	8	3524	24.1	3659	23.2	<b>3641</b>	<b>23.3</b>	8	3605	23.5	3554	23.9	<b>3580</b>	<b>23.7</b>
465.tonto	8	<b>795</b>	<b>99.0</b>	797	98.7	783	101	8	751	105	774	102	<b>757</b>	<b>104</b>
470.lbm	8	6690	16.4	<b>6431</b>	<b>17.1</b>	6422	17.1	4	2163	25.4	2212	24.9	<b>2183</b>	<b>25.2</b>
481.wrf	8	2006	44.5	1987	45.0	<b>1989</b>	<b>44.9</b>	8	2038	43.8	<b>1974</b>	<b>45.3</b>	1971	45.3
482.sphinx3	8	2351	66.3	2301	67.8	<b>2319</b>	<b>67.2</b>	4	766	102	759	103	<b>761</b>	<b>102</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

OMP\_NUM\_THREADS set to number of cores  
 KMP\_STACK\_SIZE set to 64M  
 KMP\_AFFINITY set to physical,0

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
 '/usr/bin/taskset' used to bind benchmark copies to processors, except for 436.cactusADM at peak.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

**SPECfp\_rate2006 = 72.3**

Servidor Itaute LX211 (Intel Xeon X5460)

**SPECfp\_rate\_base2006 = 64.4**

CPU2006 license: 9001

Test date: Apr-2008

Test sponsor: Itaute

Hardware Availability: Dec-2007

Tested by: Itaute

Software Availability: Jan-2008

## Platform Notes

BIOS configuration:  
Hardware Prefetch Disabled

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-fast

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

**SPECfp\_rate2006 = 72.3**

Servidor Itaute LX211 (Intel Xeon X5460)

**SPECfp\_rate\_base2006 = 64.4**

CPU2006 license: 9001

Test date: Apr-2008

Test sponsor: Itaute

Hardware Availability: Dec-2007

Tested by: Itaute

Software Availability: Jan-2008

## Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

## Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.012/bin/icc -L/opt/intel/cc/10.1.012/lib  
-I/opt/intel/cc/10.1.012/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.012/bin/icpc -L/opt/intel/cc/10.1.012/lib  
-I/opt/intel/cc/10.1.012/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.012/bin/ifort -L/opt/intel/fc/10.1.012/lib  
-I/opt/intel/fc/10.1.012/include

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECfp\_rate2006 = 72.3

Servidor Itaute LX211 (Intel Xeon X5460)

SPECfp\_rate\_base2006 = 64.4

CPU2006 license: 9001

Test date: Apr-2008

Test sponsor: Itaute

Hardware Availability: Dec-2007

Tested by: Itaute

Software Availability: Jan-2008

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp\_rate2006 = 72.3

Servidor Itautec LX211 (Intel Xeon X5460)

SPECfp\_rate\_base2006 = 64.4

CPU2006 license: 9001

Test date: Apr-2008

Test sponsor: Itautec

Hardware Availability: Dec-2007

Tested by: Itautec

Software Availability: Jan-2008

## Peak Optimization Flags (Continued)

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 16:49:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 29 April 2008.