



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp[®]2006 = 23.0

SPECfp_base2006 = 21.7

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E3110
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1
 Kernel 2.6.16.46-0.12-smp for x86_64
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008,
 l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp2006 = **23.0**

SPECfp_base2006 = **21.7**

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (4x2 GB) FB-DIMM PC2-6400E ECC CL6
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	436	31.2	432	31.5	433	31.4	432	31.4	434	31.3	433	31.4
416.gamess	888	22.0	887	22.1	890	22.0	875	22.4	878	22.3	877	22.3
433.milc	675	13.6	677	13.6	677	13.6	685	13.4	685	13.4	686	13.4
434.zeusmp	462	19.7	464	19.6	462	19.7	469	19.4	468	19.4	469	19.4
435.gromacs	368	19.4	371	19.2	369	19.3	366	19.5	366	19.5	366	19.5
436.cactusADM	337	35.5	335	35.7	334	35.8	296	40.4	300	39.8	297	40.2
437.leslie3d	485	19.4	485	19.4	485	19.4	485	19.4	485	19.4	485	19.4
444.namd	505	15.9	505	15.9	506	15.9	504	15.9	502	16.0	502	16.0
447.dealII	374	30.6	375	30.5	375	30.5	350	32.7	351	32.6	350	32.7
450.soplex	455	18.3	456	18.3	456	18.3	412	20.3	413	20.2	413	20.2
453.povray	213	25.0	213	25.0	214	24.9	180	29.6	180	29.6	180	29.6
454.calculix	495	16.7	495	16.7	494	16.7	335	24.7	334	24.7	334	24.7
459.GemsFDTD	647	16.4	648	16.4	648	16.4	642	16.5	643	16.5	642	16.5
465.tonto	465	21.2	450	21.9	450	21.9	427	23.1	427	23.0	428	23.0
470.lbm	645	21.3	644	21.3	641	21.4	553	24.8	556	24.7	557	24.7
481.wrf	442	25.3	442	25.2	443	25.2	470	23.8	470	23.8	472	23.7
482.sphinx3	673	29.0	675	28.9	671	29.0	658	29.6	660	29.6	657	29.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 200M
```

General Notes

All benchmarks compiled in 64-bit mode except 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

The Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz), the Bull NovaScale T830 E1(Intel Xeon E3110, 3.00 GHz) and the Bull NovaScale R410 E1(Intel Xeon E3110, 3.00 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale T810 E1(Intel Xeon E3110, 3.00 GHz) model.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp2006 = 23.0

SPECfp_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast -parallel

C++ benchmarks:
-fast -parallel

Fortran benchmarks:
-fast -parallel

Benchmarks using both Fortran and C:
-fast -parallel



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp2006 = 23.0

SPECfp_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp2006 = 23.0

SPECfp_base2006 = 21.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.xml



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T830 E1
(Intel Xeon E3110, 3.00 GHz)

SPECfp2006 = 23.0

SPECfp_base2006 = 21.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:57:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.