SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rj-2
(Intel Xeon X5450)

SPECfp®_rate2006 = 41.2

SPECfp_rate_base2006 = 37.7

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: Apr-2008
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon X5450
CPU Characteristics:	3.00 GHz, 2x6 MB L2 shared, 1333 MHz bus
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	Intel C++ and Fortran Compiler for Linux version 10.1 Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Run level 3 (multi-user)

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Rj-2
(Intel Xeon X5450)

SPECfp_rate2006 = 41.2

SPECfp_rate_base2006 = 37.7

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2008
Hardware Availability: Apr-2008
Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x73.2 GB SAS, 15000RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: binutils 2.17

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2649	20.5	**2650**	**20.5**	2651	20.5	4	**2398**	**22.7**	2395	22.7	2399	22.7
416.gamess	4	891	87.9	895	87.5	**892**	**87.9**	4	**879**	**89.1**	878	89.2	880	89.0
433.milc	4	2042	18.0	**2032**	**18.1**	2026	18.1	4	2013	18.2	2008	18.3	**2012**	**18.3**
434.zeusmp	4	862	42.2	**871**	**41.8**	871	41.8	4	885	41.1	**872**	**41.7**	872	41.7
435.gromacs	4	380	75.3	381	75.0	**380**	**75.2**	4	**375**	**76.1**	377	75.7	374	76.3
436.cactusADM	4	1007	47.5	**1007**	**47.5**	1009	47.4	1	188	63.4	184	64.8	**187**	**63.9**
437.leslie3d	4	2503	15.0	**2517**	**14.9**	2523	14.9	4	2138	17.6	**2139**	**17.6**	2139	17.6
444.namd	4	**508**	**63.1**	508	63.1	509	63.0	4	504	63.6	**505**	**63.5**	512	62.7
447.dealII	4	599	76.4	611	74.9	**609**	**75.2**	4	570	80.2	577	79.3	**575**	**79.6**
450.soplex	4	**1611**	**20.7**	1611	20.7	1597	20.9	4	1272	26.2	1274	26.2	**1273**	**26.2**
453.povray	4	211	101	211	101	**211**	**101**	4	**180**	**118**	180	118	179	119
454.calculix	4	540	61.1	552	59.8	**551**	**59.8**	4	390	84.5	**392**	**84.2**	397	83.2
459.GemsFDTD	4	2730	15.5	**2709**	**15.7**	2703	15.7	4	2700	15.7	2690	15.8	**2699**	**15.7**
465.tonto	4	**620**	**63.5**	617	63.8	620	63.5	4	605	65.1	**608**	**64.7**	608	64.7
470.lbm	4	**3312**	**16.6**	3312	16.6	3311	16.6	4	3357	16.4	**3355**	**16.4**	3354	16.4
481.wrf	4	1478	30.2	1480	30.2	**1479**	**30.2**	4	**1486**	**30.1**	1486	30.1	1485	30.1
482.sphinx3	4	2573	30.3	**2620**	**29.8**	2629	29.6	4	**2382**	**32.7**	2411	32.3	2370	32.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
  except for 436.cactusADM at peak.
 OMP_NUM_THREADS set to number of cores
```

Platform Notes

```
Bios settings:
Hardware Prefetcher:          Disabled
Adjacent Cache Line Prefetch: Disabled
Intel SpeedStep Technology:   Disabled
```

General Notes

```
All benchmarks compiled in 64-bit mode except 437.leslie3d,
450.soplex, 470.lbm and 482.sphinx3, for peak, are
compiled in 32-bit mode
 The NEC Express5800/120Rh-1(Intel Xeon X5450),
 the NEC Express5800/120Rj-2(Intel Xeon X5450),
 the Bull NovaScale R440 E1 (Intel Xeon X5450,3.00GHz) and
 the Bull NovaScale R460 E1 (Intel Xeon X5450,3.00GHz) models are electronically equivalent.
 The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon X5450) model.
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

Base Portability Flags

410.bwaves:	`-DSPEC_CPU_LP64`
416.gamess:	`-DSPEC_CPU_LP64`
433.milc:	`-DSPEC_CPU_LP64`
434.zeusmp:	`-DSPEC_CPU_LP64`
435.gromacs:	`-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM:	`-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d:	`-DSPEC_CPU_LP64`
444.namd:	`-DSPEC_CPU_LP64`
447.dealII:	`-DSPEC_CPU_LP64`
450.soplex:	`-DSPEC_CPU_LP64`
453.povray:	`-DSPEC_CPU_LP64`
454.calculix:	`-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD:	`-DSPEC_CPU_LP64`
465.tonto:	`-DSPEC_CPU_LP64`
470.lbm:	`-DSPEC_CPU_LP64`
481.wrf:	`-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`
482.sphinx3:	`-DSPEC_CPU_LP64`

Base Optimization Flags

C benchmarks:
`-fast`

C++ benchmarks:
`-fast`

Fortran benchmarks:
`-fast`

Benchmarks using both Fortran and C:
`-fast`

Peak Compiler Invocation

C benchmarks (except as noted below):
`/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib -I/opt/intel/cc/10.1.008/include`

433.milc: `icc`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `/opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib -I/opt/intel/cc/10.1.008/include`

Fortran benchmarks (except as noted below):
`ifort`

437.leslie3d: `/opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib -I/opt/intel/fc/10.1.008/include`

Benchmarks using both Fortran and C:
`icc ifort`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`

Continued on next page

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias -auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch -opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0 -prefetch

Continued on next page

Peak Optimization Flags (Continued)

465.tonto: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -auto`

Benchmarks using both Fortran and C:

435.gromacs: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -prefetch -auto-ilp32`

436.cactusADM: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -prefetch -parallel -auto-ilp32`

454.calculix: `-fast -unroll-aggressive -auto-ilp32`

481.wrf: `-fast -auto-ilp32`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:55:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.