# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S4, Intel Xeon E5420, 2.50 GHz

SPECint®2006 = 22.8

SPECint_base2006 = 19.8

**CPU2006 license:** 22
**Test sponsor:** Fujitsu Siemens Computers
**Tested by:** Fujitsu Siemens Computers

**Test date:** Jul-2008
**Hardware Availability:** Dec-2007
**Software Availability:** Nov-2007




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5420 |
| CPU Characteristics: | 1333 MHz system bus |
| CPU MHz: | 2500 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 12 MB I+D on chip per chip, 6 MB shared / 2 cores |
| L3 Cache: | None |
| Other Cache: | None |
| Memory: | 16 GB (8x2 GB PC2-5300F, 2 rank, CL 5-5-5, ECC) |
| Disk Subsystem: | 1x SAS, 73 GB, 15000 rpm |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp |
| Compiler: | Intel C++ Compiler for Linux32 and Linux64, Version 10.1, Build 20070913 |
| Auto Parallel: | Yes |
| File System: | ext2 |
| System State: | Multi-User Run Level 3 |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | MicroQuill SmartHeap Library, Version 8.1<br>binutils-2.17.50.0.5-0.1.x86_64 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S4, Intel Xeon E5420, 2.50 GHz

SPECint2006 = 22.8

SPECint_base2006 = 19.8

**CPU2006 license:** 22
**Test sponsor:** Fujitsu Siemens Computers
**Tested by:** Fujitsu Siemens Computers

**Test date:** Jul-2008
**Hardware Availability:** Dec-2007
**Software Availability:** Nov-2007

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 595 | 16.4 | 613 | 15.9 | **603** | **16.2** | **481** | **20.3** | 482 | 20.3 | 481 | 20.3 |
| 401.bzip2 | **708** | **13.6** | 706 | 13.7 | 710 | 13.6 | **655** | **14.7** | 655 | 14.7 | 658 | 14.7 |
| 403.gcc | **611** | **13.2** | 611 | 13.2 | 606 | 13.3 | **468** | **17.2** | 468 | 17.2 | 468 | 17.2 |
| 429.mcf | 453 | 20.1 | 451 | 20.2 | **452** | **20.2** | 420 | 21.7 | **421** | **21.7** | 421 | 21.6 |
| 445.gobmk | 636 | 16.5 | **636** | **16.5** | 637 | 16.5 | **574** | **18.3** | 574 | 18.3 | 574 | 18.3 |
| 456.hmmer | 711 | 13.1 | 712 | 13.1 | **712** | **13.1** | **410** | **22.8** | 410 | 22.8 | 409 | 22.8 |
| 458.sjeng | **806** | **15.0** | 810 | 14.9 | 804 | 15.0 | **721** | **16.8** | 721 | 16.8 | 729 | 16.6 |
| 462.libquantum | 108 | 192 | 110 | 188 | **109** | **191** | 105 | 198 | **105** | **196** | 106 | 195 |
| 464.h264ref | 852 | 26.0 | 854 | 25.9 | **853** | **25.9** | 801 | 27.6 | **801** | **27.6** | 804 | 27.5 |
| 471.omnetpp | **446** | **14.0** | 447 | 14.0 | 445 | 14.0 | **407** | **15.3** | 407 | 15.3 | 408 | 15.3 |
| 473.astar | 550 | 12.8 | 550 | 12.8 | **550** | **12.8** | 502 | 14.0 | **503** | **14.0** | 507 | 13.8 |
| 483.xalancbmk | **319** | **21.6** | 319 | 21.6 | 319 | 21.6 | **319** | **21.6** | 319 | 21.6 | 319 | 21.6 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores (default)

## Platform Notes

Hardware Prefetch = Enable, Adjacent Sector Prefetch = Enable

## General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hmmer in peak were built with 64-bit Intel
compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
http://www.fujitsu-siemens.com

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

## Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page

## Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch -auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive -auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.xml`


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:10:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 September 2008.