



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp®\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

CPU2006 license: 9016


Test date: May-2009

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Mar-2009

Tested by: ASUSTeK Computer Inc.

Software Availability: Feb-2009



**SPECfp\_rate\_base2006 = 193**

**SPECfp\_rate2006 = 199**

### Hardware

CPU Name: Intel Xeon X5570  
CPU Characteristics: Intel Turbo Boost Technology up to 3.33 GHz  
CPU MHz: 2933  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2 with patch Kernel linux 20090119, Kernel 2.6.16.60-0.34-smp  
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20090131 Package ID: l\_cproc\_p\_11.0.080, l\_cprof\_p\_11.0.080  
Auto Parallel: No  
File System: ReiserFS  
System State: Run level 3 (multi-user)

*Continued on next page*

*Continued on next page*



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

**CPU2006 license:** 9016

**Test date:** May-2009

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Mar-2009

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Feb-2009

L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 X 4 GB PC3-10600R, CL=9)  
 Disk Subsystem: HITACHI HDT725050VLA360 500GB SATAII, 7200RPM  
 Other Hardware: None

Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	1360	160	<b>1216</b>	<b>179</b>	1193	182	8	569	191	<b>568</b>	<b>192</b>	566	192
416.gamess	16	1478	212	1516	207	<b>1492</b>	<b>210</b>	8	753	208	752	208	<b>752</b>	<b>208</b>
433.milc	16	809	181	810	181	<b>810</b>	<b>181</b>	16	823	178	<b>905</b>	<b>162</b>	994	148
434.zeusmp	16	694	210	695	209	<b>694</b>	<b>210</b>	16	661	220	<b>682</b>	<b>213</b>	684	213
435.gromacs	16	558	205	<b>561</b>	<b>204</b>	562	203	16	538	212	<b>542</b>	<b>211</b>	542	211
436.cactusADM	16	<b>832</b>	<b>230</b>	828	231	832	230	16	<b>880</b>	<b>217</b>	935	205	873	219
437.leslie3d	16	1097	137	1100	137	<b>1098</b>	<b>137</b>	8	<b>558</b>	<b>135</b>	557	135	558	135
444.namd	16	<b>673</b>	<b>191</b>	670	192	678	189	16	659	195	<b>667</b>	<b>192</b>	670	191
447.dealII	16	628	291	626	292	<b>627</b>	<b>292</b>	16	588	311	606	302	<b>595</b>	<b>308</b>
450.soplex	16	921	145	903	148	<b>903</b>	<b>148</b>	8	485	137	<b>449</b>	<b>149</b>	440	151
453.povray	16	<b>305</b>	<b>279</b>	305	279	305	279	16	255	333	250	341	<b>250</b>	<b>340</b>
454.calculix	16	541	244	544	243	<b>541</b>	<b>244</b>	16	<b>542</b>	<b>243</b>	543	243	542	243
459.GemsFDTD	16	1442	118	1557	109	<b>1519</b>	<b>112</b>	8	672	126	675	126	<b>674</b>	<b>126</b>
465.tonto	16	748	211	<b>739</b>	<b>213</b>	723	218	16	687	229	697	226	<b>688</b>	<b>229</b>
470.lbm	16	<b>1752</b>	<b>126</b>	1751	126	1752	125	8	819	134	<b>819</b>	<b>134</b>	820	134
481.wrf	16	768	233	820	218	<b>787</b>	<b>227</b>	16	768	233	820	218	<b>787</b>	<b>227</b>
482.sphinx3	16	1511	206	1497	208	<b>1498</b>	<b>208</b>	16	<b>1451</b>	<b>215</b>	1439	217	<b>1441</b>	<b>216</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Component Notes

Tested system case compliance with Intel EEB 3.61 spec  
 SSI Server Power Supply 650W or higher  
 System was configured with ASPEED AST2050 VGA (on board VGA)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

**CPU2006 license:** 9016

**Test date:** May-2009

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Mar-2009

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Feb-2009

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

**CPU2006 license:** 9016

**Test date:** May-2009

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Mar-2009

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Feb-2009

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: ifort -m32

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias

470.lbm: -xsse4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

**CPU2006 license:** 9016

**Test date:** May-2009

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Mar-2009

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll12

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -fno-alias -auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -unroll12 -ansi-alias -scalar-rep-

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -unroll12 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)

437.leslie3d: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -unroll12 -Ob0 -opt-prefetch

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -opt-prefetch -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS TS500-E6 (Z8NA-D6) server system (Intel Xeon X5570)

**SPECfp\_rate2006 = 199**

**SPECfp\_rate\_base2006 = 193**

**CPU2006 license:** 9016

**Test date:** May-2009

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Mar-2009

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

436.cactusADM: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -auto-ilp32

454.calculix: -xsse4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090710.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090710.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 01:26:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 23 June 2009.