SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC Enterprise M8000

SPECfp®_rate2006 = 666

SPECfp_rate_base2006 = 616

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Sun Microsystems

Test date: Oct-2009
Hardware Availability: Nov-2009
Software Availability: Oct-2009



Hardware

CPU Name:	SPARC64 VII
CPU Characteristics:	
CPU MHz:	2880
FPU:	Integrated
CPU(s) enabled:	64 cores, 16 chips, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1 to 4 CMUs; each CMU contains 2 or 4 CPU chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	6 MB I+D on chip per chip

Continued on next page

Software

Operating System:	Solaris 10 10/09 (s10s_u8wos_06)
Compiler:	Sun Studio 12 Update 1 plus patches (see notes)
Auto Parallel:	Yes
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC Enterprise M8000

SPECfp_rate2006 = 666

SPECfp_rate_base2006 = 616

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Sun Microsystems

Test date: Oct-2009
Hardware Availability: Nov-2009
Software Availability: Oct-2009

L3 Cache: None
Other Cache: None
Memory: 512 GB (128 x 4 GB), 8-way interleaved
Disk Subsystem: 886 GB mirrored partition on 12 x 146GB 15000 RPM SAS disks in each of 2 Sun StorageTek 2530 Array (24 total disk, 12 in each array)
Other Hardware: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	127	3259	530	**3203**	**539**	3203	539	127	3259	530	**3203**	**539**	3203	539
416.gamess	127	3203	776	**3238**	**768**	3242	767	127	2678	929	**2678**	**929**	2731	911
433.milc	127	4087	285	4069	287	**4072**	**286**	127	4062	287	4080	286	**4063**	**287**
434.zeusmp	127	1626	711	1643	704	**1634**	**707**	127	1626	711	1643	704	**1634**	**707**
435.gromacs	127	**936**	**968**	941	963	935	970	127	867	1050	**858**	**1060**	845	1070
436.cactusADM	127	**1519**	**999**	1513	1000	1527	994	127	**1519**	**999**	1513	1000	1527	994
437.leslie3d	127	**3120**	**383**	3126	382	3100	385	127	3023	395	3013	396	**3015**	**396**
444.namd	127	1091	934	**1092**	**933**	1100	926	127	995	1020	990	1030	**992**	**1030**
447.dealII	127	1099	1320	1089	1330	**1089**	**1330**	127	1099	1320	1089	1330	**1089**	**1330**
450.soplex	127	3399	312	3388	313	**3393**	**312**	127	3399	312	3388	313	**3393**	**312**
453.povray	127	615	1100	616	1100	**616**	**1100**	127	510	1330	**507**	**1330**	503	1340
454.calculix	127	1020	1030	**1019**	**1030**	1018	1030	127	1019	1030	**1019**	**1030**	1013	1030
459.GemsFDTD	127	5050	267	5038	267	**5043**	**267**	127	4679	288	**4661**	**289**	4647	290
465.tonto	127	**1605**	**779**	1601	781	1606	778	127	1494	836	**1482**	**843**	1477	846
470.lbm	127	5214	335	5213	335	**5213**	**335**	1	23.7	579	**24.0**	**574**	24.1	570
481.wrf	127	**2339**	**606**	2342	606	2330	609	127	**2339**	**606**	2342	606	2330	609
482.sphinx3	127	5334	464	**5297**	**467**	5287	468	127	**5184**	**477**	5182	478	5190	477

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
Sun Studio 12 Update 1 was used, plus patch 119963-17

Sun Studio compiler patches are available at
  http://developers.sun.com/sunstudio/downloads/patches/ss12u1_patches.jsp
```

Submit Notes

```
Processes were assigned to specific processors using 'pbind'
commands.  The config file option 'submit' was used, along
with a list of processors in the 'BIND' variable, to generate
```

Continued on next page

Submit Notes (Continued)

```
the pbind commands.  (For details, please see the config file.)
```

Operating System Notes

```
Other System Settings:

The webconsole service was turned off using
    svcadm disable webconsole
```

Platform Notes

```
Memory is 8-way interleaved by filling all slots with
the same capacity DIMMs.

This result is measured on a Sun SPARC Enterprise M8000
Server.  The Sun SPARC Enterprise M8000 and the Fujitsu
SPARC Enterprise M8000 are electrically equivalent.
```

General Notes

```
Environment variables set by runspec before the start of the run:
  OMP_NUM_THREADS = "128"
  SUNW_MP_PROCBIND = "true"
  SUNW_MP_THR_IDLE = "SPIN"

447.dealII (peak): "apache_stdcxx_4_2_1" src.alt was used.

447.dealII (base): "apache_stdcxx_4_2_1" src.alt was used.
```

Base Compiler Invocation

C benchmarks:
```
cc
```

C++ benchmarks:
```
CC
```

Fortran benchmarks:
```
f90
```

Benchmarks using both Fortran and C:
```
cc f90
```

Base Optimization Flags

C benchmarks:
```
-fast -fma=fused -xipo=2 -xpagesize=4M -xalias_level=std
-xprefetch_auto_type=indirect_array_access -xprefetch_level=3
```

C++ benchmarks:
```
-xdepend -fast -fma=fused -xipo=2 -xpagesize=4M
-xalias_level=compatible -xprefetch=latx:0.5 -library=no%Cstd
-I/export/home/apache/stdcxx-4.2.1/include
-I/export/home/apache/stdcxx-4.2.1/build/include
-L/export/home/apache/stdcxx-4.2.1/build/lib
-R/export/home/apache/stdcxx-4.2.1/build/lib -lstd8d
```

Fortran benchmarks:
```
-fast -fma=fused -xipo=2 -xpagesize=4M -xprefetch_level=2
```

Benchmarks using both Fortran and C:
```
-fast(cc) -fast(f90) -fma=fused -xipo=2 -xpagesize=4M
-xalias_level=std -xprefetch_auto_type=indirect_array_access
-xprefetch_level=3 -xprefetch_level=2
```

Base Other Flags

C benchmarks:
```
-xjobs=32 -V -#
```

C++ benchmarks:
```
-xjobs=32 -verbose=diags,version
```

Fortran benchmarks:
```
-xjobs=32 -V -v
```

Benchmarks using both Fortran and C:
```
-xjobs=32 -V -# -v
```

Peak Compiler Invocation

C benchmarks:
```
cc
```

C++ benchmarks:
```
CC
```

Fortran benchmarks:
```
f90
```

Continued on next page

Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:
cc f90

Peak Optimization Flags

C benchmarks:

433.milc: -fast -xpagesize=4M -fma=fused -xipo=2 -xprefetch_level=2
-fsimple=1 -xprefetch_auto_type=indirect_array_access
-W2,-Ainline:rs=400 -xalias_level=std

470.lbm: -fast -xpagesize=4M -xprefetch_level=3 -xipo=2 -fma=fused
-xvector -xarch=generic -xautopar -xreduction

482.sphinx3: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-fma=fused -xipo=2 -xinline= -xprefetch=no%auto
-xalias_level=strong -lfast -ll2amm

C++ benchmarks:

444.namd: -xdepend -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=compatible -library=stlport4 -fma=fused
-xipo=2 -xprefetch=no%auto -xlinkopt=2

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xdepend -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=compatible -library=stlport4 -xipo=2
-xlinkopt=2

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-fma=fused -xipo=2 -xprefetch=no%auto

434.zeusmp: basepeak = yes

437.leslie3d: -fast -xpagesize=4M -xprefetch=no

Continued on next page

Peak Optimization Flags (Continued)

459.GemsFDTD: `-fast -xpagesize=4M -fma=fused -fsimple=1 -xprefetch=no`

465.tonto: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -xpagesize=4M`
`-xipo=2 -xprefetch=no -lfast -ll2amm`

Benchmarks using both Fortran and C:

435.gromacs: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast`(cc) `-fast`(f90)
`-xpagesize=4M -fma=fused -xipo=2 -xchip=generic -xinline=`
`-fsimple=0`

436.cactusADM: `basepeak = yes`

454.calculix: `-fast`(cc) `-fast`(f90) `-xpagesize=4M -fma=fused -xipo=2`
`-xprefetch_level=1 -xalias_level=std`
`-xprefetch_auto_type=indirect_array_access`

481.wrf: `basepeak = yes`

Peak Other Flags

C benchmarks:
`-xjobs=32 -V -#`

C++ benchmarks:
`-xjobs=32 -verbose=diags,version`

Fortran benchmarks:
`-xjobs=32 -V -v`

Benchmarks using both Fortran and C:
`-xjobs=32 -V -# -v`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r4.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-12u1-and-gccfss4.2.r4.xml`

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

Fujitsu SPARC Enterprise M8000

SPECfp_rate2006 = 666

SPECfp_rate_base2006 = 616

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Sun Microsystems

Test date: Oct-2009
Hardware Availability: Nov-2009
Software Availability: Oct-2009

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 04:08:23 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 28 October 2009.