# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY TX300 S6, Intel Xeon X5667, 3.06 GHz

SPECfp®_rate2006 = 215

SPECfp_rate_base2006 = 207

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2010
**Hardware Availability:** Apr-2010
**Software Availability:** Jan-2010




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5667 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.46 GHz |
| CPU MHz: | 3067 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 (x86_64), Kernel 2.6.27.19-5-default |
| Compiler: | Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l_cproc_p_11.1.064, l_cprof_p_11.1.064 |
| Auto Parallel: | No |
| File System: | ext3 |
| System State: | Multi-User Run Level 3 |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY TX300 S6, Intel Xeon X5667, 3.06 GHz

SPECfp_rate2006 = 215

SPECfp_rate_base2006 = 207

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2010
**Hardware Availability:** Apr-2010
**Software Availability:** Jan-2010

L3 Cache: 12 MB I+D on chip per chip
Other Cache: None
Memory: 48 GB (12x4 GB PC3-10600R, 2 rank, CL9-9-9, ECC)
Disk Subsystem: 1 x SATA, 160 GB, 5.4 krpm
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 16 | 1107 | 196 | **1108** | **196** | 1112 | 196 | 8 | 541 | 201 | 539 | 202 | **540** | **201** |
| 416.gamess | 16 | **1466** | **214** | 1478 | 212 | 1452 | 216 | 16 | 1444 | 217 | 1482 | 211 | **1455** | **215** |
| 433.milc | 16 | 673 | 218 | 674 | 218 | **674** | **218** | 16 | **672** | **218** | 672 | 218 | 673 | 218 |
| 434.zeusmp | 16 | **602** | **242** | 599 | 243 | 637 | 228 | 16 | **602** | **242** | 599 | 243 | 637 | 228 |
| 435.gromacs | 16 | 550 | 208 | **557** | **205** | 559 | 205 | 16 | 546 | 209 | **552** | **207** | 553 | 207 |
| 436.cactusADM | 16 | 776 | 247 | 776 | 246 | **776** | **246** | 16 | 776 | 247 | 776 | 246 | **776** | **246** |
| 437.leslie3d | 16 | 1124 | 134 | 1115 | 135 | **1116** | **135** | 8 | 532 | 141 | **532** | **141** | 532 | 141 |
| 444.namd | 16 | **657** | **195** | 657 | 195 | 658 | 195 | 16 | **637** | **201** | 637 | 202 | 640 | 201 |
| 447.dealII | 16 | 544 | 336 | **542** | **338** | 541 | 338 | 16 | 544 | 336 | **542** | **338** | 541 | 338 |
| 450.soplex | 16 | 848 | 157 | **849** | **157** | 849 | 157 | 8 | **400** | **167** | 400 | 167 | 401 | 166 |
| 453.povray | 16 | **292** | **291** | 292 | 292 | 292 | 291 | 16 | **241** | **354** | 242 | 351 | 240 | 354 |
| 454.calculix | 16 | **510** | **259** | 511 | 259 | 510 | 259 | 16 | **510** | **259** | 511 | 259 | 510 | 259 |
| 459.GemsFDTD | 16 | 1345 | 126 | 1341 | 127 | **1344** | **126** | 8 | 641 | 132 | **639** | **133** | 639 | 133 |
| 465.tonto | 16 | 656 | 240 | **654** | **241** | 652 | 242 | 16 | 629 | 250 | 613 | 257 | **614** | **256** |
| 470.lbm | 16 | 1741 | 126 | **1742** | **126** | 1744 | 126 | 8 | 808 | 136 | 809 | 136 | **809** | **136** |
| 481.wrf | 16 | 753 | 237 | **756** | **237** | 756 | 236 | 16 | 753 | 237 | **756** | **237** | 756 | 236 |
| 482.sphinx3 | 16 | 1448 | 215 | **1450** | **215** | 1452 | 215 | 16 | 1352 | 231 | 1354 | 230 | **1354** | **230** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
 numactl was used to bind copies to the cores
```

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
```

## Platform Notes

```
BIOS configuration:
Data Reuse Optimization = Disabled
```

## General Notes

```
This result was measured on the PRIMERGY RX300 S6. The PRIMERGY RX300 S6
and the PRIMERGY TX300 S6 are electronically equivalent.

For information about Fujitsu please visit: http://www.fujitsu.com
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static
```

C++ benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static
```

Continued on next page

## Base Optimization Flags (Continued)

Fortran benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`icc -m64`

482.sphinx3: `icc -m32`

C++ benchmarks (except as noted below):
`icpc -m64`

450.soplex: `icpc -m32`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

## Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
470.lbm: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -fno-alias -opt-prefetch

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -ansi-alias -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

Continued on next page

## Peak Optimization Flags (Continued)

435.gromacs: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-opt-prefetch -auto-ilp32`

436.cactusADM: `basepeak = yes`

454.calculix: `basepeak = yes`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.01.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.01.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 05:07:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 30 March 2010.