SPEC® CFP2006 Result

Hewlett-Packard Company

ProLiant DL380 G7
(2.27 GHz, Intel Xeon E5607)

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license:	3	**Test date:**	Feb-2011
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Feb-2011
Tested by:	Hewlett-Packard Company	**Software Availability:**	Dec-2010

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Hardware

CPU Name:	Intel Xeon E5607
CPU Characteristics:	
CPU MHz:	2267
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	96 GB (12 x 8 GB 2Rx4 PC3-10600R-9, ECC, running at 1067 MHz)
Disk Subsystem:	1 x 300 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 11 (x86_64) SP1, Kernel 2.6.32.12-0.7-default
Compiler:	Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116
Auto Parallel:	No
File System:	ext3
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	None

SPEC CFP2006 Result

Hewlett-Packard Company

ProLiant DL380 G7
(2.27 GHz, Intel Xeon E5607)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2011
Hardware Availability: Feb-2011
Software Availability: Dec-2010

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
416.gamess	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
433.milc	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
434.zeusmp	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
435.gromacs	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
436.cactusADM	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
437.leslie3d	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
444.namd	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
447.dealII	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
450.soplex	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
453.povray	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
454.calculix	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
459.GemsFDTD	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
465.tonto	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
470.lbm	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
481.wrf	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
482.sphinx3	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
numactl was used to bind copies to the cores
```

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Operating System Notes

```
'nodev   /mnt/hugepages   hugetlbfs   defaults   0 0' added to /etc/fstab
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
echo 3600 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

Platform Notes

```
BIOS configuration:
 HP Power Profile set to Maximum Performance
 Thermal Configuration set to Increased Cooling
 Data Reuse set to Disabled
```

General Notes

```
Binaries were compiled on RHEL5.5
```

Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc   -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

Hewlett-Packard Company

ProLiant DL380 G7
(2.27 GHz, Intel Xeon E5607)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2011
Hardware Availability: Feb-2011
Software Availability: Dec-2010

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

SPEC CFP2006 Result

Hewlett-Packard Company

ProLiant DL380 G7
(2.27 GHz, Intel Xeon E5607)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2011
Hardware Availability: Feb-2011
Software Availability: Dec-2010

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Peak Compiler Invocation

C benchmarks (except as noted below):
```
icc   -m64
```

482.sphinx3: `icc -m32`

C++ benchmarks (except as noted below):
```
icpc  -m64
```

450.soplex: `icpc -m32`

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
470.lbm: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Hewlett-Packard Company

ProLiant DL380 G7
(2.27 GHz, Intel Xeon E5607)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company
Test date: Feb-2011
Hardware Availability: Feb-2011
Software Availability: Dec-2010

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -ansi-alias -opt-prefetch -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

Continued on next page

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

Peak Optimization Flags (Continued)

437.leslie3d: `-xSSE4.2 -ipo -O3 -no-prec-div`
`-B /usr/share/libhugetlbfs/ld.hugetlbfs -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT`

459.GemsFDTD: `basepeak = yes`

465.tonto: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2)
`-no-prec-div`(pass 2) `-prof-use`(pass 2) `-unroll4 -auto`
`-inline-calloc -opt-malloc-options=3`
`-B /usr/share/libhugetlbfs/ld.hugetlbfs -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT`

Benchmarks using both Fortran and C:

435.gromacs: `basepeak = yes`

436.cactusADM: `basepeak = yes`

454.calculix: `basepeak = yes`

481.wrf: `basepeak = yes`

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html
http://www.spec.org/cpu2006/flags/HP-Intel-Linux-Settings-flags.20110316.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml
http://www.spec.org/cpu2006/flags/HP-Intel-Linux-Settings-flags.20110316.xml

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability of the system.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 16:43:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 16 March 2011.