# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 F2 (Intel Xeon E5606, 2.13 GHz)

SPECfp®_rate2006 = 131

SPECfp_rate_base2006 = 128

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** Feb-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Jan-2010




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5606 |
| CPU Characteristics: | |
| CPU MHz: | 2133 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.12-0.7-default |
| Compiler: | Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116 |
| Auto Parallel: | No |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 64-bit |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 F2 (Intel Xeon E5606, 2.13 GHz)

SPECfp_rate2006 = 131

SPECfp_rate_base2006 = 128

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** Feb-2011
**Hardware Availability:** Feb-2011
**Software Availability:** Jan-2010

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC, running at 1066 MHz)
Disk Subsystem: 146 GB 10000 RPM SAS
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: None

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 8 | 848 | 128 | 845 | 129 | **845** | **129** | 8 | 848 | 128 | 845 | 129 | **845** | **129** |
| 416.gamess | 8 | 1143 | 137 | 1142 | 137 | **1143** | **137** | 8 | 1143 | 137 | 1142 | 137 | **1143** | **137** |
| 433.milc | 8 | 550 | 133 | 550 | 133 | **550** | **133** | 8 | 545 | 135 | **545** | **135** | 546 | 135 |
| 434.zeusmp | 8 | 508 | 143 | **507** | **144** | 506 | 144 | 8 | 508 | 143 | **507** | **144** | 506 | 144 |
| 435.gromacs | 8 | 477 | 120 | 480 | 119 | **478** | **119** | 8 | 481 | 119 | 482 | 118 | **481** | **119** |
| 436.cactusADM | 8 | 678 | 141 | **676** | **141** | 673 | 142 | 8 | 678 | 141 | **676** | **141** | 673 | 142 |
| 437.leslie3d | 8 | 824 | 91.2 | **825** | **91.1** | 829 | 90.8 | 8 | 824 | 91.2 | **825** | **91.1** | 829 | 90.8 |
| 444.namd | 8 | 644 | 99.6 | 645 | 99.5 | **644** | **99.6** | 8 | **636** | **101** | 635 | 101 | 636 | 101 |
| 447.dealII | 8 | **503** | **182** | 511 | 179 | 501 | 183 | 8 | **503** | **182** | 511 | 179 | 501 | 183 |
| 450.soplex | 8 | **687** | **97.2** | 687 | 97.1 | 686 | 97.3 | 8 | **687** | **97.2** | 687 | 97.1 | 686 | 97.3 |
| 453.povray | 8 | **269** | **158** | 270 | 158 | 268 | 159 | 8 | 215 | 198 | 214 | 199 | **214** | **199** |
| 454.calculix | 8 | 406 | 163 | **406** | **163** | 406 | 163 | 8 | 406 | 163 | **406** | **163** | 406 | 163 |
| 459.GemsFDTD | 8 | **1002** | **84.7** | 1010 | 84.0 | 1000 | 84.9 | 8 | **1002** | **84.7** | 1010 | 84.0 | 1000 | 84.9 |
| 465.tonto | 8 | 562 | 140 | **558** | **141** | 556 | 141 | 8 | **543** | **145** | 547 | 144 | 542 | 145 |
| 470.lbm | 8 | 972 | 113 | **972** | **113** | 972 | 113 | 4 | 421 | 131 | **421** | **131** | 421 | 130 |
| 481.wrf | 8 | 592 | 151 | 594 | 150 | **593** | **151** | 8 | 592 | 151 | 594 | 150 | **593** | **151** |
| 482.sphinx3 | 8 | 1192 | 131 | **1190** | **131** | 1189 | 131 | 8 | 1160 | 134 | 1162 | 134 | **1160** | **134** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
 numactl was used to bind copies to the cores
```

## Operating System Notes

```
 'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 7200 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

```
BIOS Settings:
Power Management = Maximum Performance (Default =  Active Power Controller)
Data Reuse = Disabled (Default = Enabled)
```

## General Notes

```
The Dell PowerEdge R710 and
the Bull NovaScale R460 F2 models are electronically equivalent.
The results have been measured on a Dell PowerEdge R710 model.
Binaries were compiled on RHEL5.5
```

## Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias`

C++ benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias`

Fortran benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`icc -m64`

482.sphinx3: `icc -m32`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

## Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
450.soplex: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
470.lbm: `-DSPEC_CPU_LP64`

Continued on next page

## Peak Portability Flags (Continued)

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -ansi-alias -opt-prefetch -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto -inline-calloc -opt-malloc-options=3 -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Benchmarks using both Fortran and C:

Continued on next page

## Peak Optimization Flags (Continued)

435.gromacs: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2) `-opt-prefetch` `-static -auto-ilp32`

436.cactusADM: `basepeak = yes`

454.calculix: `basepeak = yes`

481.wrf: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html`
`http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110308.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml`
`http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110308.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 15:47:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 March 2011.