SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu
SPARC Enterprise M3000

SPECfp®_rate2006 = 34.9

SPECfp_rate_base2006 = 33.1

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jan-2011
Hardware Availability: Apr-2011
Software Availability: Sep-2010



Hardware

CPU Name:	SPARC64 VII+
CPU Characteristics:	
CPU MHz:	2860
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	5632 KB I+D on chip per chip

Continued on next page

Software

Operating System:	Oracle Solaris 10 9/10
Compiler:	Oracle Solaris Studio 12.2
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	Apache C++ Standard Library V4.2.1

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu
SPARC Enterprise M3000

SPECfp_rate2006 = 34.9

SPECfp_rate_base2006 = 33.1

CPU2006 license: 19
Test sponsor: Fujitsu
Tested by: Fujitsu

Test date: Jan-2011
Hardware Availability: Apr-2011
Software Availability: Sep-2010

L3 Cache: None
Other Cache: None
Memory: 32 GB (8 x 4 GB, 2-way interleaved)
Disk Subsystem: 1 x 300 GB 10,000 RPM SAS
Other Hardware: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1316	41.3	1315	41.3	**1315**	**41.3**	4	1314	41.4	**1314**	**41.4**	1314	41.4
416.gamess	4	2640	29.7	**2645**	**29.6**	2673	29.3	4	**2493**	**31.4**	2480	31.6	2539	30.8
433.milc	4	**1148**	**32.0**	1149	32.0	1144	32.1	4	1095	33.5	**1093**	**33.6**	1093	33.6
434.zeusmp	4	1063	34.2	**1058**	**34.4**	1057	34.4	4	1063	34.2	**1058**	**34.4**	1057	34.4
435.gromacs	4	883	32.3	902	31.7	**901**	**31.7**	4	828	34.5	840	34.0	**828**	**34.5**
436.cactusADM	4	1098	43.5	**1098**	**43.5**	1097	43.6	4	1092	43.8	**1092**	**43.8**	1092	43.8
437.leslie3d	4	1395	27.0	**1392**	**27.0**	1392	27.0	4	**1363**	**27.6**	1370	27.5	1358	27.7
444.namd	4	975	32.9	982	32.7	**979**	**32.8**	4	922	34.8	909	35.3	**920**	**34.9**
447.dealII	4	**749**	**61.1**	773	59.2	746	61.3	4	**706**	**64.8**	706	64.8	745	61.4
450.soplex	4	**1465**	**22.8**	1468	22.7	1464	22.8	4	1415	23.6	1416	23.6	**1416**	**23.6**
453.povray	4	616	34.6	**617**	**34.5**	623	34.2	4	461	46.1	464	45.9	**462**	**46.1**
454.calculix	4	**732**	**45.1**	730	45.2	732	45.1	4	689	47.9	690	47.8	**689**	**47.9**
459.GemsFDTD	4	2058	20.6	2060	20.6	**2060**	**20.6**	4	**2025**	**21.0**	2026	20.9	2024	21.0
465.tonto	4	**1061**	**37.1**	1060	37.1	1067	36.9	4	957	41.1	**961**	**40.9**	962	40.9
470.lbm	4	2613	21.0	2612	21.0	**2612**	**21.0**	2	1288	21.3	1287	21.3	**1288**	**21.3**
481.wrf	4	1243	36.0	**1244**	**35.9**	1247	35.8	4	1198	37.3	**1202**	**37.2**	1202	37.2
482.sphinx3	4	2387	32.7	**2380**	**32.8**	2378	32.8	4	2283	34.2	2286	34.1	**2285**	**34.1**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
  Oracle Solaris Studio 12.2 is distributed with mandatory OS patches
   118683-05  119963-20  120753-08
  Oracle Solaris Studio 12.2 and patches are available at
   http://oracle.com/goto/solarisstudio

The Apache C++ Standard Library V4.2.1 was installed from
   http://stdcxx.apache.org/download.html using:
     alias gmake=specmake
     gmake BUILDTYPE=8d CONFIG=sunpro.config
```

Submit Notes

```
  Processes were assigned to specific processors using 'pbind'
  commands.  The config file option 'submit' was used, along
  with a list of processors in the 'BIND' variable, to generate
  the pbind commands.  (For details, please see the config file.)
```

Operating System Notes

```
  ulimit -s 131072 was used to limit the space
  consumed by the stack (and therefore make more
  space available to the heap).

System Tunables:
(/etc/system parameters)

    tune_t_fsflushr=10
       Controls how many seconds elapse between runs of the
       page flush daemon, fsflush.
    autoup=600
       Causes pages older than the listed number of seconds to
       be written by fsflush.
    bufhwm=3000
       Memory byte limit for caching I/O buffers.
    segmap_percent=1
       Set maximum percent memory for file system cache.

Other System Settings:

    The "webconsole" service was turned off using
        svcadm disable webconsole
```

Platform Notes

```
  Memory is 2-way interleaved by filling all slots with
  the same capacity DIMMs.

 This result is measured on a SPARC Enterprise M3000 server from
 Fujitsu.  The SPARC Enterprise M3000 server from Oracle and from
 Fujitsu are electrically equivalent.
```

General Notes

```
447.dealII (peak): "apache_stdcxx_4_2_1" src.alt was used.

447.dealII (base): "apache_stdcxx_4_2_1" src.alt was used.
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Fortran benchmarks:
f90

Benchmarks using both Fortran and C:
cc f90

Base Optimization Flags

C benchmarks:
-fast -fma=fused -xipo=2 -xpagesize=4M -xlinkopt -xvector
-xalias_level=std -xprefetch_auto_type=indirect_array_access
-xprefetch_level=3 -xunroll=8 -ll2amm

C++ benchmarks:
-xdepend -fast -fma=fused -xipo=2 -xpagesize=4M -xlinkopt -xvector
-xO4 -xalias_level=compatible -xprefetch=latx:0.5 -library=no%Cstd
-I/mnt/spec//stdcxx-4.2.1/include
-I/mnt/spec//stdcxx-4.2.1/build/include
-L/mnt/spec//stdcxx-4.2.1/build/lib -R/mnt/spec//stdcxx-4.2.1/build/lib
-lstd8d

Fortran benchmarks:
-fast -fma=fused -xipo=2 -xpagesize=4M -xlinkopt -xvector
-xprefetch_level=2 -ll2amm

Benchmarks using both Fortran and C:
-fast(cc) -fast(f90) -fma=fused -xipo=2 -xpagesize=4M -xlinkopt
-xvector -xalias_level=std -xprefetch_auto_type=indirect_array_access
-xprefetch_level=3 -xunroll=8 -xprefetch_level=2 -ll2amm

Base Other Flags

C benchmarks:
-xjobs=4 -V -#

C++ benchmarks:
-xjobs=4 -verbose=diags,version

Fortran benchmarks:
-xjobs=4 -V -v

Continued on next page

Base Other Flags (Continued)

Benchmarks using both Fortran and C:
`-xjobs=4 -V -# -v`

Peak Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:
`CC`

Fortran benchmarks:
`f90`

Benchmarks using both Fortran and C:
`cc f90`

Peak Optimization Flags

C benchmarks:

433.milc: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused`
`-xpagesize=4M -xipo=2 -xarch=generic -xcache=generic`
`-xlinkopt -fsimple=1 -W2,-Ainline:rs=400 -xalias_level=std`
`-xprefetch_auto_type=indirect_array_access -xprefetch_level=3`
`-xunroll=2`

470.lbm: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused`
`-xpagesize=4M -xipo=2 -xO4 -xprefetch_level=2`

482.sphinx3: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused`
`-xpagesize=4M -xipo=1 -xalias_level=strong`
`-xprefetch=latx:1.5 -xunroll=4 -lbsdmalloc`

C++ benchmarks:

444.namd: `-xdepend -xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused`
`-xpagesize=4M -xalias_level=compatible -library=stlport4`
`-xipo=1 -xO3 -xchip=generic -xinline= -xlinkopt`
`-xprefetch_level=2 -xprefetch=latx:2.5 -ll2amm -lfast`

Continued on next page

Peak Optimization Flags (Continued)

447.dealII: -xdepend -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -library=no%Cstd
-I/mnt/spec//stdcxx-4.2.1/include
-I/mnt/spec//stdcxx-4.2.1/build/include -xipo=2
-xchip=generic -xprefetch_auto_type=indirect_array_access
-xrestrict -xprefetch_level=2
-L/mnt/spec//stdcxx-4.2.1/build/lib
-R/mnt/spec//stdcxx-4.2.1/build/lib -lstd8d

450.soplex: -xdepend -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -library=stlport4
-xarch=generic -xprefetch=no%auto

453.povray: -xdepend -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -library=stlport4
-M /usr/lib/ld/map.bssalign -xipo=2 -xO4 -xprefetch=no%auto
-xunroll=4 -lfast -ll2amm -lbsdmalloc

Fortran benchmarks:

410.bwaves: -fast -fma=fused -xpagesize=4M -xipo=2 -xlinkopt
-xprefetch_level=2 -xprefetch=latx:2

416.gamess: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=1 -xO3
-xinline= -xprefetch=no%auto -xunroll=3 -lfast -ll2amm
-lbsdmalloc

434.zeusmp: basepeak = yes

437.leslie3d: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=1 -xO3
-xcache=generic -xprefetch=latx:2 -xunroll=10 -ll2amm

459.GemsFDTD: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=1 -xarch=sparcvis2
-xprefetch_auto_type=indirect_array_access -xprefetch_level=2
-xprefetch=latx:0.1 -xunroll=7

465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xipo=2 -xprefetch=no%auto -xunroll=4
-lbsdmalloc

Continued on next page

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast`(cc) `-fast`(f90)
`-fma=fused -xpagesize=4M -xO4 -xchip=generic`
`-xcache=generic -fsimple=0 -xprefetch=no%auto -xunroll=3`

436.cactusADM: `-fast`(cc) `-fast`(f90) `-fma=fused -xpagesize=4M`
`-xalias_level=std -xunroll=12 -lfast`

454.calculix: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast`(cc) `-fast`(f90)
`-fma=fused -xpagesize=4M -xipo=2 -xcache=generic`
`-xprefetch=latx:3 -xunroll=8 -xalias_level=std -lmopt`

481.wrf: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast`(cc) `-fast`(f90)
`-fma=fused -xpagesize=4M -xalias_level=std -xipo=2 -xO4`
`-xcache=generic -xprefetch_auto_type=indirect_array_access`
`-xprefetch=latx:1`

Peak Other Flags

C benchmarks:
`-xjobs=4 -V -#`

C++ benchmarks:
`-xjobs=4 -verbose=diags,version`

Fortran benchmarks:
`-xjobs=4 -V -v`

Benchmarks using both Fortran and C:
`-xjobs=4 -V -# -v`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 19:09:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 April 2011.