



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp®2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2011

Hardware Availability: Apr-2011

Software Availability: Apr-2011



Hardware

CPU Name: Intel Xeon E7-8837
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip
CPU(s) orderable: 2,4 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.12-0.7-default
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3
Auto Parallel: Yes
File System: ext3
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55

Test date: Mar-2011

Test sponsor: Dell Inc.

Hardware Availability: Apr-2011

Tested by: Dell Inc.

Software Availability: Apr-2011

L3 Cache: 24 MB I+D on chip per chip
 Other Cache: None
 Memory: 512 GB (64 x 8 GB 4Rx8 PC3-8500R-7, ECC)
 Disk Subsystem: 1 x 500 GB 7200 RPM SAS 6Gb
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32.5	418	32.1	424	<u>32.1</u>	<u>424</u>	32.1	424	<u>32.1</u>	<u>424</u>	32.3	421
416.gamess	1048	18.7	1050	18.7	<u>1049</u>	<u>18.7</u>	841	23.3	<u>842</u>	<u>23.3</u>	843	23.2
433.milc	403	22.8	399	23.0	<u>402</u>	<u>22.9</u>	403	22.8	399	23.0	<u>402</u>	<u>22.9</u>
434.zeusmp	90.9	100	<u>90.5</u>	<u>101</u>	90.5	101	90.9	100	<u>90.5</u>	<u>101</u>	90.5	101
435.gromacs	387	18.5	389	18.4	<u>387</u>	<u>18.4</u>	363	19.7	<u>364</u>	<u>19.6</u>	366	19.5
436.cactusADM	24.5	487	<u>24.7</u>	<u>484</u>	24.9	479	24.5	487	<u>24.7</u>	<u>484</u>	24.9	479
437.leslie3d	<u>48.0</u>	<u>196</u>	49.4	190	46.2	203	<u>48.0</u>	<u>196</u>	49.4	190	46.2	203
444.namd	492	16.3	492	16.3	<u>492</u>	<u>16.3</u>	<u>483</u>	<u>16.6</u>	483	16.6	483	16.6
447.dealII	376	30.4	<u>376</u>	<u>30.4</u>	376	30.4	376	30.4	<u>376</u>	<u>30.4</u>	376	30.4
450.soplex	396	21.0	<u>401</u>	<u>20.8</u>	405	20.6	<u>396</u>	<u>21.0</u>	<u>401</u>	<u>20.8</u>	405	20.6
453.povray	204	26.0	<u>205</u>	<u>26.0</u>	207	25.7	<u>163</u>	<u>32.6</u>	163	32.7	164	32.5
454.calculix	354	23.3	<u>358</u>	<u>23.0</u>	362	22.8	<u>302</u>	<u>27.3</u>	301	27.4	302	27.3
459.GemsFDTD	113	93.8	106	100	<u>107</u>	<u>99.4</u>	87.0	122	88.0	121	<u>87.4</u>	<u>121</u>
465.tonto	513	19.2	525	18.7	<u>514</u>	<u>19.2</u>	351	28.0	<u>351</u>	<u>28.0</u>	351	28.1
470.lbm	<u>22.8</u>	<u>602</u>	22.8	602	23.0	597	<u>22.8</u>	<u>602</u>	22.8	602	23.0	597
481.wrf	344	32.4	356	31.4	<u>350</u>	<u>31.9</u>	344	32.4	356	31.4	<u>350</u>	<u>31.9</u>
482.sphinx3	430	45.4	<u>430</u>	<u>45.3</u>	431	45.3	<u>388</u>	<u>50.2</u>	390	50.0	<u>389</u>	<u>50.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

Platform Notes

BIOS Settings:

Power Management = Maximum Performance (Default = Active Power Controller)
 Node Interleaving = Enabled (Default = Disabled)



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55

Test date: Mar-2011

Test sponsor: Dell Inc.

Hardware Availability: Apr-2011

Tested by: Dell Inc.

Software Availability: Apr-2011

General Notes

The Dell PowerEdge R910 and
the Bull NovaScale R480 F2 models are electronically equivalent.
The results have been measured on a Dell PowerEdge R910 model.
OMP_NUM_THREADS set to number of cores
Binaries were compiled on RHEL5.5

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
  433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
  437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
  447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
  465.tonto: -DSPEC_CPU_LP64
  470.lbm: -DSPEC_CPU_LP64
  481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55

Test date: Mar-2011

Test sponsor: Dell Inc.

Hardware Availability: Apr-2011

Tested by: Dell Inc.

Software Availability: Apr-2011

Base Optimization Flags (Continued)

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2011

Hardware Availability: Apr-2011

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

```
453.povray: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias
            -B /usr/share/libhugetlbfsl -Wl,-melf_x86_64 -Wl,-hugetlbfsl-link=BDT
```

Fortran benchmarks:

```
410.bwaves: -xsse4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel
            -static
```

```
416.gamess: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
            -inline-level=0 -scalar-rep -static
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

```
459.GemsFDTD: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll12
            -inline-level=0 -opt-prefetch -parallel
            -B /usr/share/libhugetlbfsl -Wl,-melf_x86_64 -Wl,-hugetlbfsl-link=BDT
```

```
465.tonto: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
            -opt-malloc-options=3 -auto -unroll14
            -B /usr/share/libhugetlbfsl -Wl,-melf_x86_64 -Wl,-hugetlbfsl-link=BDT
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
            -ansi-alias
```

436.cactusADM: basepeak = yes

454.calculix: -xsse4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp2006 = 59.0

PowerEdge R910 (Intel Xeon E7-8837, 2.67 GHz)

SPECfp_base2006 = 54.4

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2011

Hardware Availability: Apr-2011

Software Availability: Apr-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 20:03:34 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 May 2011.