# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

## Huawei RH2285,Intel Xeon X5660

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** Jun-2011
**Hardware Availability:** May-2011
**Software Availability:** Jan-2011

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

| Copies |
|---|
| 410.bwaves |
| 416.gamess |
| 433.milc |
| 434.zeusmp |
| 435.gromacs |
| 436.cactusADM |
| 437.leslie3d |
| 444.namd |
| 447.dealII |
| 450.soplex |
| 453.povray |
| 454.calculix |
| 459.GemsFDTD |
| 465.tonto |
| 470.lbm |
| 481.wrf |
| 482.sphinx3 |

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

## Huawei RH2285,Intel Xeon X5660

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** Jun-2011
**Hardware Availability:** May-2011
**Software Availability:** Jan-2011

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5660 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.20 GHz |
| CPU MHz: | 2850 |
| FPU: | Integrated |
| CPU(s) enabled: | 12 cores, 2 chips, 6 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1,2 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 12 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC) |
| Disk Subsystem: | 1 x 300 GB SAS, 10K RPM |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.12-0.7-default |
| Compiler: | Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.1.116 Build 20101116 |
| Auto Parallel: | No |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | None |

Non-Compliant

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Huawei

## Huawei RH2285,Intel Xeon X5660

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** Jun-2011
**Hardware Availability:** May-2011
**Software Availability:** Jan-2011

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 24 | NC | NC | NC | NC | NC | NC | 12 | NC | NC | NC | NC | NC | NC |
| 416.gamess | 24 | NC | NC | NC | NC | NC | NC | 12 | NC | NC | NC | NC | NC | NC |
| 433.milc | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 434.zeusmp | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 435.gromacs | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 436.cactusADM | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 437.leslie3d | 24 | NC | NC | NC | NC | NC | NC | 12 | NC | NC | NC | NC | NC | NC |
| 444.namd | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 447.dealII | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 450.soplex | 24 | NC | NC | NC | NC | NC | NC | 12 | NC | NC | NC | NC | NC | NC |
| 453.povray | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 454.calculix | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 459.GemsFDTD | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 465.tonto | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 470.lbm | 24 | NC | NC | NC | NC | NC | NC | 12 | NC | NC | NC | NC | NC | NC |
| 481.wrf | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |
| 482.sphinx3 | 24 | NC | NC | NC | NC | NC | NC | 24 | NC | NC | NC | NC | NC | NC |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
 numactl was used to bind copies to the cores
```

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
echo 1 >/proc/sys/vm/zone_reclaim_mode
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 7200 > /proc/sys/vm/nr_hugepages
```

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Operating System Notes (Continued)

```
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

```
Data Reuse Optimization disabled in BIOS Setup.
```

## General Notes

```
Binaries compiled on RHEL 5.5
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
```

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Base Portability Flags (Continued)

447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:
-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):
icpc -m64

450.soplex: icpc -m32

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Peak Compiler Invocation (Continued)

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP
416.gamess: -DSPEC_CPU_LP
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP -nofor_main
437.leslie3d: -DSPEC_CPU_LP
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3
-ansi-alias -opt-prefetch -static -auto-ilp32

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Peak Optimization Flags (Continued)

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3
-B /usr/share/libhugetlbfs/ -Wl,-hugetlbfs-link=BDT

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3
-B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was customized in a manner that did not meet SPEC's requirements for documented and supported systems.**

Non-Compliant

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html
http://www.spec.org/cpu2006/flags/HUAWEI-platform-linux64-revC.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml
http://www.spec.org/cpu2006/flags/HUAWEI-platform-linux64-revC.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 21:46:39 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 5 July 2011.