



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

**SPECfp®2006 = 54.2**

IBM BladeCenter HS22 (Intel Xeon X5647)

**SPECfp\_base2006 = 50.2**

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jun-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011



**SPECfp\_base2006 = 50.2**

**SPECfp2006 = 54.2**

## Hardware

CPU Name: Intel Xeon X5647  
CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz  
CPU MHz: 2933  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86\_64), Kernel 2.6.32.12-0.7-default  
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3  
Auto Parallel: Yes  
File System: ext3  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

**SPECfp2006 = 54.2**

## IBM BladeCenter HS22 (Intel Xeon X5647)

**SPECfp\_base2006 = 50.2**

**CPU2006 license:** 11

**Test date:** Jun-2011

**Test sponsor:** IBM Corporation

**Hardware Availability:** Feb-2011

**Tested by:** IBM Corporation

**Software Availability:** Apr-2011

L3 Cache: 12 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 48 GB (12 x 4 GB 2Rx8 PC3-10600R-9, ECC, running at 1066 MHz)  
 Disk Subsystem: 1 x 73 GB SAS, 10000 RPM  
 Other Hardware: None

Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b>85.3</b>	<b>159</b>	85.5	159	85.3	159	<b>85.3</b>	<b>159</b>	85.5	159	85.3	159
416.gamess	947	20.7	884	22.2	<b>913</b>	<b>21.4</b>	737	26.6	736	26.6	<b>737</b>	<b>26.6</b>
433.milc	189	48.7	188	48.9	<b>188</b>	<b>48.8</b>	186	49.4	<b>186</b>	<b>49.4</b>	186	49.4
434.zeusmp	<b>99.7</b>	<b>91.3</b>	103	88.5	99.3	91.7	<b>99.7</b>	<b>91.3</b>	103	88.5	99.3	91.7
435.gromacs	341	20.9	341	20.9	<b>341</b>	<b>20.9</b>	<b>319</b>	<b>22.4</b>	318	22.4	319	22.4
436.cactusADM	<b>60.2</b>	<b>199</b>	61.6	194	60.0	199	<b>60.2</b>	<b>199</b>	61.6	194	60.0	199
437.leslie3d	92.0	102	94.0	100	<b>92.4</b>	<b>102</b>	92.0	102	94.0	100	<b>92.4</b>	<b>102</b>
444.namd	431	18.6	<b>429</b>	<b>18.7</b>	429	18.7	<b>421</b>	<b>19.0</b>	421	19.0	421	19.0
447.dealII	<b>298</b>	<b>38.3</b>	298	38.3	298	38.3	<b>298</b>	<b>38.3</b>	298	38.3	298	38.3
450.soplex	273	30.5	273	30.6	<b>273</b>	<b>30.5</b>	273	30.5	273	30.6	<b>273</b>	<b>30.5</b>
453.povray	180	29.6	179	29.8	<b>179</b>	<b>29.7</b>	142	37.4	142	37.4	<b>142</b>	<b>37.4</b>
454.calculix	<b>294</b>	<b>28.1</b>	294	28.1	293	28.2	<b>259</b>	31.8	<b>259</b>	<b>31.8</b>	259	31.8
459.GemsFDTD	139	76.5	<b>161</b>	<b>65.9</b>	162	65.5	130	81.4	<b>131</b>	<b>80.9</b>	131	80.9
465.tonto	413	23.8	<b>413</b>	<b>23.8</b>	365	27.0	<b>309</b>	<b>31.9</b>	308	31.9	309	31.9
470.lbm	58.2	236	96.4	142	<b>70.2</b>	<b>196</b>	58.2	236	96.4	142	<b>70.2</b>	<b>196</b>
481.wrf	267	41.8	241	46.3	<b>243</b>	<b>46.0</b>	267	41.8	241	46.3	<b>243</b>	<b>46.0</b>
482.sphinx3	<b>400</b>	<b>48.7</b>	399	48.9	408	47.8	<b>346</b>	<b>56.3</b>	360	54.1	345	56.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'nodev /mnt/hugepages hugetlbfs defaults 0 0' added to /etc/fstab
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```

## Platform Notes

Load Default BIOS Settings and then change the following  
 Turbo Mode enabled  
 Turbo Boost set to Traditional  
 Power C-states enabled  
 Demand Scrub disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	<b>SPECfp2006 =</b>	<b>54.2</b>
IBM BladeCenter HS22 (Intel Xeon X5647)	<b>SPECfp_base2006 =</b>	<b>50.2</b>
<b>CPU2006 license:</b> 11	<b>Test date:</b>	Jun-2011
<b>Test sponsor:</b> IBM Corporation	<b>Hardware Availability:</b>	Feb-2011
<b>Tested by:</b> IBM Corporation	<b>Software Availability:</b>	Apr-2011

## General Notes

Binaries compiled on RHEL5.5  
OMP\_NUM\_THREADS set to number of cores

## Base Compiler Invocation

C benchmarks:

    icc -m64

C++ benchmarks:

    icpc -m64

Fortran benchmarks:

    ifort -m64

Benchmarks using both Fortran and C:

    icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
    433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
    437.leslie3d: -DSPEC\_CPU\_LP64  
    444.namd: -DSPEC\_CPU\_LP64  
    447.dealII: -DSPEC\_CPU\_LP64  
    450.soplex: -DSPEC\_CPU\_LP64  
    453.povray: -DSPEC\_CPU\_LP64  
    454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
    465.tonto: -DSPEC\_CPU\_LP64  
    470.lbm: -DSPEC\_CPU\_LP64  
    481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

    -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
    -ansi-alias

C++ benchmarks:

    -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECfp2006 = 54.2**

IBM BladeCenter HS22 (Intel Xeon X5647)

**SPECfp\_base2006 = 50.2**

CPU2006 license: 11

Test date: Jun-2011

Test sponsor: IBM Corporation

Hardware Availability: Feb-2011

Tested by: IBM Corporation

Software Availability: Apr-2011

## Base Optimization Flags (Continued)

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -ansi-alias  
-parallel

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	<b>SPECfp2006 =</b>	<b>54.2</b>
IBM BladeCenter HS22 (Intel Xeon X5647)	<b>SPECfp_base2006 =</b>	<b>50.2</b>
<b>CPU2006 license:</b> 11	<b>Test date:</b>	Jun-2011
<b>Test sponsor:</b> IBM Corporation	<b>Hardware Availability:</b>	Feb-2011
<b>Tested by:</b> IBM Corporation	<b>Software Availability:</b>	Apr-2011

## Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xsSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xsSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xsSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

465.tonto: -xsSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4  
-B /usr/share/libhugetlbfs/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfs-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xsSE4 .2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xsSE4 .2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>  
<http://www.spec.org/cpu2006/flags/IBM-platform-linux64-revA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>  
<http://www.spec.org/cpu2006/flags/IBM-platform-linux64-revA.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 54.2

IBM BladeCenter HS22 (Intel Xeon X5647)

SPECfp\_base2006 = 50.2

CPU2006 license: 11

Test date: Jun-2011

Test sponsor: IBM Corporation

Hardware Availability: Feb-2011

Tested by: IBM Corporation

Software Availability: Apr-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Thu Jul 24 00:19:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 August 2011.