



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

### SPECfp<sup>®</sup>\_rate2006 = 58.0

### Intel DH61WW motherboard (Intel Pentium G860)

### SPECfp\_rate\_base2006 = 57.2

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Sep-2011

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Pentium G860  
 CPU Characteristics:  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Windows 7 Ultimate (64-bit)  
 Compiler: C/C++: Version 12.0.3.176 of Intel C++ Studio XE for Windows;  
 Fortran: Version 12.0.3.176 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1  
 Auto Parallel: No  
 File System: NTFS

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp\_rate2006 = **58.0**

Intel DH61WW motherboard (Intel Pentium G860)

SPECfp\_rate\_base2006 = **57.2**

CPU2006 license: 13

Test date: Oct-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

L3 Cache: 3 MB I+D on chip per chip  
Other Cache: None  
Memory: 4 GB (2 x 2 GB 2Rx4 PC3-10600U-9)  
Disk Subsystem: 1 TB Seagate SATA, 7200 RPM  
Other Hardware: None

System State: Default  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	332	82.0	354	76.6	<b>354</b>	<b>76.8</b>	2	332	82.0	354	76.6	<b>354</b>	<b>76.8</b>
416.gamess	2	671	58.4	<b>671</b>	<b>58.4</b>	670	58.4	2	671	58.4	<b>671</b>	<b>58.4</b>	670	58.4
433.milc	2	221	83.0	<b>221</b>	<b>83.0</b>	221	83.2	2	221	83.0	<b>221</b>	<b>83.0</b>	221	83.2
434.zeusmp	2	336	54.2	335	54.4	<b>335</b>	<b>54.4</b>	2	336	54.2	335	54.4	<b>335</b>	<b>54.4</b>
435.gromacs	2	325	44.0	325	44.0	<b>325</b>	<b>44.0</b>	2	320	44.6	<b>320</b>	<b>44.6</b>	320	44.6
436.cactusADM	2	452	52.8	455	52.4	<b>452</b>	<b>52.8</b>	2	452	52.8	455	52.4	<b>452</b>	<b>52.8</b>
437.leslie3d	2	369	51.0	<b>370</b>	<b>50.8</b>	370	50.8	2	369	51.0	<b>370</b>	<b>50.8</b>	370	50.8
444.namd	2	<b>405</b>	<b>39.6</b>	406	39.6	404	39.8	2	398	40.4	398	40.4	<b>398</b>	<b>40.4</b>
447.dealII	2	<b>386</b>	<b>59.2</b>	385	59.4	390	58.6	2	392	58.4	<b>390</b>	<b>58.6</b>	390	58.6
450.soplex	2	359	46.4	358	46.6	<b>359</b>	<b>46.6</b>	2	357	46.6	<b>356</b>	<b>46.8</b>	355	47.0
453.povray	2	148	71.6	148	72.0	<b>148</b>	<b>72.0</b>	2	<b>124</b>	<b>86.0</b>	123	86.2	124	86.0
454.calculix	2	257	64.2	255	64.6	<b>255</b>	<b>64.6</b>	2	256	64.6	<b>256</b>	<b>64.6</b>	256	64.6
459.GemsFDTD	2	564	37.6	562	37.8	<b>563</b>	<b>37.8</b>	2	564	37.6	562	37.8	<b>563</b>	<b>37.8</b>
465.tonto	2	<b>386</b>	<b>51.0</b>	385	51.0	386	51.0	2	377	52.2	375	52.4	<b>376</b>	<b>52.4</b>
470.lbm	2	369	74.4	<b>369</b>	<b>74.6</b>	368	74.6	2	369	74.4	<b>369</b>	<b>74.6</b>	368	74.6
481.wrf	2	<b>300</b>	<b>74.4</b>	300	74.4	301	74.2	2	<b>300</b>	<b>74.4</b>	300	74.4	301	74.2
482.sphinx3	2	<b>676</b>	<b>57.8</b>	675	57.8	677	57.6	2	<b>676</b>	<b>57.6</b>	677	57.6	675	57.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
The start command with the /affinity switch was used to bind processes to cores

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 58.0

Intel DH61WW motherboard (Intel Pentium G860)

SPECfp\_rate\_base2006 = 57.2

CPU2006 license: 13

Test date: Oct-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64 -names:lowercase  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 -names:lowercase /assume:underscore  
 437.lelie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 450.soplex: -DSPEC\_CPU\_P64  
 453.povray: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER -names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32  
/F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qcxx-features  
-Qauto-ilp32 /F1000000000 shlw64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias /F1000000000  
-link /FORCE:MULTIPLE

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 58.0

Intel DH61WW motherboard (Intel Pentium G860)

SPECfp\_rate\_base2006 = 57.2

CPU2006 license: 13

Test date: Oct-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc9 -Qstd=c99 ifort
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlw64M.lib -link /FORCE:MULTIPLE
```

```
447.dealIII: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qscalar-rep- -Qauto-ilp32 /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 58.0

Intel DH61WW motherboard (Intel Pentium G860)

SPECfp\_rate\_base2006 = 57.2

CPU2006 license: 13

Test date: Oct-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Peak Optimization Flags (Continued)

450.soplex: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qauto-ilp32 /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

453.povray: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32  
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000  
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32  
/F1000000000 -link /FORCE:MULTIPLE

436.cactusADM: basepeak = yes

454.calculix: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qauto-ilp32 /F1000000000  
-link /FORCE:MULTIPLE

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.20111012.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.20111012.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings-revC.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 58.0

Intel DH61WW motherboard (Intel Pentium G860)

SPECfp\_rate\_base2006 = 57.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2011

Hardware Availability: Sep-2011

Software Availability: Apr-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Thu Jul 24 01:44:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 25 October 2011.