



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp®2006 = 67.9**

**SPECfp\_base2006 = 65.9**

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jan-2012

Hardware Availability: Mar-2012

Software Availability: Dec-2011



## Hardware

CPU Name: Intel Xeon E5-2637  
CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
Compiler: 2.6.32-220.el6.x86\_64  
C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;  
Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux  
Auto Parallel: Yes  
File System: ext4

*Continued on next page*

*Continued on next page*



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp2006 = 67.9**

<b>CPU2006 license:</b> 19	<b>Test date:</b> Jan-2012
<b>Test sponsor:</b> Fujitsu	<b>Hardware Availability:</b> Mar-2012
<b>Tested by:</b> Fujitsu	<b>Software Availability:</b> Dec-2011
L3 Cache: 5 MB I+D on chip per chip	System State: Run level 3 (multi-user)
Other Cache: None	Base Pointers: 64-bit
Memory: 128 GB (16 x 8 GB 2Rx4 PC3L-12800R-11, ECC)	Peak Pointers: 32/64-bit
Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM	Other Software: None
Other Hardware: None	

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	72.8	187	69.2	196	<b>69.4</b>	<b>196</b>	72.8	187	69.2	196	<b>69.4</b>	<b>196</b>
416.gamess	591	33.1	<b>589</b>	<b>33.2</b>	589	33.2	<b>531</b>	<b>36.9</b>	<b>531</b>	<b>36.9</b>	531	36.9
433.milc	<b>142</b>	<b>64.8</b>	142	64.8	142	64.8	<b>141</b>	<b>65.0</b>	141	65.1	141	65.0
434.zeusmp	100	91.0	100	90.8	<b>100</b>	<b>91.0</b>	100	91.0	100	90.8	<b>100</b>	<b>91.0</b>
435.gromacs	192	37.2	<b>192</b>	<b>37.3</b>	191	37.5	192	37.2	<b>192</b>	<b>37.3</b>	191	37.5
436.cactusADM	<b>56.2</b>	<b>212</b>	55.8	214	57.7	207	<b>56.2</b>	<b>212</b>	55.8	214	<b>57.7</b>	207
437.leslie3d	<b>86.0</b>	<b>109</b>	85.8	110	92.2	102	<b>86.0</b>	<b>109</b>	85.8	110	92.2	102
444.namd	<b>336</b>	<b>23.9</b>	336	23.9	336	23.9	<b>331</b>	<b>24.3</b>	331	24.3	330	24.3
447.dealII	214	53.4	215	53.2	<b>215</b>	<b>53.2</b>	214	53.4	215	53.2	<b>215</b>	<b>53.2</b>
450.soplex	229	36.4	228	36.5	<b>229</b>	<b>36.4</b>	229	36.4	228	36.5	<b>229</b>	<b>36.4</b>
453.povray	<b>121</b>	<b>43.9</b>	120	44.2	121	43.8	99.9	53.2	<b>101</b>	<b>52.6</b>	102	52.3
454.calculix	206	40.1	<b>207</b>	<b>39.8</b>	208	39.6	<b>193</b>	<b>42.8</b>	193	42.8	191	43.1
459.GemsFDTD	122	86.7	122	86.8	<b>122</b>	<b>86.8</b>	116	91.2	116	91.7	<b>116</b>	<b>91.4</b>
465.tonto	<b>242</b>	<b>40.7</b>	244	40.3	239	41.1	<b>224</b>	<b>43.8</b>	225	43.6	224	43.9
470.lbm	66.8	206	70.2	196	<b>67.4</b>	<b>204</b>	66.8	206	70.2	196	<b>67.4</b>	<b>204</b>
481.wrf	158	70.5	<b>159</b>	<b>70.4</b>	163	68.5	<b>158</b>	<b>70.5</b>	<b>159</b>	<b>70.4</b>	163	68.5
482.sphinx3	<b>318</b>	<b>61.2</b>	316	61.7	337	57.9	<b>318</b>	<b>61.2</b>	<b>316</b>	<b>61.7</b>	337	57.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Intel HT Technology = Disable  
 Frequency Floor Override = Enable

## General Notes

Environment variables set by runspec before the start of the run:  
 KMP\_AFFINITY = "granularity=fine,scatter"  
 LD\_LIBRARY\_PATH = "/SPECcpu2006/lib32:/SPECcpu2006/lib64"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp2006 = 67.9**

CPU2006 license: 19

Test date: Jan-2012

Test sponsor: Fujitsu

Hardware Availability: Mar-2012

Tested by: Fujitsu

Software Availability: Dec-2011

## General Notes (Continued)

OMP\_NUM\_THREADS = "4"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp2006 = 67.9**

CPU2006 license: 19

Test date: Jan-2012

Test sponsor: Fujitsu

Hardware Availability: Mar-2012

Tested by: Fujitsu

Software Availability: Dec-2011

## Base Optimization Flags (Continued)

C++ benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias
```

Fortran benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias
```

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp2006 = 67.9**

CPU2006 license: 19

Test date: Jan-2012

Test sponsor: Fujitsu

Hardware Availability: Mar-2012

Tested by: Fujitsu

Software Availability: Dec-2011

## Peak Optimization Flags (Continued)

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll14

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120320.html>

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120320.xml>

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX300 S7, Intel Xeon E5-2637, 3.0 GHz

**SPECfp2006 = 67.9**

**SPECfp\_base2006 = 65.9**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Jan-2012

**Hardware Availability:** Mar-2012

**Software Availability:** Dec-2011

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 07:00:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 10 April 2012.