



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp<sup>®</sup>2006 = **64.3**

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

SPECfp\_base2006 = **62.7**

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2012

Hardware Availability: Jul-2012

Software Availability: Feb-2012



### Hardware

CPU Name: Intel Xeon E5-1410  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
 2.6.32-220.el6.x86\_64  
 Compiler: C/C++: Version 12.1.0.293 of Intel C++ Studio XE for Linux;  
 Fortran: Version 12.1.0.293 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **64.3**

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

SPECfp\_base2006 = **62.7**

CPU2006 license: 19

Test date: Jul-2012

Test sponsor: Fujitsu

Hardware Availability: Jul-2012

Tested by: Fujitsu

Software Availability: Feb-2012

L3 Cache: 10 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 48 GB (6 x 8 GB 2Rx4 PC3L-12800R-11, ECC, running at 1333 MHz and CL7)  
 Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	97.8	139	95.8	142	<b>96.2</b>	<b>141</b>	96.4	141	<b>96.4</b>	<b>141</b>	96.2	141
416.gamess	635	30.8	<b>635</b>	<b>30.9</b>	633	30.9	581	33.7	579	33.8	<b>580</b>	<b>33.8</b>
433.milc	144	63.9	<b>144</b>	<b>63.9</b>	143	64.0	142	64.6	142	64.8	<b>142</b>	<b>64.7</b>
434.zeusmp	88.0	103	88.0	103	<b>88.0</b>	<b>103</b>	88.0	103	88.0	103	<b>88.0</b>	<b>103</b>
435.gromacs	216	33.0	<b>216</b>	<b>33.0</b>	217	32.9	216	33.0	<b>216</b>	<b>33.0</b>	217	32.9
436.cactusADM	56.6	211	<b>56.6</b>	<b>211</b>	57.2	209	56.6	211	<b>56.6</b>	<b>211</b>	57.2	209
437.leslie3d	<b>99.0</b>	<b>94.9</b>	99.0	94.9	98.8	95.1	<b>99.0</b>	<b>94.9</b>	99.0	94.9	98.8	95.1
444.namd	<b>367</b>	<b>21.8</b>	367	21.8	367	21.8	361	22.2	<b>361</b>	<b>22.2</b>	361	22.2
447.dealII	217	52.7	<b>216</b>	<b>53.0</b>	216	53.1	<b>216</b>	<b>53.1</b>	216	53.0	215	53.1
450.soplex	230	36.3	<b>229</b>	<b>36.4</b>	229	36.4	230	36.3	<b>229</b>	<b>36.4</b>	229	36.4
453.povray	129	41.2	130	40.9	<b>130</b>	<b>41.0</b>	109	48.6	111	48.0	<b>110</b>	<b>48.3</b>
454.calculix	<b>213</b>	<b>38.8</b>	213	38.7	213	38.8	<b>208</b>	<b>39.6</b>	208	39.6	207	39.9
459.GemsFDTD	<b>147</b>	<b>72.0</b>	147	72.0	147	72.0	<b>137</b>	<b>77.6</b>	137	77.7	137	77.5
465.tonto	259	38.0	259	37.9	<b>259</b>	<b>38.0</b>	243	40.6	245	40.2	<b>243</b>	<b>40.5</b>
470.lbm	82.8	166	<b>83.2</b>	<b>165</b>	83.4	165	82.8	166	<b>83.2</b>	<b>165</b>	83.4	165
481.wrf	128	87.0	129	86.8	<b>129</b>	<b>86.8</b>	128	87.0	129	86.8	<b>129</b>	<b>86.8</b>
482.sphinx3	<b>273</b>	<b>71.3</b>	274	71.1	271	71.8	<b>273</b>	<b>71.3</b>	274	71.1	271	71.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"  
 Transparent Huge Pages enabled with:  
 echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

## Platform Notes

BIOS configuration:  
 Intel HT Technology = Disable  
 Frequency Floor Override = Enable



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 64.3**

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

**SPECfp\_base2006 = 62.7**

**CPU2006 license:** 19

**Test date:** Jul-2012

**Test sponsor:** Fujitsu

**Hardware Availability:** Jul-2012

**Tested by:** Fujitsu

**Software Availability:** Feb-2012

## General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/SPECcpu2006/libs/32:/SPECcpu2006/libs/64"
OMP_NUM_THREADS = "4"
```

Binaries compiled on a system with 1x E3-1270v2 CPU + 32 GB memory using RHEL6.2

For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 64.3**

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

**SPECfp\_base2006 = 62.7**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Jul-2012

**Hardware Availability:** Jul-2012

**Software Availability:** Feb-2012

## Base Optimization Flags

C benchmarks:

`-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias`

C++ benchmarks:

`-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias`

## Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: `-xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `basepeak = yes`

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 64.3**

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

**SPECfp\_base2006 = 62.7**

**CPU2006 license:** 19

**Test date:** Jul-2012

**Test sponsor:** Fujitsu

**Hardware Availability:** Jul-2012

**Tested by:** Fujitsu

**Software Availability:** Feb-2012

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-ansi-alias

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -parallel  
-static

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120320.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 64.3

PRIMERGY TX150 S8, Intel Xeon E5-1410, 2.80 GHz

SPECfp\_base2006 = 62.7

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2012

Hardware Availability: Jul-2012

Software Availability: Feb-2012

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120320.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 11:13:29 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 August 2012.