SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Fire X4-2 (Intel Xeon E5-2697 v2 2.7GHz)

SPECint®2006 = 60.5

SPECint_base2006 = 47.9

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: Sep-2013
Hardware Availability: Sep-2013
Software Availability: Nov-2013



Hardware

CPU Name:	Intel Xeon E5-2697 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.50 GHz
CPU MHz:	2700
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip
CPU(s) orderable:	2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem:	1 x 600 GB SAS, 10K RPM
Other Hardware:	None

Software

Operating System:	Solaris 11.1 (SRU 11)
Compiler:	C/C++: Version 12.3 of Oracle Solaris Studio 10/13 Patch Set (tested with nightly build 20130822)
Auto Parallel:	Yes
File System:	zfs
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V9.01

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Fire X4-2 (Intel Xeon E5-2697 v2 2.7GHz)

SPECint2006 = 60.5

SPECint_base2006 = 47.9

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: Sep-2013
Hardware Availability: Sep-2013
Software Availability: Nov-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	398	24.6	**396**	**24.7**	396	24.7	238	41.0	**238**	**41.0**	238	41.1
401.bzip2	491	19.7	493	19.6	**493**	**19.6**	**399**	**24.2**	399	24.2	399	24.2
403.gcc	**276**	**29.1**	276	29.1	277	29.1	204	39.4	205	39.3	**205**	**39.3**
429.mcf	**210**	**43.5**	210	43.4	209	43.6	132	69.3	**131**	**69.8**	131	69.8
445.gobmk	503	20.9	**503**	**20.9**	504	20.8	**374**	**28.0**	374	28.0	374	28.0
456.hmmer	202	46.1	202	46.1	**202**	**46.1**	**168**	**55.7**	168	55.7	168	55.7
458.sjeng	540	22.4	540	22.4	**540**	**22.4**	440	27.5	440	27.5	**440**	**27.5**
462.libquantum	5.86	3540	5.91	3510	**5.87**	**3530**	5.86	3540	5.91	3510	**5.87**	**3530**
464.h264ref	**433**	**51.1**	433	51.1	433	51.1	**349**	**63.4**	349	63.4	349	63.4
471.omnetpp	**181**	**34.5**	181	34.6	182	34.3	129	48.6	129	48.3	**129**	**48.5**
473.astar	221	31.7	222	31.7	**221**	**31.7**	217	32.4	217	32.4	**217**	**32.4**
483.xalancbmk	**123**	**56.1**	123	56.1	123	56.1	**117**	**58.9**	117	58.9	117	59.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used to bind processes to CPU threads with pbind(1)
```

Operating System Notes

```
ulimit -s unlimited  (shell): increases stack
/etc/system parameters
   autoup=1000
   tune_t_fsflushr=10

gzip compression set using "zfs set compression=gzip <zfs-filesystem>"
```

Platform Notes

```
Default BIOS Settings were used except:
    Hyper-Threading (HT) Technology was Disabled

Sysinfo program /export/home/cpu2006v1.2/Docs/sysinfo
: 6775  2011-08-16 #f7622badcf24e01c368b1db4377c
running on bur398-85 Sun Sep  1 03:28:11 2013

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo


From /usr/sbin/psrinfo -pv
 Intel(r) Xeon(r) CPU E5-2697 v2 @ 2.70GHz
```

Continued on next page

Platform Notes (Continued)

```
 x86 (GenuineIntel 306E4 family 6 model 62 step 4 clock 2693 MHz)

/usr/sbin/psrinfo -p:   2 chips
/usr/sbin/psrinfo | wc -l: 24 threads

/usr/sbin/prtconf | grep "Memory size:": 262087 Megabytes

/etc/release:
                              Oracle Solaris 11.1 X86
uname -a:
SunOS bur398-85 5.11 11.1 i86pc i386 i86pc

disk: df -h
Filesystem             Size   Used  Available Capacity  Mounted on
rpool/export/home      547G    48G       420G    11%    /export/home

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
MTEXCLUSIVE = "Y"
OMP_NUM_THREADS = "24"
SUNW_MP_PROCBIND = "scatter"
SUNW_MP_THR_IDLE = "spin"
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
464.h264ref: -DSPEC_CPU_LP64

Continued on next page

Base Portability Flags (Continued)

471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-g -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xautopar -xreduction

C++ benchmarks:
-g -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=compatible -library=stlport4 -lfast

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=std -lbsdmalloc -xprefetch=no%auto

401.bzip2: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=strong

Continued on next page

Peak Optimization Flags (Continued)

403.gcc: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m32 -xpagesize=2M -xalias_level=std -W2,-Abuiltin_opt:calloc_no_support=on

429.mcf: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m32 -xpagesize=4K -xalias_level=std -W2,-Asac

445.gobmk: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xtarget=sandybridge -m64 -xpagesize=2M -xrestrict -xalias_level=strong

456.hmmer: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=strong -xprefetch=no%auto

458.sjeng: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=std

462.libquantum: basepeak = yes

464.h264ref: Same as 401.bzip2

C++ benchmarks:

471.omnetpp: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m32 -xpagesize=2M -xalias_level=compatible -library=stlport4 -lfast

473.astar: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -xalias_level=compatible -xrestrict -library=stlport4 -lfast

483.xalancbmk: -g -xprofile=collect:./feedback(pass 1) -xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M -library=stlport4 -lfast

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.3-x86_64.20130924.html
http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.CPUv1.2-RevA.20120425.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.3-x86_64.20130924.xml
http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.CPUv1.2-RevA.20120425.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 16:07:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 September 2013.