SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-4820 v2, 1.90 GHz)

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: May-2014
Hardware Availability: Apr-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Copies	
410.bwaves	
416.gamess	
433.milc	
434.zeusmp	
435.gromacs	
436.cactusADM	
437.leslie3d	
444.namd	
447.dealII	
450.soplex	
453.povray	
454.calculix	
459.GemsFDTD	
465.tonto	
470.lbm	
481.wrf	
482.sphinx3	

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-4820 v2, 1.90 GHz)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: May-2014
Hardware Availability: Apr-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Hardware

CPU Name:	Intel Xeon E7-4820 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 2.50 GHz
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	32 cores, 4 chips, 8 cores/chip, 2 threads/core
CPU(s) orderable:	1,2,3,4 Chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	16 MB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (64 x 8 GB 2Rx4 PC3-12800R-11, ECC, running at 1333 MHz and CL11)
Disk Subsystem:	1 x 300 GB SAS SATA 15K RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 6.4 (Santiago) 2.6.32-358.el6.x86_64
Compiler:	C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux; Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
Auto Parallel:	No
File System:	ext4
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-4820 v2, 1.90 GHz)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: May-2014
Hardware Availability: Apr-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
416.gamess	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
433.milc	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
434.zeusmp	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
435.gromacs	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
436.cactusADM	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
437.leslie3d	64	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
444.namd	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
447.dealII	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
450.soplex	64	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
453.povray	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
454.calculix	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
459.GemsFDTD	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
465.tonto	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
470.lbm	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
481.wrf	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC
482.sphinx3	64	NC	NC	NC	NC	NC	NC	64	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Platform Notes

```
CPU performance set to HPC
Power Technology set to Custom
CPU Power State C6 set to Enabled
CPU Power State C1 Enhanced set to Disabled
Package C State Limit set to C0/C1 State
Energy Performance policy set to Performance
Memory RAS configuration set to Maximum Performance
DRAM Clock Throttling Set to Performance
LV DDR Mode set to Performance-mode
DRAM Refresh Rate Set to 1x
 Sysinfo program /opt/cpu2006-1.2/config/sysinfo.rev6818
 $Rev: 6818 $ $Date:: 2012-07-17 #$ e86d102572650a6e4d596a3cee98f191
 running on SPECCPU-RHEL64 Thu May  1 05:02:16 2014

 This section contains SUT (System Under Test) info as seen by
 some common utilities.  To remove or add to this section, see:
   http://www.spec.org/cpu2006/Docs/config.html#sysinfo

 From /proc/cpuinfo
    model name : Intel(R) Xeon(R) CPU E7-4820 v2 @ 2.00GHz
       4 "physical id"s (chips)
       64 "processors"
    cores, siblings (Caution: counting these is hw and system dependent.  The
    following excerpts from /proc/cpuinfo might not be reliable.  Use with
    caution.)
       cpu cores : 8
       siblings  : 16
       physical 0: cores 0 1 2 3 4 5 6 7
       physical 1: cores 0 1 2 3 4 5 6 7
       physical 2: cores 0 1 2 3 4 5 6 7
       physical 3: cores 0 1 2 3 4 5 6 7
    cache size : 16384 KB

 From /proc/meminfo
    MemTotal:       529141664 kB
    HugePages_Total:       0
    Hugepagesize:       2048 kB

 /usr/bin/lsb_release -d
    Red Hat Enterprise Linux Server release 6.4 (Santiago)
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Platform Notes (Continued)

```
From /etc/*release* /etc/*version*
   redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
   system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
   Linux SPECCPU-RHEL64 2.6.32-358.el6.x86_64 #1 SMP Tue Jan 29 11:47:41 EST
   2013 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Apr 30 13:50

SPEC is set to: /opt/cpu2006-1.2
   Filesystem     Type    Size  Used Avail Use% Mounted on
   /dev/sda2      ext4    275G   13G  248G   5% /

Additional information from dmidecode:
  BIOS Cisco Systems, Inc. C460M4.1.5.5.13.012720142211 01/27/2014
  Memory:
   64x   8 GB
   64x 0xCE00 M393B1K70QB0-YK0 8 GB 1333 MHz 2 rank
   32x NO DIMM NO DIMM

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/opt/cpu2006-1.2/libs/32:/opt/cpu2006-1.2/libs/64:/opt/cpu2006-1.2/sh"

  Binaries compiled on a system with 1x Core i7-860 CPU + 8GB
  memory using RedHat EL 6.4
  Transparent Huge Pages enabled with:
  echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
  Filesystem page cache cleared with:
  echo 1>       /proc/sys/vm/drop_caches
  runspec command invoked through numactl i.e.:
  numactl --interleave=all runspec <etc>

Submitted_by: "Sheshgiri I (shei)" <shei@cisco.com>
Submitted: Wed May 28 03:16:44 EDT 2014
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

General Notes (Continued)

```
Submission: cpu2006-20140505-29493.sub
```

Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

Base Portability Flags

```
    410.bwaves: -DSPEC_CPU_LP64
   416.gamess: -DSPEC_CPU_LP64
  433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
  435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
   447.dealII: -DSPEC_CPU_LP64
   450.soplex: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
     465.tonto: -DSPEC_CPU_LP64
      470.lbm: -DSPEC_CPU_LP64
      481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
  482.sphinx3: -DSPEC_CPU_LP64
```

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Base Optimization Flags

C benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

C++ benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

Fortran benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias
-opt-mem-layout-trans=3

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):
icpc -m64

[illegible] icpc -m32

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -opt-mem-layout-trans=3 -unroll2

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

Non-Compliant

Peak Optimization Flags (Continued)

450.soplex: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -auto-ilp32

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-4820 v2, 1.90 GHz)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: May-2014
Hardware Availability: Apr-2014
Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a BIOS which included a version of the Intel MRC (Memory Reference Code) that is not supported by Cisco or Intel.

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64_20140128.html
http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2-revB.html

You can also download the XML flags source by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml
http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2-revB.xml

Non-Compliant

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Sep 19 15:51:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 June 2014.