



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Intel Corporation**

**SPECint®2006 = 39.3**

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint\_base2006 = 37.8**

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2014

Hardware Availability: Dec-2013

Software Availability: Oct-2013



<b>Hardware</b>		<b>Software</b>
CPU Name:	Intel Celeron G1830	Operating System: Microsoft Windows 8.1 Pro 6.3.9600 N/A Build 9600
CPU Characteristics:		Compiler: C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows; Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
CPU MHz:	2794	Auto Parallel: Yes
FPU:	Integrated	File System: NTFS
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip	System State: Default
CPU(s) orderable:	1 chip	Base Pointers: 32/64-bit
Primary Cache:	32 KB I + 32 KB D on chip per core	Peak Pointers: 32/64-bit
Secondary Cache:	256 KB I+D on chip per core	Other Software: SmartHeap Library Version 10.0 from <a href="http://www.microquill.com/">http://www.microquill.com/</a>
L3 Cache:	2 MB I+D on chip per chip	
Other Cache:	None	
Memory:	8 GB (2 x 4 GB 2Rx4 PC3-12800U-11, running at 1333 MHz and CL9)	
Disk Subsystem:	1 TB Seagate SATA HDD, 7200 RPM	
Other Hardware:	None	



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

**SPECint2006 = 39.3**

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint\_base2006 = 37.8**

CPU2006 license: 13

Test date: Jun-2014

Test sponsor: Intel Corporation

Hardware Availability: Dec-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	350	27.9	<b>350</b>	<b>27.9</b>	351	27.8	<b>287</b>	<b>34.1</b>	286	34.1	288	33.9
401.bzip2	528	18.3	<b>527</b>	<b>18.3</b>	526	18.3	<b>524</b>	<b>18.4</b>	<b>527</b>	<b>18.3</b>	541	17.8
403.gcc	329	24.5	<b>329</b>	<b>24.4</b>	330	24.4	<b>312</b>	<b>25.8</b>	310	26.0	313	25.7
429.mcf	<b>191</b>	<b>47.7</b>	192	47.5	191	47.8	<b>191</b>	<b>47.7</b>	192	47.5	191	47.8
445.gobmk	<b>465</b>	<b>22.5</b>	465	22.5	465	22.5	<b>442</b>	<b>23.8</b>	441	23.8	<b>441</b>	<b>23.8</b>
456.hammer	<b>182</b>	<b>51.4</b>	181	51.5	182	51.4	<b>182</b>	<b>51.4</b>	181	51.5	182	51.4
458.sjeng	461	26.3	<b>460</b>	<b>26.3</b>	458	26.4	<b>461</b>	<b>26.3</b>	<b>460</b>	<b>26.3</b>	458	26.4
462.libquantum	44.0	471	<b>43.6</b>	<b>475</b>	43.5	476	44.0	471	<b>43.6</b>	<b>475</b>	43.5	476
464.h264ref	429	51.6	425	52.1	<b>427</b>	<b>51.9</b>	390	56.8	393	56.3	<b>390</b>	<b>56.7</b>
471.omnetpp	327	19.1	319	19.6	<b>320</b>	<b>19.6</b>	301	20.8	300	20.8	<b>300</b>	<b>20.8</b>
473.astar	<b>303</b>	<b>23.2</b>	303	23.2	305	23.0	<b>303</b>	<b>23.2</b>	303	23.2	305	23.0
483.xalancbmk	166	41.6	<b>165</b>	<b>41.7</b>	165	41.9	<b>166</b>	<b>41.6</b>	<b>165</b>	<b>41.7</b>	165	41.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 14.0 was set up to generate 64-bit binaries with the command:

"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

## Platform Notes

```
Sysinfo program C:\SPEC14.0\Docs/sysinfo
$Rev: 6775 $ $Date::: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on Clt54BEF70B2D93 Fri Jun 27 16:53:15 2014
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 8.1 Pro
OS Version   : 6.3.9600 N/A Build 9600
System Manufacturer: INTEL_
System Model  : DH87MC_
Processor(s)  : 1 Processor(s) Installed.
[01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~2794 Mhz
BIOS Version  : Intel Corp. MCH8710H.86A.0047.2013.0606.1508, 6/6/2013
Total Physical Memory: 7,864 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint2006 = 39.3**

**SPECint\_base2006 = 37.8**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Jun-2014

**Hardware Availability:** Dec-2013

**Software Availability:** Oct-2013

## Platform Notes (Continued)

```
L2CacheSize      : 512
L3CacheSize      : 2048
MaxClockSpeed   : 2794
Name            : Intel(R) Celeron(R) CPU G1830 @ 2.80GHz
NumberOfCores    : 2
NumberOfLogicalProcessors: 2
```

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

OMP\_NUM\_THREADS set to number of processors cores  
KMP\_AFFINITY set to granularity=fine,scatter  
Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

## Base Portability Flags

```
400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
                  -DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption_cpp,--no_wchar_t_keyword
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

**SPECint2006 = 39.3**

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint\_base2006 = 37.8**

CPU2006 license: 13

Test date: Jun-2014

Test sponsor: Intel Corporation

Hardware Availability: Dec-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Base Optimization Flags

C benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qauto-ilp32 /F512000000
```

C++ benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
-Qauto-ilp32 /F5120000000 shlw64M.lib -link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F5120000000 shlw64M.lib  
-link /FORCE:MULTIPLE
```

```
401.bzip2: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias  
-Qauto-ilp32 /F5120000000
```

```
403.gcc: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F5120000000
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

**SPECint2006 = 39.3**

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint\_base2006 = 37.8**

**CPU2006 license:** 13

**Test date:** Jun-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Dec-2013

**Tested by:** Intel Corporation

**Software Availability:** Oct-2013

## Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32  
/F512000000

456.hmmr: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias  
-Qauto-ilp32 /F512000000

C++ benchmarks:

471.omnetpp: -QxSSE4.2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000  
shlw64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

**SPECint2006 = 39.3**

Intel DH87MC Motherboard (Intel Celeron G1830)

**SPECint\_base2006 = 37.8**

**CPU2006 license:** 13

**Test date:** Jun-2014

**Test sponsor:** Intel Corporation

**Hardware Availability:** Dec-2013

**Tested by:** Intel Corporation

**Software Availability:** Oct-2013

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Jul 30 10:54:21 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 July 2014.