SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Microsoft Corporation

(Test Sponsor: Intel Corporation)

Surface Pro 3

SPECint®2006 = 42.2

SPECint_base2006 = 40.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2014
Hardware Availability: Jun-2014
Software Availability: Oct-2013



Hardware

CPU Name:	Intel Core i5-4300U
CPU Characteristics:	Intel Turbo Boost Technology up to 2.90 GHz
CPU MHz:	1900
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	3 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (4 x 1 GB 2Rx32 PC3L-12800U-11)
Disk Subsystem:	128 GB SSD
Other Hardware:	None

Software

Operating System:	Microsoft Windows 8.1 Pro 6.3.9600 N/A Build 9600
Compiler:	C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows; Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 10.0 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Microsoft Corporation
(Test Sponsor: Intel Corporation)

Surface Pro 3

SPECint2006 = 42.2

SPECint_base2006 = 40.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2014
Hardware Availability: Jun-2014
Software Availability: Oct-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	355	27.5	**339**	**28.8**	337	29.0	**271**	**36.0**	271	36.0	271	36.1
401.bzip2	486	19.9	**469**	**20.6**	468	20.6	467	20.7	471	20.5	**469**	**20.6**
403.gcc	323	25.0	**323**	**24.9**	323	24.9	296	27.2	**298**	**27.0**	298	27.0
429.mcf	178	51.3	172	53.0	**173**	**52.7**	178	51.3	172	53.0	**173**	**52.7**
445.gobmk	446	23.5	446	23.5	**446**	**23.5**	**422**	**24.8**	422	24.8	422	24.9
456.hmmer	161	57.9	160	58.2	**161**	**58.0**	161	57.9	160	58.2	**161**	**58.0**
458.sjeng	451	26.8	**451**	**26.8**	451	26.8	451	26.8	**451**	**26.8**	451	26.8
462.libquantum	28.5	727	28.8	719	**28.7**	**722**	28.5	727	28.8	719	**28.7**	**722**
464.h264ref	472	46.9	458	48.3	**460**	**48.1**	472	46.9	458	48.3	**460**	**48.1**
471.omnetpp	**313**	**20.0**	312	20.0	319	19.6	292	21.4	**293**	**21.3**	297	21.0
473.astar	293	24.0	**293**	**24.0**	293	23.9	293	24.0	**293**	**24.0**	293	23.9
483.xalancbmk	**158**	**43.6**	160	43.2	158	43.7	**158**	**43.6**	160	43.2	158	43.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 14.0 was set up to
generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r)
Parallel Studio XE 2013 program folder)
```

Platform Notes

```
Sysinfo program C:\Users\peca\Desktop\SPEC14.0\SPEC14.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on ea_i5 Wed Sep 10 16:01:09 2014

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name       : Microsoft Windows 8.1 Pro
OS Version    : 6.3.9600 N/A Build 9600
System Manufacturer: Microsoft Corporation
System Model  : Surface Pro 3
Processor(s)  : 1 Processor(s) Installed.
     [01]: Intel64 Family 6 Model 69 Stepping 1 GenuineIntel ~1900 Mhz
BIOS Version  : American Megatrends Inc. 3.10.0250, 8/28/2014
Total Physical Memory: 4,001 MB

Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page

Platform Notes (Continued)

```
 L2CacheSize   : 512
 L3CacheSize   : 3072
 MaxClockSpeed : 2501
 Name          : Intel(R) Core(TM) i5-4300U CPU @ 1.90GHz
 NumberOfCores : 2
 NumberOfLogicalProcessors: 4

 (End of data from sysinfo program)
```

Component Notes

```
Test ran with power supply connected
Power Supply: 12V, 2.58A
```

General Notes

```
 OMP_NUM_THREADS set to number of processors cores
 KMP_AFFINITY set to granularity=fine,scatter
 Binaries compiled on a system with 1x Intel Core i7-860 CPU
 + 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Base Portability Flags

```
    400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
                   -DSPEC_CPU_NO_NEED_VA_COPY
      401.bzip2: -DSPEC_CPU_P64
        403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
        429.mcf: -DSPEC_CPU_P64
      445.gobmk: -DSPEC_CPU_P64
      456.hmmer: -DSPEC_CPU_P64
       458.sjeng: -DSPEC_CPU_P64
    462.libquantum: -DSPEC_CPU_P64
      464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
    471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
        473.astar: -DSPEC_CPU_P64
  483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword
```

Base Optimization Flags

C benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F512000000
```

C++ benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F512000000 shlW64M.lib            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch`
`-Qauto-ilp32 /F512000000 shlW64M.lib`
`-link /FORCE:MULTIPLE`

401.bzip2: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias`
`-Qauto-ilp32 /F512000000`

403.gcc: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Nov 6 13:46:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 November 2014.