SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Microsoft Corporation

(Test Sponsor: Intel Corporation)

Surface Pro 3

SPECint®2006 = 24.3

SPECint_base2006 = 23.4

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2014
Hardware Availability: Jun-2014
Software Availability: Oct-2013



Hardware

CPU Name:	Intel Core i3-4020Y
CPU Characteristics:	
CPU MHz:	1500
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	3 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (4 x 1 GB 2Rx32 PC3L-12800U-11)
Disk Subsystem:	64 GB SSD
Other Hardware:	None

Software

Operating System:	Microsoft Windows 8.1 Pro 6.3.9600 N/A Build 9600
Compiler:	C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows; Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 10.0 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Microsoft Corporation
(Test Sponsor: Intel Corporation)

Surface Pro 3

SPECint2006 = 24.3

SPECint_base2006 = 23.4

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Sep-2014
Hardware Availability: Jun-2014
Software Availability: Oct-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	635	15.4	624	15.7	**626**	**15.6**	500	19.5	501	19.5	**501**	**19.5**
401.bzip2	**886**	**10.9**	883	10.9	887	10.9	883	10.9	882	10.9	**882**	**10.9**
403.gcc	541	14.9	**539**	**14.9**	539	14.9	501	16.1	**501**	**16.1**	502	16.1
429.mcf	283	32.3	284	32.1	**283**	**32.2**	283	32.3	284	32.1	**283**	**32.2**
445.gobmk	837	12.5	836	12.5	**836**	**12.5**	**791**	**13.3**	791	13.3	791	13.3
456.hmmer	309	30.2	**310**	**30.1**	325	28.7	309	30.2	**310**	**30.1**	325	28.7
458.sjeng	845	14.3	845	14.3	**845**	**14.3**	845	14.3	845	14.3	**845**	**14.3**
462.libquantum	44.4	467	**44.3**	**468**	44.2	469	44.4	467	**44.3**	**468**	44.2	469
464.h264ref	775	28.5	**776**	**28.5**	776	28.5	775	28.5	**776**	**28.5**	776	28.5
471.omnetpp	445	14.0	447	14.0	**447**	**14.0**	412	15.2	**412**	**15.2**	413	15.1
473.astar	524	13.4	**525**	**13.4**	525	13.4	524	13.4	**525**	**13.4**	525	13.4
483.xalancbmk	**276**	**25.0**	277	24.9	276	25.0	**276**	**25.0**	277	24.9	276	25.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 14.0 was set up to
generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r)
Parallel Studio XE 2013 program folder)
```

Platform Notes

```
Sysinfo program C:\Users\peca\Desktop\SPEC14.0\SPEC14.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on peca_i3 Wed Sep 10 15:59:54 2014

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name       : Microsoft Windows 8.1 Pro
OS Version    : 6.3.9600 N/A Build 9600
System Manufacturer: Microsoft Corporation
System Model  : Surface Pro 3
Processor(s)  : 1 Processor(s) Installed.
     [01]: Intel64 Family 6 Model 69 Stepping 1 GenuineIntel ~1500 Mhz
BIOS Version  : American Megatrends Inc. 3.10.0250, 8/28/2014
Total Physical Memory: 4,001 MB

Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page

Platform Notes (Continued)

```
 L2CacheSize   : 512
 L3CacheSize   : 3072
 MaxClockSpeed : 1501
 Name          : Intel(R) Core(TM) i3-4020Y CPU @ 1.50GHz
 NumberOfCores : 2
 NumberOfLogicalProcessors: 4

 (End of data from sysinfo program)
```

Component Notes

```
Test ran with power supply connected
Power Supply: 12V, 2.58A
```

General Notes

```
 OMP_NUM_THREADS set to number of processors cores
 KMP_AFFINITY set to granularity=fine,scatter
 Binaries compiled on a system with 1x Intel Core i7-860 CPU
 + 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Base Portability Flags

```
    400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
                   -DSPEC_CPU_NO_NEED_VA_COPY
      401.bzip2: -DSPEC_CPU_P64
        403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
        429.mcf: -DSPEC_CPU_P64
      445.gobmk: -DSPEC_CPU_P64
      456.hmmer: -DSPEC_CPU_P64
       458.sjeng: -DSPEC_CPU_P64
    462.libquantum: -DSPEC_CPU_P64
      464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
    471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
        473.astar: -DSPEC_CPU_P64
  483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword
```

Base Optimization Flags

C benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F512000000
```

C++ benchmarks:
```
-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F512000000 shlW64M.lib            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch`
`-Qauto-ilp32 /F512000000 shlW64M.lib`
`-link /FORCE:MULTIPLE`

401.bzip2: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias`
`-Qauto-ilp32 /F512000000`

403.gcc: `-QxCORE-AVX2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Nov 6 13:46:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 November 2014.