SPEC® CFP2006 Result

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license:	3	**Test date:**	Nov-2014
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Sep-2014
Tested by:	Hewlett-Packard Company	**Software Availability:**	Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Hardware

CPU Name:	Intel Xeon E5-2667 v3
CPU Characteristics:	Intel Turbo Boost Technology up to 3.60 GHz
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	16 cores, 2 chips, 8 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	20 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)
Disk Subsystem:	2 x 400 GB SAS SSD, RAID 1
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 7.0 (Maipo) 3.10.0-123.el7.x86_64
Compiler:	C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux; Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux
Auto Parallel:	No
File System:	ext4
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	None

SPEC CFP2006 Result

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
416.gamess	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
433.milc	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
434.zeusmp	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
435.gromacs	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
436.cactusADM	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
437.leslie3d	32	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC
444.namd	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
447.dealII	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
450.soplex	32	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC	NC	NC
453.povray	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
454.calculix	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
459.GemsFDTD	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
465.tonto	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
470.lbm	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
481.wrf	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC
482.sphinx3	32	NC	NC	NC	NC	NC	NC	32	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
Filesystem page cache cleared with:
 echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
```

Platform Notes

```
BIOS Configuration:
 HP Power Profile set to Custom
 HP Power Regulator set to HP Static High Performance Mode
 Minimum Processor Idle Power Core State set to C6 State
 Minimum Processor Idle Power Package State set to No Package State
 Thermal Configuration set to Maximum Cooling
 Collaborative Power Control set to Disabled
 QPI Snoop Configuration set to Early Snoop
 Processor Power and Utilization Monitoring set to Disabled
 Memory Refresh Rate set to 1x Refresh
Sysinfo program /cpu2006/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on Y-BL460cGen9-VP2 Tue Nov 18 22:14:06 2014

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2667 v3 @ 3.20GHz
      2 "physical id"s (chips)
      32 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 8
      siblings  : 16
      physical 0: cores 0 1 2 3 4 5 6 7
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Platform Notes (Continued)

```
      physical 1: cores 0 1 2 3 4 5 6 7
   cache size : 20480 KB

From /proc/meminfo
   MemTotal:       263844364 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.0 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.0"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:
   Linux Y-BL460cGen9-VP2 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT
   2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Nov 18 12:47

SPEC is set to: /cpu2006
   Filesystem            Type  Size  Used Avail Use% Mounted on
   /dev/mapper/rhel-root ext4  310G  116G  179G  40% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS HP I36 08/26/2014
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Platform Notes (Continued)

```
 Memory:
  16x HP 752369-081 16 GB 2 rank 2133 MHz

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/cpu2006/libs/32:/cpu2006/libs/64:/cpu2006/sh"

 Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB
 memory using RedHat EL 7.0
```

Base Compiler Invocation

C benchmarks:
`icc -m64`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

Base Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`

Continued on next page

SPEC CFP2006 Result

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3		**Test date:**	Nov-2014
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Sep-2014
Tested by:	Hewlett-Packard Company	**Software Availability:**	Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Base Portability Flags (Continued)

435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

C++ benchmarks:
```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

Fortran benchmarks:
```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
```

Benchmarks using both Fortran and C:
```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

SPEC CFP2006 Result

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company
Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks (except as noted below):
```
icpc  -m64
```

450.soplex: `icpc -m32 -L/opt/intel/composer_xe_2015/lib/ia32`

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
470.lbm: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`
482.sphinx3: `-DSPEC_CPU_LP64`

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3 -unroll2

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep-

Continued on next page

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Optimization Flags (Continued)

434.zeusmp: `basepeak = yes`

437.leslie3d: `-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch`

459.GemsFDTD: `basepeak = yes`

465.tonto: `-xCORE-AVX2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2) `-unroll4` `-auto -inline-calloc -opt-malloc-options=3`

Benchmarks using both Fortran and C:

435.gromacs: `-xCORE-AVX2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-opt-mem-layout-trans=3`(pass 2) `-prof-use`(pass 2) `-opt-prefetch -auto-ilp32`

436.cactusADM: `basepeak = yes`

454.calculix: `basepeak = yes`

481.wrf: `-xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32`

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html
http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml
http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Nov 3 17:34:12 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 January 2015.