



# SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp®2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

CPU2006 license: 55


**Test date:** Apr-2015

**Test sponsor:** Dell Inc.

**Hardware Availability:** Jun-2015

**Tested by:** Dell Inc.

**Software Availability:** Mar-2015



## Hardware

CPU Name: Intel Xeon E7-8870 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.90 GHz  
 CPU MHz: 2100  
 FPU: Integrated  
 CPU(s) enabled: 72 cores, 4 chips, 18 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

*Continued on next page*

## Software

Operating System: Red Hat Enterprise Linux Server release 7.1 (Maipo)  
 Compiler: 3.10.0-229.el7.x86\_64  
 Auto Parallel: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;  
 File System: Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux  
 Secondary Cache: Yes  
 ext4

*Continued on next page*



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

CPU2006 license: 55

Test date: Apr-2015

Test sponsor: Dell Inc.

Hardware Availability: Jun-2015

Tested by: Dell Inc.

Software Availability: Mar-2015

L3 Cache: 45 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 512 GB (32 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)  
 Disk Subsystem: 2 x 300 GB 15000 RPM SAS6, RAID0  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	<b>10.5</b>	<b>1290</b>	10.4	1310	11.6	1180	<b>10.5</b>	<b>1290</b>	10.4	1310	11.6	1180
416.gamess	629	31.1	<b>625</b>	<b>31.3</b>	623	31.4	532	36.8	<b>532</b>	<b>36.8</b>	531	36.9
433.milc	153	60.1	154	59.8	<b>153</b>	<b>60.1</b>	152	60.5	<b>152</b>	<b>60.5</b>	152	60.5
434.zeusmp	56.3	162	<b>56.2</b>	<b>162</b>	55.9	163	56.3	162	<b>56.2</b>	<b>162</b>	55.9	163
435.gromacs	<b>217</b>	<b>33.0</b>	216	33.1	225	31.8	<b>217</b>	<b>33.0</b>	216	33.1	225	31.8
436.cactusADM	11.7	1020	11.6	1030	<b>11.7</b>	<b>1030</b>	11.7	1020	11.6	1030	<b>11.7</b>	<b>1030</b>
437.leslie3d	36.7	256	<b>36.7</b>	<b>256</b>	36.9	255	36.7	256	<b>36.7</b>	<b>256</b>	36.9	255
444.namd	<b>328</b>	<b>24.5</b>	327	24.5	328	24.5	319	25.2	<b>318</b>	<b>25.2</b>	318	25.2
447.dealII	242	47.2	<b>243</b>	<b>47.1</b>	243	47.1	242	47.2	<b>243</b>	<b>47.1</b>	243	47.1
450.soplex	213	39.2	215	38.8	<b>214</b>	<b>39.0</b>	213	39.2	215	38.8	<b>214</b>	<b>39.0</b>
453.povray	<b>108</b>	<b>49.3</b>	108	49.3	107	49.6	<b>96.3</b>	<b>55.3</b>	96.2	55.3	96.4	55.2
454.calculix	186	44.3	<b>186</b>	<b>44.2</b>	188	44.0	<b>170</b>	<b>48.5</b>	170	48.5	170	48.6
459.GemsFDTD	51.1	207	53.2	199	<b>52.3</b>	<b>203</b>	43.7	243	42.8	248	<b>43.1</b>	<b>246</b>
465.tonto	312	31.6	293	33.6	<b>295</b>	<b>33.4</b>	<b>220</b>	<b>44.8</b>	219	44.9	220	44.7
470.lbm	<b>8.11</b>	<b>1690</b>	8.09	1700	8.66	1590	<b>8.11</b>	<b>1690</b>	8.09	1700	8.66	1590
481.wrf	110	102	<b>109</b>	<b>103</b>	108	103	110	102	<b>109</b>	<b>103</b>	108	103
482.sphinx3	<b>315</b>	<b>62.0</b>	311	62.6	316	61.8	<b>314</b>	<b>62.1</b>	<b>314</b>	<b>62.0</b>	316	61.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
 Virtualization Technology disabled  
 System Profile set to Custom  
 CPU Power Management set to Maximum Performance  
 Memory Frequency set to Maximum Performance  
 Turbo Boost enabled  
 Energy Efficient Turbo disabled  
 C1E disabled  
 C States disabled

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Mar-2015

## Platform Notes (Continued)

Collaborative CPU Performance Control disabled

Memory Patrol Scrub disabled

Memory Refresh Rate set to 1x

Uncore Frequency set to Maximum

Energy Efficient Policy set to Performance

Monitor/MWait enabled

Sysinfo program

```
/root/Desktop/Performance/ic15.0_Aug29_2014/config/sysinfo.rev6914
$Rev: 6914 $ $Date::: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Fri Apr 10 15:52:05 2015
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E7-8870 v3 @ 2.10GHz
        4 "physical id"s (chips)
        144 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 18
siblings : 36
physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 2: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
physical 3: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
cache size : 46080 KB
```

From /proc/meminfo

```
MemTotal:      528089244 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

From /etc/\*release\* /etc/\*version\*

```
os-release:
  NAME="Red Hat Enterprise Linux Server"
  VERSION="7.1 (Maipo)"
  ID="rhel"
  ID_LIKE="fedora"
  VERSION_ID="7.1"
  PRETTY_NAME="Red Hat Enterprise Linux Server 7.1 (Maipo)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:redhat:enterprise_linux:7.1:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.1:ga:server
```

uname -a:

```
Linux localhost.localdomain 3.10.0-229.el7.x86_64 #1 SMP Thu Jan 29 18:37:38
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Mar-2015

## Platform Notes (Continued)

EST 2015 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Apr 10 15:51 last=5

SPEC is set to: /root/Desktop/Performance/ic15.0\_Aug29\_2014  
Filesystem Type Size Used Avail Use% Mounted on

/dev/sda2 ext4 366G 10G 338G 3% /

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Dell Inc. 1.0.1 [MRC\_096] 03/27/2015

Memory:

32x 00AD00B300AD Not Specified 16 GB 2 rank 2133 MHz, configured at 1600 MHz  
64x Not Specified Not Specified

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"

LD\_LIBRARY\_PATH = "/root/Desktop/Performance/ic15.0\_Aug29\_2014/lib32:/root/Desktop/Performance/ic15.0\_Aug29\_2014/lib64:/root/Desktop/Performance/ic15.0\_Aug29\_2014/sh"

OMP\_NUM\_THREADS = "72"

Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB memory using RedHat EL 7.0

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent\_hugepage/enabled

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp2006 =**

**111**

**SPECfp\_base2006 =**

**105**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:**

Apr-2015

**Hardware Availability:** Jun-2015

**Software Availability:** Mar-2015

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias
```

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias
```

Fortran benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Apr-2015

Hardware Availability: Jun-2015

Software Availability: Mar-2015

## Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll12 -ansi-alias  
-parallel

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll14  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 111**

PowerEdge R930 (Intel Xeon E7-8870 v3, 2.10 GHz)

**SPECfp\_base2006 = 105**

CPU2006 license: 55

Test date: Apr-2015

Test sponsor: Dell Inc.

Hardware Availability: Jun-2015

Tested by: Dell Inc.

Software Availability: Mar-2015

## Peak Optimization Flags (Continued)

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll14

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>  
<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revE.20150421.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>  
<http://www.spec.org/cpu2006/flags/Dell-Platform-Settings-V1.2-revE.20150421.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue May 5 15:15:41 2015 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 5 May 2015.