# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Supermicro

Supermicro X11SSL-nF motherboard
(X11SSL-nF , Intel Xeon E3-1270 v5)

SPECfp®2006 = 98.1

SPECfp_base2006 = 95.8

**CPU2006 license:** 001176
**Test sponsor:** Supermicro
**Tested by:** Supermicro

**Test date:** Jan-2016
**Hardware Availability:** Oct-2015
**Software Availability:** Mar-2015




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E3-1270 v5 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 4.00 GHz |
| CPU MHz: | 3600 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 1 chip, 4 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | Red Hat Enterprise Linux Server release 7.1, Kernel 3.10.0-229.el7.x86_64 |
| Compiler: | C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux;<br>Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux |
| Auto Parallel: | Yes |
| File System: | xfs |
| System State: | Run level 3 (multi-user) |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Supermicro

Supermicro X11SSL-nF motherboard
(X11SSL-nF , Intel Xeon E3-1270 v5)

SPECfp2006 = 98.1

SPECfp_base2006 = 95.8

**CPU2006 license:** 001176
**Test sponsor:** Supermicro
**Tested by:** Supermicro

**Test date:** Jan-2016
**Hardware Availability:** Oct-2015
**Software Availability:** Mar-2015

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 64 GB (4 x 16 GB 2Rx8 PC4-2133P-E)
Disk Subsystem: 1 x 1000 GB SATA III, 7200 RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 97.6 | 139 | **97.5** | **139** | 97.3 | 140 | 97.6 | 139 | **97.5** | **139** | 97.3 | 140 |
| 416.gamess | **378** | **51.7** | 378 | 51.8 | 380 | 51.5 | **346** | **56.5** | 346 | 56.6 | 347 | 56.5 |
| 433.milc | 84.4 | 109 | 84.0 | 109 | **84.1** | **109** | 84.0 | 109 | 83.5 | 110 | **83.6** | **110** |
| 434.zeusmp | 43.3 | 210 | **43.3** | **210** | 43.3 | 210 | 43.3 | 210 | **43.3** | **210** | 43.3 | 210 |
| 435.gromacs | 113 | 63.4 | 113 | 63.5 | **113** | **63.4** | 113 | 63.4 | 113 | 63.5 | **113** | **63.4** |
| 436.cactusADM | 33.6 | 356 | 33.7 | 354 | **33.7** | **354** | 33.6 | 356 | 33.7 | 354 | **33.7** | **354** |
| 437.leslie3d | 87.9 | 107 | **88.1** | **107** | 88.1 | 107 | 87.9 | 107 | **88.1** | **107** | 88.1 | 107 |
| 444.namd | 213 | 37.6 | 212 | 37.8 | **213** | **37.7** | 209 | 38.3 | 209 | 38.4 | **209** | **38.3** |
| 447.dealII | 151 | 75.7 | **151** | **75.6** | 151 | 75.5 | 151 | 75.7 | **151** | **75.6** | 151 | 75.5 |
| 450.soplex | 151 | 55.1 | 148 | 56.3 | **151** | **55.2** | 151 | 55.1 | 148 | 56.3 | **151** | **55.2** |
| 453.povray | 72.4 | 73.5 | **72.3** | **73.6** | 72.1 | 73.8 | **64.3** | **82.7** | 64.0 | 83.1 | 64.5 | 82.4 |
| 454.calculix | 107 | 76.8 | **108** | **76.3** | 109 | 75.8 | 103 | 79.9 | **103** | **80.0** | 103 | 80.4 |
| 459.GemsFDTD | 129 | 82.2 | 129 | 82.3 | **129** | **82.2** | **127** | **83.7** | 127 | 83.7 | 127 | 83.6 |
| 465.tonto | **148** | **66.5** | 148 | 66.3 | 147 | 66.7 | 133 | 74.1 | 134 | 73.6 | **133** | **74.1** |
| 470.lbm | **73.8** | **186** | 73.8 | 186 | 73.8 | 186 | **73.8** | **186** | 73.8 | 186 | 73.8 | 186 |
| 481.wrf | **85.5** | **131** | 85.3 | 131 | 85.5 | 131 | **85.5** | **131** | 85.3 | 131 | 85.5 | 131 |
| 482.sphinx3 | 188 | 104 | 190 | 103 | **190** | **103** | 189 | 103 | **189** | **103** | 187 | 104 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

## Platform Notes

```
As tested, the system used a Supermicro CSE-113MFAC2-R606CB chassis.
The chassis is configured with 2 PWS-606P-1R redundant power supply, 1 SNK-P0046P heatsink,
as well as 4 FAN-0154L4 middle cooling fan.
 Sysinfo program /home/cpu2006/config/sysinfo.rev6914
 $Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
 running on localhost.localdomain Mon Jan 18 18:59:47 2016

 This section contains SUT (System Under Test) info as seen by
 some common utilities.  To remove or add to this section, see:
   http://www.spec.org/cpu2006/Docs/config.html#sysinfo
```

Continued on next page

## Platform Notes (Continued)

```
From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E3-1270 v5 @ 3.60GHz
      1 "physical id"s (chips)
      8 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 4
      siblings  : 8
      physical 0: cores 0 1 2 3
   cache size : 8192 KB

From /proc/meminfo
   MemTotal:       65630744 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.1 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.1"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.1 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.1:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.1 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.1:ga:server

uname -a:
   Linux localhost.localdomain 3.10.0-229.el7.x86_64 #1 SMP Thu Jan 29 18:37:38
   EST 2015 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Jan 18 18:48

SPEC is set to: /home/cpu2006
   Filesystem            Type  Size  Used Avail Use% Mounted on
   /dev/mapper/rhel-home xfs   865G  170G  696G  20% /home
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS American Megatrends Inc. 1.0a 12/25/2015
  Memory:
   4x Samsung M391A2K43BB1-CPB 16 GB 2 rank 2133 MHz
```

Continued on next page

## Platform Notes (Continued)

```
(End of data from sysinfo program)
```

## General Notes

```
Environment variables set by runspec before the start of the run:
KMP_AFFINITY = "granularity=fine,compact,1,0"
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"
OMP_NUM_THREADS = "4"

 Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB
 memory using RedHat EL 7.0
 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
```

# Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

# Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Continued on next page

## Base Portability Flags (Continued)

482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

## Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-auto-ilp32 -ansi-alias

Continued on next page

# Peak Optimization Flags (Continued)

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias -parallel

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

Continued on next page

## Peak Optimization Flags (Continued)

481.wrf: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html`
`http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revG.20141230.00.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml`
`http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revG.20141230.00.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Feb 9 17:20:29 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 February 2016.