SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697 v4)

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Feb-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Copies
410.bwaves
416.gamess
433.milc
434.zeusmp
435.gromacs
436.cactusADM
437.leslie3d
444.namd
447.dealII
450.soplex
453.povray
454.calculix
459.GemsFDTD
[illegible]
470.lbm
481.wrf
482.sphinx3

Non-Compliant

SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697 v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Feb-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Hardware

CPU Name:	Intel Xeon E5-2697 v4
CPU Characteristics:	Intel Turbo Boost Technology up to 3.60 GHz
CPU MHz:	2300
FPU:	Integrated
CPU(s) enabled:	36 cores, 2 chips, 18 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	45 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2400T-)
Disk Subsystem:	1 x 600GB SAS, 10000 RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 7.0 (Maipo) 3.10.0-123.el7.x86_64
Compiler:	C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux; Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux
Auto Parallel:	No
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697 v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Feb-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
416.gamess	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
433.milc	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
434.zeusmp	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
435.gromacs	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
436.cactusADM	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
437.leslie3d	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
444.namd	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
447.dealII	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
450.soplex	72	NC	NC	NC	NC	NC	NC	36	NC	NC	NC	NC	NC	NC
453.povray	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
454.calculix	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
459.GemsFDTD	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
465.tonto	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
470.lbm	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
481.wrf	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC
482.sphinx3	72	NC	NC	NC	NC	NC	NC	72	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Platform Notes

```
BIOS configuration:
Set Power Efficiency Mode to Performance
Set Snoop Mode to COD mode
Set Patrol Scrub to Disable
Sysinfo program /spec/spec16/config/sysinf rev69
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb866 5a2859 2ceab81e28219e1
running on localhost.localdaomain Fri Nov  7 0 57:54 2014

This section contains SUT (System Un er Tes ) info as seen by
some common utilities.  To rem ve or add to his section, see:
  http://www.spec.org/cpu200 /Docs/co ig.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) X on(R) CPU E 2697 v4 @ 2.30GHz
      2 "physical id"s (ch s)
      72 "processors"
   cores, siblings (Caution: unting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 9
      siblings  : 1
      physical 0: cores  1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
      physical 1: cores 0 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
   cache size : 230 KB

From /proc/memin
   MemTotal:       263564176 kB
   HugePages_Total:       0
   Hugepagesi :       2048 kB

From /etc/ elease* /etc/*version*
   os-r
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.0 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.0"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Platform Notes (Continued)

```
uname -a:
   Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
   EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Nov 5 10:50

SPEC is set to: /spec/spec16
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda2      xfs   549G  138G  411G  26% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS Insyde Corp. 7.11 02/1[illegible]2016
  Memory:
   8x NO DIMM NO DIMM   3 Rank
   8x Samsung M393A2G40EB[illegible]-CRC 16 GB 1 rank 2400 MHz
   8x Samsung M393A[illegible]EB1-CRC 16 GB 2 rank 2400 MHz

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/spec/spec16/libs/32:/spec/spec16/libs/64:/spec/spec16/sh"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB
      RedHat EL 7.1
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1>       /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>
The Huawei CH121 V3 and Huawei CH222 V3
are electronically equivalent.
The results have been measured on a Huawei CH121 V3 model
```

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Base Optimization Flags (Continued)

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p3
-ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks (except as noted below):
icpc -m64

450.soplex: icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page

Non-Compliant

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Peak Portability Flags (Continued)

450.soplex: -D_FILE_OFFSET_BITS=64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

-xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Peak Optimization Flags (Continued)

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:thre fe(pass
-ipo(pass 2) -O3(pass 2) -no-prec-di (pass
-par-num-threads=1(pass 1) -prof e(pass -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pas 2) -prof-gen threadsafe(pass 1)
-ipo(pass 2) -O3(2) -no-prec-div(pass 2)
-par-num-threads pass 1) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -op loc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AV pass 2) -prof-gen:threadsafe(pass 1)
-ipo(ss 2) - pass 2) -no-prec-div(pass 2)
-par- m-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-u pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml

SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697 v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Feb-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 15:51:42 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 April 2016.