# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Huawei

Huawei XH620 V3(Intel Xeon E5-2630L v4)

SPECfp®_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** May-2016
**Hardware Availability:** Mar-2016
**Software Availability:** Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

| Copies |
|---|
| 410.bwaves |
| 416.gamess |
| 433.milc |
| 434.zeusmp |
| 435.gromacs |
| 436.cactusADM |
| 437.leslie3d |
| 444.namd |
| 447.dealII |
| 450.soplex |
| 453.povray |
| 454.calculix |
| 459.GemsFDTD |
| [illegible] |
| 470.lbm |
| 481.wrf |
| 482.sphinx3 |

Non-Compliant

# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Huawei

Huawei XH620 V3(Intel Xeon E5-2630L v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** May-2016
**Hardware Availability:** Mar-2016
**Software Availability:** Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5-2630L v4 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 2.90 GHz |
| CPU MHz: | 1800 |
| FPU: | Integrated |
| CPU(s) enabled: | 20 cores, 2 chips, 10 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1,2 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 25 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 256 GB (16 x 16 GB 2Rx4 PC4-240[illegible]R, runnin[illegible] 2133 MHz) |
| Disk Subsystem: | 1 x 500 GB SATA, 7[illegible]00 RPM |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | Red Hat Enterprise Linux Server release 7.2 (Maipo) 3.[illegible]-327.el7.x86_64 |
| Compiler: | C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux; |
| Auto Parallel: | No |
| File System: | xfs |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32/64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | None |

# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Huawei

Huawei XH620 V3(Intel Xeon E5-2630L v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** May-2016
**Hardware Availability:** Mar-2016
**Software Availability:** Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 416.gamess | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 433.milc | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 434.zeusmp | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 435.gromacs | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 436.cactusADM | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 437.leslie3d | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 444.namd | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 447.dealII | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 450.soplex | 40 | NC | NC | NC | NC | NC | NC | 20 | NC | NC | NC | NC | NC | NC |
| 453.povray | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 454.calculix | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 459.GemsFDTD | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 465.tonto | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 470.lbm | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 481.wrf | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |
| 482.sphinx3 | 40 | NC | NC | NC | NC | NC | NC | 40 | NC | NC | NC | NC | NC | NC |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

## Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

## Platform Notes

```
BIOS configuration:
Set Power Efficiency Mode to Performance
Set Snoop Mode to ES mode
Set Patrol Scrub to Disable
Sysinfo program /spec16/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667a2859632ceab81e28219e1
running on localhost.localdomain Tue May 10 06:16:30 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2630L v4 @ 1.80GHz
      2 "physical id"s (chips)
      40 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 10
      siblings  : 20
      physical 0: cores 0 1 2 3 4 8 9 10 11 12
      physical 1: cores 0 1 2 3 4 8 9 10 11 12
   cache size : 25600 KB

From /proc/meminfo
   MemTotal:       263567004 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.2 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.2"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.2 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.2:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.2:ga:server
```

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

## Platform Notes (Continued)

```
uname -a:
   Linux localhost.localdomain 3.10.0-327.el7.x86_64 #1 SMP Thu Oct 29 17:29:29
   EDT 2015 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 May 6 08:37

SPEC is set to: /spec16
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda3      xfs   431G   84G  347G  20% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS Insyde Corp. 3.12 03/04/2016
  Memory:
   8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz, configured at 2133 MHz
   8x Samsung M393A2G40EB2-CRC 16 GB 2 rank 2400 MHz, configured at 2133 MHz

(End of data from sysinfo program)
```

## General Notes

```
Environment variable set by runspec before the start of the run:
LD_LIBRARY_PATH = "/spec16/libs/32:/spec16/libs/64:/spec16/sh"

 Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB
 memory using RedHat EL 7.1
 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
 Filesystem page cache cleared with:
 echo 1>       /proc/sys/vm/drop_caches
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
 The Huawei XH622 V3 and Huawei XH628 V3 and Huawei XH620 V3
 are electronically equivalent.
 The results have been measured on a Huawei XH620 V3 model
```

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

## Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Continued on next page

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

## Base Optimization Flags (Continued)

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p3
-ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

## Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks (except as noted below):
icpc -m64

450.soplex: icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page



Non-Compliant

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not <a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

## Peak Portability Flags (Continued)

450.soplex: -D_FILE_OFFSET_BITS=64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

-xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

Continued on next page



Non-Compliant

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

## Peak Optimization Flags (Continued)

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:thre fe(pass
-ipo(pass 2) -O3(pass 2) -no-prec-di (pass
-par-num-threads=1(pass 1) -prof e(pass -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pas 2) -prof-gen threadsafe(pass 1)
-ipo(pass 2) -O3( 2) -no-prec-div(pass 2)
-par-num-threads pass 1) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -op loc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AV pass 2) -prof-gen:threadsafe(pass 1)
-ipo( ss 2) -O pass 2) -no-prec-div(pass 2)
-par- m-threads=1(pass 1) -opt-mem-layout-trans=3(pass 2)
-prof-u pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml

# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Huawei

Huawei XH620 V3(Intel Xeon E5-2630L v4)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

**CPU2006 license:** 3175
**Test sponsor:** Huawei
**Tested by:** Huawei

**Test date:** May-2016
**Hardware Availability:** Mar-2016
**Software Availability:** Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener**

Non-Compliant

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 16:31:45 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 14 June 2016.