SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6 PRO-7400B with Radeon R5 Graphics)

SPECfp®_rate2006 = 39.0

SPECfp_rate_base2006 = 38.5

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2016
Hardware Availability: Jul-2014
Software Availability: Aug-2015



Hardware

CPU Name:	AMD A6 PRO-7400B
CPU Characteristics:	AMD Turbo CORE technology up to 3.90 GHz
CPU MHz:	3500
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	96 KB I on chip per chip; 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per chip

Continued on next page

Software

Operating System:	Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
Auto Parallel:	No

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6 PRO-7400B with Radeon R5 Graphics)

SPECfp_rate2006 = 39.0

SPECfp_rate_base2006 = 38.5

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2016
Hardware Availability: Jul-2014
Software Availability: Aug-2015

L3 Cache: None
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
Disk Subsystem: Seagate Barracuda 250 GB SATA, 7200 RPM
Other Hardware: None

File System: NTFS
System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 11.0 from http://www.microquill.com/

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	585	46.4	583	46.6	**583**	**46.6**	2	585	46.4	583	46.6	**583**	**46.6**
416.gamess	2	823	47.6	832	47.0	**831**	**47.2**	2	823	47.6	832	47.0	**831**	**47.2**
433.milc	2	**448**	**41.0**	448	41.0	448	41.0	2	**448**	**41.0**	448	41.0	448	41.0
434.zeusmp	2	433	42.0	432	42.0	**433**	**42.0**	2	433	42.0	432	42.0	**433**	**42.0**
435.gromacs	2	440	32.4	445	32.0	**443**	**32.2**	2	440	32.4	445	32.0	**443**	**32.2**
436.cactusADM	2	614	39.0	**614**	**39.0**	611	39.2	2	614	39.0	**614**	**39.0**	611	39.2
437.leslie3d	2	716	26.2	728	25.8	**723**	**26.0**	2	716	26.2	728	25.8	**723**	**26.0**
444.namd	2	**549**	**29.2**	548	29.2	549	29.2	2	**544**	**29.6**	544	29.6	543	29.6
447.dealII	2	**431**	**53.2**	432	53.0	430	53.2	2	**431**	**53.2**	432	53.0	430	53.2
450.soplex	2	**652**	**25.6**	652	25.6	649	25.8	2	633	26.4	**634**	**26.4**	635	26.2
453.povray	2	**203**	**52.4**	203	52.4	201	53.0	2	**182**	**58.4**	180	59.0	183	58.2
454.calculix	2	**362**	**45.6**	398	41.4	361	45.6	2	**362**	**45.6**	398	41.4	361	45.6
459.GemsFDTD	2	1014	21.0	1019	20.8	**1016**	**20.8**	2	1014	21.0	1019	20.8	**1016**	**20.8**
465.tonto	2	**529**	**37.2**	531	37.0	526	37.4	2	510	38.6	**511**	**38.6**	512	38.4
470.lbm	2	449	61.2	450	61.0	**450**	**61.2**	2	449	61.2	450	61.0	**450**	**61.2**
481.wrf	2	**469**	**47.6**	468	47.6	470	47.6	2	**469**	**47.6**	468	47.6	470	47.6
482.sphinx3	2	1134	34.4	**1135**	**34.4**	1136	34.4	2	1134	34.4	**1135**	**34.4**	1136	34.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on Clt1C872C5DF572 Sun May 15 07:29:18 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
    http://www.spec.org/cpu2006/Docs/config.html#sysinfo

  Trying 'systeminfo'
  OS Name       : Microsoft Windows 7 Ultimate
  OS Version    : 6.1.7601 Service Pack 1 Build 7601
  System Manufacturer: System manufacturer
  System Model  : System Product Name
  Processor(s)  : 1 Processor(s) Installed.
       [01]: AMD64 Family 21 Model 48 Stepping 1 AuthenticAMD ~3500 Mhz
  BIOS Version  : American Megatrends Inc. 2502, 12/11/2015
  Total Physical Memory: 7,108 MB

  Trying 'wmic cpu get /value'
  DeviceID      : CPU0
  L2CacheSize   : 25359
  L3CacheSize   : 0
  MaxClockSpeed : 3500
  Name          : AMD A6 PRO-7400B R5, 6 Compute Cores 2C+4G
  NumberOfCores : 1
  NumberOfLogicalProcessors: 2

  (End of data from sysinfo program)
```

Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
```

General Notes

```
450.soplex (peak): "getline_test" src.alt was used.

447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.

450.soplex (base): "getline_test" src.alt was used.

447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.

 Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
 + 64GB memory using Windows 8.1 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
    icl -Qvc12 -Qstd=c99
```

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
453.povray: -DSPEC_CPU_P64
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch /F1000000000 -link /FORCE:MULTIPLE

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

Peak Compiler Invocation

C benchmarks:
icl -Qvc12 -Qstd=c99

C++ benchmarks:
icl -Qvc12

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc12 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE

447.dealII: basepeak = yes

450.soplex: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

Continued on next page

Peak Optimization Flags (Continued)

453.povray: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:20 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.