



# SPEC® CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

## Huawei

SPECfp®2006 = **151**

### Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = **145**

CPU2006 license: 3175


Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016



**Hardware**

CPU Name: Intel Xeon Gold 6150  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.70 GHz  
 CPU MHz: 2700  
 FPU: Integrated  
 CPU(s) enabled: 36 cores, 2 chips, 18 cores/chip  
 CPU(s) orderable: 1,2 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

**Software**

Operating System: Red Hat Enterprise Linux Server release 7.3 (Maipo)  
 3.10.0-514.el7.x86\_64  
 Compiler: C/C++: Version 17.0.0.098 of Intel C/C++ Compiler for Linux;  
 Fortran: Version 17.0.0.098 of Intel Fortran Compiler for Linux  
 Auto Parallel: Yes  
 File System: xfs

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

## Huawei

SPECfp2006 = **151**

## Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = **145**

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

L3 Cache: 24.75 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 384 GB (24 x 16 GB 2Rx8 PC4-2666V-R)  
 Disk Subsystem: 1 x 1200 GB SAS, 10000 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

| Benchmark     | Base               |                    |                    |                    |                    |                    | Peak               |                    |                    |                    |                    |                    |
|---------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
|               | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              |
| 410.bwaves    | <b><u>13.1</u></b> | <b><u>1040</u></b> | 12.9               | 1050               | 13.2               | 1030               | <b><u>13.1</u></b> | <b><u>1040</u></b> | 12.9               | 1050               | 13.2               | 1030               |
| 416.gamess    | 395                | 49.5               | <b><u>395</u></b>  | <b><u>49.5</u></b> | 395                | 49.5               | <b><u>371</u></b>  | <b><u>52.8</u></b> | 371                | 52.8               | 370                | 52.9               |
| 433.milc      | 116                | 79.3               | <b><u>115</u></b>  | <b><u>79.6</u></b> | 111                | 82.4               | 116                | 79.3               | <b><u>115</u></b>  | <b><u>79.6</u></b> | 111                | 82.4               |
| 434.zeusmp    | <b><u>32.9</u></b> | <b><u>277</u></b>  | 32.7               | 279                | 32.9               | 276                | <b><u>32.9</u></b> | <b><u>277</u></b>  | 32.7               | 279                | 32.9               | 276                |
| 435.gromacs   | 123                | 58.2               | 123                | 57.9               | <b><u>123</u></b>  | <b><u>58.0</u></b> | 123                | 58.2               | 123                | 57.9               | <b><u>123</u></b>  | <b><u>58.0</u></b> |
| 436.cactusADM | <b><u>10.5</u></b> | <b><u>1130</u></b> | 10.6               | 1130               | 10.5               | 1140               | <b><u>10.5</u></b> | <b><u>1130</u></b> | 10.6               | 1130               | 10.5               | 1140               |
| 437.leslie3d  | <b><u>19.3</u></b> | <b><u>487</u></b>  | 19.7               | 477                | 19.2               | 490                | <b><u>19.3</u></b> | <b><u>487</u></b>  | 19.7               | 477                | 19.2               | 490                |
| 444.namd      | 225                | 35.6               | <b><u>225</u></b>  | <b><u>35.6</u></b> | 225                | 35.6               | 221                | 36.3               | <b><u>221</u></b>  | <b><u>36.3</u></b> | 221                | 36.3               |
| 447.dealII    | 162                | 70.8               | <b><u>162</u></b>  | <b><u>70.8</u></b> | 162                | 70.7               | 162                | 70.8               | <b><u>162</u></b>  | <b><u>70.8</u></b> | 162                | 70.7               |
| 450.soplex    | 161                | 51.6               | <b><u>162</u></b>  | <b><u>51.6</u></b> | 162                | 51.5               | 161                | 51.6               | <b><u>162</u></b>  | <b><u>51.6</u></b> | 162                | 51.5               |
| 453.povray    | 77.1               | 69.0               | 76.6               | 69.5               | <b><u>76.8</u></b> | <b><u>69.2</u></b> | <b><u>67.8</u></b> | <b><u>78.4</u></b> | 68.1               | 78.2               | 66.3               | 80.3               |
| 454.calculix  | 112                | 73.4               | <b><u>112</u></b>  | <b><u>73.4</u></b> | 113                | 73.2               | <b><u>107</u></b>  | <b><u>77.0</u></b> | 107                | 77.1               | 107                | 76.9               |
| 459.GemsFDTD  | 37.9               | 280                | <b><u>38.3</u></b> | <b><u>277</u></b>  | 39.2               | 271                | <b><u>31.6</u></b> | <b><u>336</u></b>  | 31.9               | 332                | 31.4               | 338                |
| 465.tonto     | <b><u>183</u></b>  | <b><u>53.7</u></b> | 184                | 53.5               | 181                | 54.4               | 142                | 69.5               | 141                | 69.7               | <b><u>141</u></b>  | <b><u>69.5</u></b> |
| 470.lbm       | 10.2               | 1340               | <b><u>10.2</u></b> | <b><u>1340</u></b> | 10.4               | 1320               | 10.2               | 1340               | <b><u>10.2</u></b> | <b><u>1340</u></b> | 10.4               | 1320               |
| 481.wrf       | 86.4               | 129                | 82.9               | 135                | <b><u>83.6</u></b> | <b><u>134</u></b>  | 86.4               | 129                | 82.9               | 135                | <b><u>83.6</u></b> | <b><u>134</u></b>  |
| 482.sphinx3   | 237                | 82.3               | <b><u>237</u></b>  | <b><u>82.1</u></b> | 239                | 81.4               | 237                | 82.3               | <b><u>237</u></b>  | <b><u>82.1</u></b> | 239                | 81.4               |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Set Power Efficiency Mode to Custom  
 Set Hyper-Threading to Disable  
 Sysinfo program /spec17/config/sysinfo.rev6993  
 Revision 6993 of 2015-11-06 (b5e8d4b4eb51ed28d7f98696cbe290c1)  
 running on localhost.localdomain Mon Jul 3 23:37:05 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 151

Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = 145

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

## Platform Notes (Continued)

```

From /proc/cpuinfo
model name : Intel(R) Xeon(R) Gold 6150 CPU @ 2.70GHz
 2 "physical id"s (chips)
36 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 18
  siblings  : 18
  physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
  physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27
cache size : 25344 KB

```

```

From /proc/meminfo
MemTotal:      394919348 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

```

From /etc/*release* /etc/*version*
os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.3 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.3"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.3 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.3:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.3:ga:server

```

```

uname -a:
Linux localhost.localdomain 3.10.0-514.el7.x86_64 #1 SMP Wed Oct 19 11:24:13
EDT 2016 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Jul 3 07:07

```

SPEC is set to: /spec17
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2       xfs   262G  86G  177G  33% /

```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS INSYDE Corp. 0.10 02/14/2017

Memory:

24x Samsung M393A2K43BB1-CTD 16 GB 2 rank 2666 MHz  
Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 151

Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = 145

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

## Platform Notes (Continued)

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact"

LD\_LIBRARY\_PATH = "/spec17/libs/32:/spec17/libs/64:/spec17/sh10.2"

OMP\_NUM\_THREADS = "36"

Binaries compiled on a system with 1x Intel Core i7-4790 CPU + 32GB RAM memory using Redhat Enterprise Linux 7.2

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 151

Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = 145

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

## Base Portability Flags (Continued)

465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 5



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 151

Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = 145

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

## Peak Optimization Flags (Continued)

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)  
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)  
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)  
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)  
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -unroll2 -inline-level=0  
-qopt-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xCORE-AVX2(pass 2)  
-par-num-threads=1(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -inline-calloc -qopt-malloc-options=3  
-auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Huawei

SPECfp2006 = 151

Huawei 2288H V5 (Intel Xeon Gold 6150)

SPECfp\_base2006 = 145

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Jul-2017

Hardware Availability: Aug-2017

Software Availability: Nov-2016

## Peak Optimization Flags (Continued)

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-SKL-V1.6.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic17.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-SKL-V1.6.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Jul 25 15:53:37 2017 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 25 July 2017.