SPEC® CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECfp®_rate2006 = 894

SPECfp_rate_base2006 = 871

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Feb-2017
Hardware Availability: Jan-2017
Software Availability: Jan-2016



Hardware

CPU Name:	Intel Xeon Phi 7290F
CPU Characteristics:	Intel Turbo Boost Technology up to 1.70 GHz
CPU MHz:	1500
FPU:	Integrated
CPU(s) enabled:	72 cores, 1 chip, 72 cores/chip, 4 threads/core
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per two cores

Continued on next page

Software

Operating System:	SUSE Linux Enterprise Server 12 SP2 (x86_64) 4.4.16-56-default
Compiler:	C/C++: Version 16.0.2.181 of Intel C++ Studio XE for Linux; Fortran: Version 16.0.2.181 of Intel Fortran Studio XE for Linux
Auto Parallel:	No
File System:	btrfs
System State:	Run level 3 (multi-user)

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECfp_rate2006 = 894

SPECfp_rate_base2006 = 871

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Feb-2017
Hardware Availability: Jan-2017
Software Availability: Jan-2016

L3 Cache: None
Other Cache: None
Memory: 400 GB (6 x 64 GB 2Rx8 PC4-2400T-R, 8 x 2 GB 7200 MHz MCDRAM)
Disk Subsystem: 1 x 1 TB 7.2K SATA
Other Hardware: None

Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	288	8419	465	8432	464	**8423**	**465**	288	8419	465	8432	464	**8423**	**465**
416.gamess	288	7995	705	8031	702	**8028**	**702**	288	**7599**	**742**	7601	742	7570	745
433.milc	288	**4247**	**623**	4251	622	4244	623	288	**4247**	**623**	4251	622	4244	623
434.zeusmp	288	**2486**	**1050**	2523	1040	2455	1070	288	**2486**	**1050**	2523	1040	2455	1070
435.gromacs	288	1712	1200	1734	1190	**1723**	**1190**	288	1675	1230	**1678**	**1230**	1683	1220
436.cactusADM	288	2282	1510	**2283**	**1510**	2294	1500	288	2282	1510	**2283**	**1510**	2294	1500
437.leslie3d	288	4052	668	3982	680	**4016**	**674**	288	4052	668	3982	680	**4016**	**674**
444.namd	288	2355	981	2366	976	**2357**	**980**	288	**2276**	**1010**	2268	1020	2282	1010
447.dealII	288	2315	1420	2310	1430	**2310**	**1430**	288	2315	1420	2310	1430	**2310**	**1430**
450.soplex	288	4111	584	**3758**	**639**	3755	640	288	**3682**	**652**	3738	643	3263	736
453.povray	288	1641	934	**1638**	**935**	1616	948	288	1326	1160	1306	1170	**1307**	**1170**
454.calculix	288	1719	1380	1727	1380	**1723**	**1380**	288	1719	1380	1727	1380	**1723**	**1380**
459.GemsFDTD	288	**10075**	**303**	10121	302	10067	304	288	**10075**	**303**	10121	302	10067	304
465.tonto	288	2805	1010	**2810**	**1010**	2811	1010	288	**2600**	**1090**	2600	1090	2597	1090
470.lbm	288	6173	641	**6174**	**641**	6175	641	288	6173	641	**6174**	**641**	6175	641
481.wrf	288	2605	1240	**2559**	**1260**	2559	1260	288	2605	1240	**2559**	**1260**	2559	1260
482.sphinx3	288	4401	1280	**4334**	**1300**	4275	1310	288	4401	1280	**4334**	**1300**	4275	1310

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Platform Notes

```
BIOS settings:
Virtualization Technology disabled
System Profile set to Custom
```

Continued on next page

Platform Notes (Continued)

```
CPU Performance set to Maximum Performance
C States set to autonomous
C1E disabled
Uncore Frequency set to Dynamic
Energy Efficiency Policy set to Performance
Memory Patrol Scrub disabled
CPU Interconnect Bus Link Power Management disabled
PCI ASPM L1 Link Power Management disabled
Sysinfo program /root/cpu2006-1.2/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on linux-z6tq Thu Feb 16 10:21:16 2017

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Genuine Intel(R) CPU 0000 @ 1.50GHz
      1 "physical id"s (chips)
      288 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 72
      siblings  : 288
      physical 0: cores 0 1 2 3 8 9 10 11 12 13 14 15 18 19 20 21 22 23 24 25 26
      27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 46 47 48 49 50 51 52 53
      54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75
   cache size : 1024 KB

From /proc/meminfo
   MemTotal:       396132044 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   SuSE-release:
      SUSE Linux Enterprise Server 12 (x86_64)
      VERSION = 12
      PATCHLEVEL = 2
      # This file is deprecated and will be removed in a future service pack or
      release.
      # Please check /etc/os-release for details about this release.
   os-release:
      NAME="SLES"
      VERSION="12-SP2"
      VERSION_ID="12.2"
      PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
      ID="sles"
      ANSI_COLOR="0;32"
      CPE_NAME="cpe:/o:suse:sles:12:sp2"
```

Continued on next page

Platform Notes (Continued)

```
uname -a:
   Linux linux-z6tq 4.4.16-56-default #1 SMP Mon Aug 8 14:24:26 UTC 2016
   (5b281a8) x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Feb 13 15:41

SPEC is set to: /root/cpu2006-1.2
   Filesystem     Type   Size  Used Avail Use% Mounted on
   /dev/sdb2      btrfs  930G  257G  671G  28% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS Dell Inc. 1.1.3 12/001/2016
  Memory:
   6x Hynix HMAA8GL7MMR4N-UH 64 GB 4 rank 2400 MHz
   8x INTEL N/A 2 GB 7200 MHz

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/root/cpu2006-1.2/libs/32:/root/cpu2006-1.2/libs/64:/root/cpu2006-1.2/sh"

 Binaries compiled on a system with
 Intel 2nd Generation Xeon Phi CPU
 with 96GB DDR4 RAM memory using RedHat EL 7.2
 Filesystem page cache cleared with:
 echo 1>       /proc/sys/vm/drop_caches
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
```

Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias

C++ benchmarks:
-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias

Fortran benchmarks:
-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias

Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks (except as noted below):
icpc -m64

450.soplex: icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Continued on next page

Peak Compiler Invocation (Continued)

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -D_FILE_OFFSET_BITS=64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1)
-opt-malloc-options=3

Continued on next page

Peak Optimization Flags (Continued)

453.povray: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1) -prof-use(pass 2) -par-num-threads=1(pass 1) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1) -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1) -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1) -prof-use(pass 2) -par-num-threads=1(pass 1) -opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64-revB.html
http://www.spec.org/cpu2006/flags/Dell-Platform-Flags-PowerEdge14G-revC.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64-revB.xml
http://www.spec.org/cpu2006/flags/Dell-Platform-Flags-PowerEdge14G-revC.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Aug 23 13:13:35 2017 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 22 August 2017.