SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR950 (Intel Xeon Platinum 8280L)

SPEChpc 2021_sml_base = 1.44

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2021
Hardware Availability: Apr-2019
Software Availability: Sep-2020



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	OMP	32	7	943	1.64	**947**	**1.64**	949	1.63									
613.soma_s	OMP	32	7	701	2.28	**701**	**2.28**	703	2.28									
618.tealeaf_s	OMP	32	7	**2474**	**0.829**	2474	0.829	2473	0.829									
619.clvleaf_s	OMP	32	7	**1923**	**0.858**	1923	0.858	1922	0.859									
621.miniswp_s	OMP	32	7	380	2.90	379	2.90	**379**	**2.90**									
628.pot3d_s	OMP	32	7	2081	0.805	**2086**	**0.803**	2086	0.803									
632.sph_exa_s	OMP	32	7	684	3.36	686	3.35	**685**	**3.36**									
634.hpgmgfv_s	OMP	32	7	1105	0.882	**1107**	**0.881**	1108	0.880									
635.weather_s	OMP	32	7	**1750**	**1.49**	1745	1.49	1756	1.48									

SPEChpc 2021_sml_base = 1.44

SPEChpc 2021_sml_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR950 (Intel Xeon Platinum 8280L)

SPEChpc 2021_sml_base = 1.44

SPEChpc 2021_sml_peak = Not Run

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2021
Hardware Availability: Apr-2019
Software Availability: Sep-2020

Hardware Summary

Type of System:	Homogenous
Compute Node:	ThinkSystem SR950
Interconnect:	N/A
Compute Nodes Used:	1
Total Chips:	8
Total Cores:	224
Total Threads:	224
Total Memory:	1536 GB
Max. Peak Threads:	--

Software Summary

Compiler:	Intel oneAPI C/C++/Fortran Compiler Version 2021.2.0 Build 20210228
MPI Library:	Intel oneAPI MPI Library for Linux* OS Version 2020 Version 2021.2 Build 20210302
Other MPI Info:	--
Other Software:	--
Base Parallel Model:	OMP
Base Ranks Run:	32
Base Threads Run:	7
Peak Parallel Models:	Not Run
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--
Max. Peak Threads:	--
Min. Peak Threads:	--

Node Description: ThinkSystem SR950

Hardware

Number of nodes:	1
Uses of the node:	compute
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR950
CPU Name:	Intel Xeon Platinum 8280L
CPU(s) orderable:	2,3,4,6,8 chips
Chips enabled:	8
Cores enabled:	224
Cores per chip:	28
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology up to 4.0 GHz
CPU MHz:	2700
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	39424 KB I+D on chip per chip
Other Cache:	None
Memory:	1536 GB (96 x 16 GB 2Rx8 PC4-2933Y-R)
Disk Subsystem:	1 x 960 GB NVME 2.5" SSD
Other Hardware:	None
Accel Count:	0
Accel Model:	None
Accel Vendor:	None
Accel Type:	None
Accel Connection:	None
Accel ECC enabled:	None
Accel Description:	None
Adapter:	None
Number of Adapters:	0
Slot Type:	None
Data Rate:	None

(Continued on next page)

Software

Accelerator Driver:	--
Adapter:	None
Adapter Driver:	None
Adapter Firmware:	None
Operating System:	Red Hat Enterprise Linux Server release 7.6, Kernel 3.10.0-957.el7.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Node Description: ThinkSystem SR950

Hardware (Continued)

Ports Used: 0
Interconnect Type: None

Interconnect Description: N/A

Hardware

Vendor: N/A
Model: N/A
Switch Model: N/A
Number of Switches: 0
Number of Ports: 0
Data Rate: N/A
Firmware: N/A
Topology: N/A
Primary Use: N/A

Software

: --

Submit Notes

```
The config file option 'submit' was used.
submit = mpirun -host localhost -genv coll_hcoll_enable 1 -genv HCOLL_MAIN_IB=mlx5_0:1
-genv UCX_TLS=sm -genv pml ucx --map-by numa -np $ranks $command
```

Compiler Version Notes

```
==============================================================================
 CC  605.lbm_s(base) 613.soma_s(base) 618.tealeaf_s(base) 621.miniswp_s(base)
      634.hpgmgfv_s(base)
------------------------------------------------------------------------------
Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 2021.2.0 Build 20210228_000000
Copyright (C) 1985-2021 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
 CXXC 632.sph_exa_s(base)
------------------------------------------------------------------------------
Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 2021.2.0 Build 20210228_000000
Copyright (C) 1985-2021 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
```

(Continued on next page)

Compiler Version Notes (Continued)

```
 FC  619.clvleaf_s(base) 628.pot3d_s(base) 635.weather_s(base)
------------------------------------------------------------------------------
Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
  64, Version 2021.2.0 Build 20210228_000000
Copyright (C) 1985-2021 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
mpiicc

C++ benchmarks:
mpiicpc

Fortran benchmarks:
mpiifort

Base Portability Flags

613.soma_s: -DSPEC_NO_VAR_ARRAY_REDUCE
621.miniswp_s: -DUSE_KBA -DUSE_ACCELDIR
632.sph_exa_s: -DSPEC_USE_LT_IN_KERNELS

Base Optimization Flags

C benchmarks:
-Ofast -xCORE-AVX512 -no-prec-div -ipo -qopenmp -ansi-alias

C++ benchmarks:
-Ofast -xCORE-AVX512 -no-prec-div -ipo -qopenmp -ansi-alias

Fortran benchmarks:
-Ofast -xCORE-AVX512 -no-prec-div -ipo -qopenmp

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2021-10-20.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2021-10-20.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.1 on 2020-08-26 08:39:23-0400.
Report generated on 2023-08-25 18:57:52 by hpc2021 PS formatter v1.0.3.
Originally published on 2021-10-20.