SPEChpc™ 2021 Tiny Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_tny_base = 16.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	MPI	320	1	122	18.5	**122**	**18.5**	122	18.4									
513.soma_t	MPI	320	1	**192**	**19.3**	191	19.4	195	19.0									
518.tealeaf_t	MPI	320	1	129	12.8	**131**	**12.6**	133	12.4									
519.clvleaf_t	MPI	320	1	**141**	**11.7**	141	11.7	141	11.7									
521.miniswp_t	MPI	320	1	**128**	**12.5**	128	12.5	128	12.5									
528.pot3d_t	MPI	320	1	198	10.7	**199**	**10.7**	199	10.7									
532.sph_exa_t	MPI	320	1	71.5	27.3	**71.0**	**27.5**	71.0	27.5									
534.hpgmgfv_t	MPI	320	1	**103**	**11.4**	103	11.4	102	11.5									
535.weather_t	MPI	320	1	63.2	51.1	63.8	50.6	**63.4**	**50.9**									

SPEChpc 2021_tny_base = 16.9

SPEChpc 2021_tny_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Tiny Result

Copyright 2021-2022 Standard Performance Evaluation Corporation

xFusion

FusionServer 2288H V6 (Intel Xeon Platinum 8380)

SPEChpc 2021_tny_base = 16.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jul-2022
Hardware Availability: Apr-2021
Software Availability: Oct-2021

Hardware Summary

Type of System:	Homogeneous Cluster
Compute Node:	FusionServer 2288H V6
Interconnect:	Mellanox HDR
Compute Nodes Used:	4
Total Chips:	8
Total Cores:	320
Total Threads:	320
Total Memory:	1 TB
Max. Peak Threads:	--

Software Summary

Compiler:	Intel oneAPI Compiler 2021.4.0
MPI Library:	Intel MPI Library for Linux* OS, Version 2021.4.0 Build 20210831
Other MPI Info:	--
Other Software:	--
Base Parallel Model:	MPI
Base Ranks Run:	320
Base Threads Run:	1
Peak Parallel Models:	Not Run
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--
Max. Peak Threads:	--
Min. Peak Threads:	--

Node Description: FusionServer 2288H V6

Hardware

Number of nodes:	4
Uses of the node:	Compute
Vendor:	xFusion
Model:	FusionServer 2288H V6
CPU Name:	Intel Xeon Platinum 8380
CPU(s) orderable:	1, 2 chips
Chips enabled:	2
Cores enabled:	80
Cores per chip:	40
Threads per core:	1
CPU Characteristics:	Turbo Boost Technology up to 3.4 GHz
CPU MHz:	2300
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	1.25 MB I+D on chip per core
L3 Cache:	60 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx8 PC4-3200R)
Disk Subsystem:	2 x 480 GB SATA 2.5" SSD (RAID 1)
Other Hardware:	None
Accel Count:	None
Accel Model:	--
Accel Vendor:	None
Accel Type:	None
Accel Connection:	None
Accel ECC enabled:	None
Accel Description:	None
Adapter:	MCX653105A-EFAT
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	100 Gb/s
Ports Used:	1

(Continued on next page)

Software

Accelerator Driver:	--
Adapter:	MCX653105A-EFAT
Adapter Driver:	5.4-3.1.0
Adapter Firmware:	20.32.1010
Operating System:	CentOS Linux release 8.2.2004 4.18.0-193.el8.x86_644
Local File System:	xfs
Shared File System:	NFS
System State:	Multi-user, run level 3
Other Software:	None

Node Description: FusionServer 2288H V6

Hardware (Continued)

Interconnect Type: Mellanox HDR

Interconnect Description: Mellanox HDR

Hardware

Vendor:	Mellanox
Model:	Mellanox HDR
Switch Model:	Mellanox MQM8790-HS2F InfiniBand Switch
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gbit/s
Firmware:	--
Topology:	Mesh
Primary Use:	MPI Traffic

Software

: --

Submit Notes

```
The config file option 'submit' was used.
export LD_PRELOAD="/usr/lib64/libhugetlbfs.so $LD_PRELOAD"
MPI startup command:
mpiexec.hydra -bootstrap ssh -hostfile $[top]/4node --bind-to core -np $ranks -ppn $ppn $command
```

Compiler Version Notes

```
==============================================================================
 CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
     534.hpgmgfv_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2021.4.0 (2021.4.0.20210924)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /home/opt/compiler/oneapi/2021.4.0/compiler/2021.4.0/linux/bin
------------------------------------------------------------------------------

==============================================================================
 CXXC 532.sph_exa_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2021.4.0 (2021.4.0.20210924)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /home/opt/compiler/oneapi/2021.4.0/compiler/2021.4.0/linux/bin
```

(Continued on next page)

Compiler Version Notes (Continued)

```
------------------------------------------------------------------------------

==============================================================================
 FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
------------------------------------------------------------------------------
ifx (IFORT) 2021.4.0 Beta 20210924
Copyright (C) 1985-2021 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx -lstdc++(*)`

C++ benchmarks:
`mpiicpc -cxx=icx -lstdc++(*)`

Fortran benchmarks:
`mpiifort -fc=ifx -lstdc++(*)`

(*) Indicates a compiler flag that was found in a non-compiler variable.

Base Portability Flags

513.soma_t: `-DSPEC_NO_VAR_ARRAY_REDUCE`

Base Optimization Flags

C benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

Fortran benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -nostandard-realloc-lhs -align array64byte`

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.3 on 2022-07-12 08:12:09-0400.
Report generated on 2022-08-24 18:40:32 by hpc2021 PS formatter v1.0.3.
Originally published on 2022-08-24.