SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_base = 8.12

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jan-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	MPI	120	1	227	9.90	**225**	**10.0**	224	10.0									
513.soma_t	MPI	120	1	346	10.7	346	10.7	**346**	**10.7**									
518.tealeaf_t	MPI	120	1	**334**	**4.94**	333	4.95	335	4.93									
519.clvleaf_t	MPI	120	1	**331**	**4.98**	331	4.98	331	4.98									
521.miniswp_t	MPI	120	1	**213**	**7.53**	212	7.53	217	7.37									
528.pot3d_t	MPI	120	1	471	4.51	**471**	**4.51**	471	4.51									
532.sph_exa_t	MPI	120	1	135	14.4	135	14.4	**135**	**14.4**									
534.hpgmgfv_t	MPI	120	1	226	5.21	225	5.22	**225**	**5.21**									
535.weather_t	MPI	120	1	140	23.0	141	22.9	**141**	**23.0**									

SPEChpc 2021_tny_base = 8.12

SPEChpc 2021_tny_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_base = 8.12

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Jan-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022

Hardware Summary

Type of System:	Homogenous Cluster
Compute Node:	xFusion 2288H V7
Interconnect:	N/A
Compute Nodes Used:	1
Total Chips:	2
Total Cores:	120
Total Threads:	120
Total Memory:	1 TB
Max. Peak Threads:	--

Software Summary

Compiler:	Intel oneAPI Compiler 2022.2.1
MPI Library:	Intel MPI Library for Linux* OS, Version 2022.2.1 Build 20221020
Other MPI Info:	N/A
Other Software:	N/A
Base Parallel Model:	MPI
Base Ranks Run:	120
Base Threads Run:	1
Peak Parallel Models:	Not Run
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--
Max. Peak Threads:	--
Min. Peak Threads:	--

Node Description: xFusion 2288H V7

Hardware

Number of nodes:	1
Uses of the node:	Compute
Vendor:	xFusion
Model:	xFusion 2288H V7
CPU Name:	Intel Xeon Platinum 8490H
CPU(s) orderable:	2 chips
Chips enabled:	2
Cores enabled:	120
Cores per chip:	60
Threads per core:	1
CPU Characteristics:	Turbo Boost Technology up to 3.5 GHz
CPU MHz:	1900
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	112.5 MB I+D on chip per chip
Other Cache:	None
Memory:	1 TB (16 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem:	1 x 7.68 TB NVMe SSD
Other Hardware:	None
Accel Count:	--
Accel Model:	--
Accel Vendor:	--
Accel Type:	--
Accel Connection:	--
Accel ECC enabled:	--
Accel Description:	--
Adapter:	N/A
Number of Adapters:	0
Slot Type:	N/A
Data Rate:	N/A
Ports Used:	0

(Continued on next page)

Software

Accelerator Driver:	N/A
Adapter:	N/A
Adapter Driver:	N/A
Adapter Firmware:	N/A
Operating System:	CentOS Linux release 8.2.2004 4.18.0-193.el8.x86_644
Local File System:	xfs
Shared File System:	N/A
System State:	Multi-user, run level 3
Other Software:	N/A

Node Description: xFusion 2288H V7

Hardware (Continued)

Interconnect Type: N/A

Interconnect Description: N/A

Hardware

Vendor:	N/A
Model:	N/A
Switch Model:	N/A
Number of Switches:	0
Number of Ports:	0
Data Rate:	N/A
Firmware:	N/A
Topology:	N/A
Primary Use:	N/A

Software

: --

Submit Notes

```
The config file option 'submit' was used.
export LD_PRELOAD="/usr/lib64/libhugetlbfs.so $LD_PRELOAD"
export OMP_PROC_BIND=true
mpiexec.hydra -bootstrap ssh --bind-to core -np $ranks -genv OMP_NUM_THREADS=$threads $command
```

General Notes

```
Submitted_by: luxu <luxu@xfusion.com>
Submitted: Thu Jan 26 12:25:09 EST 2023
Submission: hpc2021-20230110-00157.sub
```

Compiler Version Notes

```
==============================================================================
 CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
     534.hpgmgfv_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /mnt/share/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm
------------------------------------------------------------------------------

==============================================================================
```

(Continued on next page)

Compiler Version Notes (Continued)

```
 CXXC 532.sph_exa_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /mnt/share/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm
------------------------------------------------------------------------------

==============================================================================
 FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
------------------------------------------------------------------------------
ifx (IFORT) 2022.1.0 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

C++ benchmarks:
`mpiicpc -cxx=icx`

Fortran benchmarks:
`mpiifort -fc=ifx`

Base Portability Flags

505.lbm_t: `-lstdc++`
513.soma_t: `-lstdc++ -DSPEC_NO_VAR_ARRAY_REDUCE`
518.tealeaf_t: `-lstdc++`
519.clvleaf_t: `-lstdc++`
521.miniswp_t: `-lstdc++`
528.pot3d_t: `-lstdc++`
532.sph_exa_t: `-lstdc++`
534.hpgmgfv_t: `-lstdc++`
535.weather_t: `-lstdc++`

Base Optimization Flags

C benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -ansi-alias`

Fortran benchmarks:
`-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp -nostandard-realloc-lhs -align array64byte`

Base Other Flags

C benchmarks (except as noted below):
`-Ispecmpitime`

521.miniswp_t: `-Ispecmpitime/`

534.hpgmgfv_t: `-Ispecmpitime`

C++ benchmarks:
`-Ispecmpitime`

Fortran benchmarks:

519.clvleaf_t: `-Ispecmpitime`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.2023-01-27.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.2023-01-27.xml`

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-01-10 07:57:28-0500.
Report generated on 2023-01-27 19:55:15 by hpc2021 PS formatter v1.0.3.
Originally published on 2023-01-27.