SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR655 V3 (AMD EPYC 9654P)

SPEChpc 2021_tny_base = 6.99

SPEChpc 2021_tny_peak = 6.99

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Feb-2023
Software Availability: Feb-2023



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	12	16	**236**	**9.55**	244	9.24	227	9.91	OMP	12	16	**236**	**9.55**	244	9.24	227	9.91
513.soma_t	OMP	12	16	260	14.2	**260**	**14.2**	264	14.0	OMP	12	16	260	14.2	**260**	**14.2**	264	14.0
518.tealeaf_t	OMP	12	16	**458**	**3.60**	459	3.59	458	3.60	OMP	12	16	**458**	**3.60**	459	3.59	458	3.60
519.clvleaf_t	OMP	12	16	464	3.56	463	3.56	**463**	**3.56**	OMP	12	16	464	3.56	463	3.56	**463**	**3.56**
521.miniswp_t	OMP	12	16	190	8.42	189	8.45	**189**	**8.45**	OMP	12	16	190	8.42	189	8.45	**189**	**8.45**
528.pot3d_t	OMP	12	16	660	3.22	**659**	**3.22**	658	3.23	OMP	12	16	660	3.22	**659**	**3.22**	658	3.23
532.sph_exa_t	OMP	12	16	**252**	**7.73**	252	7.74	254	7.68	OMP	12	16	**252**	**7.73**	252	7.74	254	7.68
534.hpgmgfv_t	OMP	12	16	268	4.38	**268**	**4.39**	267	4.40	OMP	12	16	268	4.38	**268**	**4.39**	267	4.40
535.weather_t	OMP	12	16	**130**	**24.8**	130	24.9	130	24.7	OMP	12	16	**130**	**24.8**	130	24.9	130	24.7

SPEChpc 2021_tny_base = 6.99

SPEChpc 2021_tny_peak = 6.99

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR655 V3 (AMD EPYC 9654P)

SPEChpc 2021_tny_base = 6.99

SPEChpc 2021_tny_peak = 6.99

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Feb-2023
Software Availability: Feb-2023

Hardware Summary

Type of System:	Homogeneous Cluster
Compute Node:	ThinkSystem SR655 V3
Interconnect:	Nvidia Mellanox ConnectX-6 HDR
Compute Nodes Used:	1
Total Chips:	1
Total Cores:	96
Total Threads:	192
Total Memory:	768 GB
Max. Peak Threads:	16

Software Summary

Compiler:	Intel oneAPI Compiler 2022.1.0
MPI Library:	Intel MPI Library for Linux OS, Build 20220227
Other MPI Info:	--
Other Software:	--
Base Parallel Model:	OMP
Base Ranks Run:	12
Base Threads Run:	16
Peak Parallel Models:	OMP
Minimum Peak Ranks:	12
Maximum Peak Ranks:	12
Max. Peak Threads:	16
Min. Peak Threads:	16

Node Description: ThinkSystem SR655 V3

Hardware

Number of nodes:	1
Uses of the node:	Compute
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR655 V3
CPU Name:	AMD EPYC 9654P
CPU(s) orderable:	1 chips
Chips enabled:	1
Cores enabled:	96
Cores per chip:	96
Threads per core:	2
CPU Characteristics:	Max Boost Clock up to 3.7 GHz
CPU MHz:	2400
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	384 MB I+D on chip per chip 32 MB shared / 8 cores
Other Cache:	None
Memory:	768 GB (12 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem:	1x ThinkSystem 2.5" 5300 480GB SSD
Other Hardware:	None
Accel Count:	--
Accel Model:	--
Accel Vendor:	--
Accel Type:	--
Accel Connection:	--
Accel ECC enabled:	--
Accel Description:	--
Adapter:	Nvidia Mellanox ConnectX-6 HDR
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gb/s
Ports Used:	1

(Continued on next page)

Software

Accelerator Driver:	--
Adapter:	Nvidia Mellanox ConnectX-6 HDR
Adapter Driver:	5.7-1.0.2
Adapter Firmware:	20.28.1002
Operating System:	Red Hat Enterprise Linux Server release 8.6, Kernel 4.18.0-372.9.1.el8.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Node Description: ThinkSystem SR655 V3

Hardware (Continued)

Interconnect Type: ConnectX-6 HDR

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR

Hardware

Vendor:	Nvidia
Model:	Nvidia Mellanox ConnectX-6 HDR
Switch Model:	QM8700
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gb/s
Firmware:	3.9.0606
Topology:	Mesh
Primary Use:	MPI Traffic, NFS Access

Software

: --

Submit Notes

```
The config file option 'submit' was used.
submit = mpiexec -hostfile $[top]/6nodes -np ranks -genv OMP_NUM_THREADS=$threads -ppn %{NRNK} $command
```

Compiler Version Notes

```
==============================================================================
 FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
ifx: command line error: no files specified; for help type "ifx -help"
------------------------------------------------------------------------------

==============================================================================
 CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
      534.hpgmgfv_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
clang: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
==============================================================================
 CXXC 532.sph_exa_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
clang: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

C++ benchmarks:
`mpiicpc -cxx=icx`

Fortran benchmarks:
`mpiifort -fc=ifx`

Base Portability Flags

505.lbm_t: `-lstdc++`
513.soma_t: `-lstdc++ -DSPEC_NO_VAR_ARRAY_REDUCE`
518.tealeaf_t: `-lstdc++`
519.clvleaf_t: `-lstdc++`
521.miniswp_t: `-lstdc++`
528.pot3d_t: `-lstdc++`
532.sph_exa_t: `-lstdc++`
534.hpgmgfv_t: `-lstdc++`
535.weather_t: `-lstdc++`

Base Optimization Flags

C benchmarks:
`-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp`

(Continued on next page)

Base Optimization Flags (Continued)

C++ benchmarks (continued):
`-ansi-alias`

Fortran benchmarks:
`-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp -nostandard-realloc-lhs -align array64byte`

Base Other Flags

C benchmarks (except as noted below):
`-Ispecmpitime`

521.miniswp_t: `-Ispecmpitime/`

534.hpgmgfv_t: `-Ispecmpitime`

C++ benchmarks:
`-Ispecmpitime`

Fortran benchmarks:

519.clvleaf_t: `-Ispecmpitime`

Peak Optimization Flags

C benchmarks:

505.lbm_t: `basepeak = yes`

513.soma_t: `basepeak = yes`

518.tealeaf_t: `basepeak = yes`

521.miniswp_t: `basepeak = yes`

534.hpgmgfv_t: `basepeak = yes`

C++ benchmarks:

532.sph_exa_t: `basepeak = yes`

(Continued on next page)

Peak Optimization Flags (Continued)

Fortran benchmarks:

519.clvleaf_t: `basepeak = yes`

528.pot3d_t: `basepeak = yes`

535.weather_t: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.xml`

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2018-06-24 13:00:30-0400.
Report generated on 2023-02-22 12:25:48 by hpc2021 PS formatter v1.0.3.
Originally published on 2023-02-22.