SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_tny_base = 38.2

SPEChpc 2021_tny_peak = 38.2

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	72	8	48.0	46.8	**43.4**	**51.8**	42.2	53.3	OMP	72	8	48.0	46.8	**43.4**	**51.8**	42.2	53.3
513.soma_t	OMP	72	8	**79.5**	**46.5**	78.7	47.0	83.2	44.5	OMP	72	8	**79.5**	**46.5**	78.7	47.0	83.2	44.5
518.tealeaf_t	OMP	72	8	**21.3**	**77.3**	21.1	78.1	21.9	75.5	OMP	72	8	**21.3**	**77.3**	21.1	78.1	21.9	75.5
519.clvleaf_t	OMP	72	8	76.4	21.6	100	16.4	**87.7**	**18.8**	OMP	72	8	76.4	21.6	100	16.4	**87.7**	**18.8**
521.miniswp_t	OMP	72	8	**68.4**	**23.4**	67.9	23.6	68.4	23.4	OMP	72	8	**68.4**	**23.4**	67.9	23.6	68.4	23.4
528.pot3d_t	OMP	72	8	60.9	34.9	**60.8**	**34.9**	60.0	35.4	OMP	72	8	60.9	34.9	**60.8**	**34.9**	60.0	35.4
532.sph_exa_t	OMP	72	8	**81.2**	**24.0**	81.7	23.9	81.0	24.1	OMP	72	8	**81.2**	**24.0**	81.7	23.9	81.0	24.1
534.hpgmgfv_t	OMP	72	8	55.1	21.3	53.0	22.2	**54.0**	**21.8**	OMP	72	8	55.1	21.3	53.0	22.2	**54.0**	**21.8**
535.weather_t	OMP	72	8	27.6	117	**27.6**	**117**	28.3	114	OMP	72	8	27.6	117	**27.6**	**117**	28.3	114

SPEChpc 2021_tny_base = 38.2

SPEChpc 2021_tny_peak = 38.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR665 V3 (AMD EPYC 9654)

SPEChpc 2021_tny_base = 38.2

SPEChpc 2021_tny_peak = 38.2

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Jan-2023
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Hardware Summary

Type of System:	Homogeneous Cluster
Compute Node:	ThinkSystem SR665 V3
Interconnect:	Nvidia Mellanox ConnectX-6 HDR
Compute Nodes Used:	3
Total Chips:	6
Total Cores:	576
Total Threads:	1152
Total Memory:	4608 GB
Max. Peak Threads:	8

Software Summary

Compiler:	Intel oneAPI Compiler 2022.1.0
MPI Library:	Intel MPI Library for Linux OS, Build 20220227
Other MPI Info:	--
Other Software:	--
Base Parallel Model:	OMP
Base Ranks Run:	72
Base Threads Run:	8
Peak Parallel Models:	OMP
Minimum Peak Ranks:	72
Maximum Peak Ranks:	72
Max. Peak Threads:	8
Min. Peak Threads:	8

Node Description: ThinkSystem SR665 V3

Hardware

Number of nodes:	3
Uses of the node:	Compute
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR665 V3
CPU Name:	AMD EPYC 9654
CPU(s) orderable:	1,2 chips
Chips enabled:	2
Cores enabled:	192
Cores per chip:	96
Threads per core:	2
CPU Characteristics:	Max Boost Clock up to 3.7 GHz
CPU MHz:	2400
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	384 MB I+D on chip per chip 32 MB shared / 8 cores
Other Cache:	None
Memory:	1536 GB (24 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem:	1x ThinkSystem 2.5" 5300 480GB SSD
Other Hardware:	None
Accel Count:	--
Accel Model:	--
Accel Vendor:	--
Accel Type:	--
Accel Connection:	--
Accel ECC enabled:	--
Accel Description:	--
Adapter:	Nvidia Mellanox ConnectX-6 HDR
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200 Gb/s
Ports Used:	1

(Continued on next page)

Software

Accelerator Driver:	--
Adapter:	Nvidia Mellanox ConnectX-6 HDR
Adapter Driver:	5.7-1.0.2
Adapter Firmware:	20.28.1002
Operating System:	Red Hat Enterprise Linux Server release 8.6, Kernel 4.18.0-372.9.1.el8.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Node Description: ThinkSystem SR665 V3

Hardware (Continued)

Interconnect Type: ConnectX-6 HDR

Interconnect Description: Nvidia Mellanox ConnectX-6 HDR

Hardware

Vendor:	Nvidia
Model:	Nvidia Mellanox ConnectX-6 HDR
Switch Model:	QM8700
Number of Switches:	1
Number of Ports:	40
Data Rate:	200 Gb/s
Firmware:	3.9.0606
Topology:	Mesh
Primary Use:	MPI Traffic, NFS Access

Software

: --

Submit Notes

```
The config file option 'submit' was used.
submit = mpiexec -hostfile $[top]/3nodes -np ranks -genv OMP_NUM_THREADS=$threads -ppn %{NRNK} $command
```

Compiler Version Notes

```
==============================================================================
 FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
ifx: command line error: no files specified; for help type "ifx -help"
------------------------------------------------------------------------------

==============================================================================
 CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
      534.hpgmgfv_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
clang: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
==============================================================================
 CXXC 532.sph_exa_t(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.1.0 Build 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
clang: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

C++ benchmarks:
`mpiicpc -cxx=icx`

Fortran benchmarks:
`mpiifort -fc=ifx`

Base Portability Flags

505.lbm_t: `-lstdc++`
513.soma_t: `-lstdc++ -DSPEC_NO_VAR_ARRAY_REDUCE`
518.tealeaf_t: `-lstdc++`
519.clvleaf_t: `-lstdc++`
521.miniswp_t: `-lstdc++`
528.pot3d_t: `-lstdc++`
532.sph_exa_t: `-lstdc++`
534.hpgmgfv_t: `-lstdc++`
535.weather_t: `-lstdc++`

Base Optimization Flags

C benchmarks:
`-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp`

(Continued on next page)

Base Optimization Flags (Continued)

C++ benchmarks (continued):
-ansi-alias

Fortran benchmarks:
-Ofast -mprefer-vector-width=512 -march=core-avx2 -ipo -fiopenmp
-nostandard-realloc-lhs -align array64byte

Base Other Flags

C benchmarks (except as noted below):
-Ispecmpitime

521.miniswp_t: -Ispecmpitime/

534.hpgmgfv_t: -Ispecmpitime

C++ benchmarks:
-Ispecmpitime

Fortran benchmarks:

519.clvleaf_t: -Ispecmpitime

Peak Optimization Flags

C benchmarks:

505.lbm_t: basepeak = yes

513.soma_t: basepeak = yes

518.tealeaf_t: basepeak = yes

521.miniswp_t: basepeak = yes

534.hpgmgfv_t: basepeak = yes

C++ benchmarks:

532.sph_exa_t: basepeak = yes

(Continued on next page)

Peak Optimization Flags (Continued)

Fortran benchmarks:

519.clvleaf_t: `basepeak = yes`

528.pot3d_t: `basepeak = yes`

535.weather_t: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.xml`

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2018-06-22 22:36:55-0400.
Report generated on 2023-02-22 12:26:38 by hpc2021 PS formatter v1.0.3.
Originally published on 2023-02-22.