SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V3 (Intel Xeon Platinum 8490H, 1.90 GHz)

SPEChpc 2021_sml_base = 1.40

SPEChpc 2021_sml_peak = 1.40

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2023
Hardware Availability: Aug-2023
Software Availability: Jun-2023



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	MPI	480	1	**789**	**1.96**	786	1.97	791	1.96	MPI	480	1	**789**	**1.96**	786	1.97	791	1.96
613.soma_s	MPI	480	1	**1292**	**1.24**	1296	1.23	1292	1.24	MPI	480	1	**1292**	**1.24**	1296	1.23	1292	1.24
618.tealeaf_s	MPI	480	1	2445	0.839	2447	0.838	**2446**	**0.838**	MPI	480	1	2445	0.839	2447	0.838	**2446**	**0.838**
619.clvleaf_s	MPI	480	1	1877	0.879	**1877**	**0.879**	1876	0.880	MPI	480	1	1877	0.879	**1877**	**0.879**	1876	0.880
621.miniswp_s	MPI	480	1	**553**	**1.99**	553	1.99	554	1.99	MPI	480	1	**553**	**1.99**	553	1.99	554	1.99
628.pot3d_s	MPI	480	1	**2063**	**0.812**	2064	0.812	2059	0.813	MPI	480	1	**2063**	**0.812**	2064	0.812	2059	0.813
632.sph_exa_s	MPI	480	1	**534**	**4.31**	533	4.31	535	4.30	MPI	480	1	**534**	**4.31**	533	4.31	535	4.30
634.hpgmgfv_s	MPI	480	1	1059	0.920	**1055**	**0.924**	1055	0.925	MPI	480	1	1059	0.920	**1055**	**0.924**	1055	0.925
635.weather_s	MPI	480	1	1457	1.78	1453	1.79	**1457**	**1.78**	MPI	480	1	1457	1.78	1453	1.79	**1457**	**1.78**
SPEChpc 2021_sml_base = 1.40																		
SPEChpc 2021_sml_peak = 1.40																		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V3 (Intel Xeon Platinum 8490H, 1.90 GHz)

SPEChpc 2021_sml_base = 1.40

SPEChpc 2021_sml_peak = 1.40

hpc2021 License: 28
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: Aug-2023
Hardware Availability: Aug-2023
Software Availability: Jun-2023

Hardware Summary

Type of System:	SMP
Compute Node:	ThinkSystem SR860 V3
Compute Nodes Used:	1
Total Chips:	4
Total Cores:	240
Total Threads:	480
Total Memory:	2 TB
Max. Peak Threads:	1

Software Summary

Compiler:	Intel oneAPI Compiler 2022.1.0
MPI Library:	Intel MPI Library for Linux OS, Build 20220227
Other MPI Info:	None
Other Software:	None
Base Parallel Model:	MPI
Base Ranks Run:	480
Base Threads Run:	1
Peak Parallel Models:	MPI
Minimum Peak Ranks:	480
Maximum Peak Ranks:	480
Max. Peak Threads:	1
Min. Peak Threads:	1

Node Description: ThinkSystem SR860 V3

Hardware

Number of nodes:	1
Uses of the node:	Compute
Vendor:	Lenovo Global Technology
Model:	ThinkSystem SR860 V3
CPU Name:	Intel Xeon Platinum 8490H
CPU(s) orderable:	4 chips
Chips enabled:	4
Cores enabled:	240
Cores per chip:	60
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.5 GHz
CPU MHz:	1900
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	112.5 MB I+D on chip per chip
Other Cache:	None
Memory:	2 TB (32 x 64 GB 2Rx4 PC5-4800V)
Disk Subsystem:	1x ThinkSystem 2.5" 5300 480GB SSD
Other Hardware:	None
Accel Count:	None
Accel Model:	None
Accel Vendor:	None
Accel Type:	None
Accel Connection:	None
Accel ECC enabled:	None
Accel Description:	None
Adapter:	None
Number of Adapters:	0
Slot Type:	None
Data Rate:	None
Ports Used:	0
Interconnect Type:	None

Software

Accelerator Driver:	None
Adapter:	None
Adapter Driver:	None
Adapter Firmware:	None
Operating System:	Red Hat Enterprise Linux Server release 8.6, Kernel 4.18.0-372.9.1.el8.x86_64
Local File System:	xfs
Shared File System:	None
System State:	Multi-user, run level 3
Other Software:	None

Submit Notes

```
The config file option 'submit' was used.
```

Compiler Version Notes

```
==============================================================================
 FC  619.clvleaf_s(base) 628.pot3d_s(base) 635.weather_s(base)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2022.2.0 Build 20220730
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
ifx: command line error: no files specified; for help type "ifx -help"
------------------------------------------------------------------------------

==============================================================================
 CC  605.lbm_s(base) 613.soma_s(base) 618.tealeaf_s(base) 621.miniswp_s(base)
      634.hpgmgfv_s(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.2.0 Build 20220730
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
icx: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------

==============================================================================
 CXXC 632.sph_exa_s(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2022.2.0 Build 20220730
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
icx: warning: -Z-reserved-lib-stdc++: 'linker' input unused
  [-Wunused-command-line-argument]
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
```
mpiicc -cc=icx
```

C++ benchmarks:
```
mpiicpc -cxx=icx
```

Fortran benchmarks:
```
mpiifort  -fc=ifx
```

Base Portability Flags

605.lbm_s: `-lstdc++`
613.soma_s: `-lstdc++`
618.tealeaf_s: `-lstdc++`
619.clvleaf_s: `-lstdc++`
621.miniswp_s: `-lstdc++`
628.pot3d_s: `-lstdc++`
632.sph_exa_s: `-lstdc++`
634.hpgmgfv_s: `-lstdc++`
635.weather_s: `-lstdc++`

Base Optimization Flags

C benchmarks:
`-Ofast -mprefer-vector-width=512 -xCORE-AVX512 -ipo -ansi-alias`

C++ benchmarks:
`-Ofast -mprefer-vector-width=512 -xCORE-AVX512 -ipo -ansi-alias`

Fortran benchmarks:
`-Ofast -mprefer-vector-width=512 -xCORE-AVX512 -ipo`
`-nostandard-realloc-lhs -align array64byte`

Peak Optimization Flags

C benchmarks:

605.lbm_s: `basepeak = yes`

613.soma_s: `basepeak = yes`

618.tealeaf_s: `basepeak = yes`

621.miniswp_s: `basepeak = yes`

634.hpgmgfv_s: `basepeak = yes`

C++ benchmarks:

632.sph_exa_s: `basepeak = yes`

Fortran benchmarks:

(Continued on next page)

Peak Optimization Flags (Continued)

619.clvleaf_s: `basepeak = yes`

628.pot3d_s: `basepeak = yes`

635.weather_s: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2022-11-10.xml`

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-27 23:54:15-0400.
Report generated on 2023-09-26 13:14:33 by hpc2021 PS formatter v1.0.3.
Originally published on 2023-09-26.